

Lumi United Technology Co., Ltd.

CE TEST REPORT

SCOPE OF WORK:

Article 3.1a health of RE directive (2014/53/EU) – EMF report

Model:

HM1S-G01

REPORT NUMBER

200702409SHA-005

ISSUE DATE

August 31, 2020

DOCUMENT CONTROL NUMBER

TTRF62311_V1

© 2018 Intertek



Applicant : Lumi United Technology Co., Ltd.
8th Floor, JinQi Wisdom Valley, No.1 Tangling Road, Liuxian Ave,
Taoyuan Residential District, Nanshan District, Shenzhen. China

Manufacturer : Same as applicant

Manufacturing site : GUANGDONG NEW ENERGY TECHNOLOGY CO., LTD.
Floor1-4, Building 2, No.197 plant, East Side of Xinhua Road,
Tongqiao Town, Zhongkai High-tech Zone, Huizhou, Guangdong,
516032, China

Summary

The equipment complies with the requirements according to the following standard(s) or Specification:

1999/519/EC: COUNCIL RECOMMENDATION of 12 July 1999 on the limitation of exposure of the general public to electromagnetic fields (0 Hz to 300 GHz)

EN 50665:2017: Generic standard for assessment of electronic and electrical equipment related to human exposure restrictions for electromagnetic fields (0 Hz - 300 GHz)

EN 62311: 2008: Assessment of electronic and electrical equipment related to human exposure restrictions for electromagnetic fields (0 Hz - 300 GHz)

PREPARED BY:

REVIEWED BY:



Project Engineer
Eric Li

Reviewer
Wakeyou Wang

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Revision History

Report No.	Version	Description	Issued Date
200702409SHA-005	Rev. 01	Initial issue of report	August 31, 2020

Appendix I

According to assessment method & relevant limit showed in Appendix III of this report, the MPE limit for the frequency higher than 2GHz is 10W/m² (namely 1mW/cm²).

Power density (S) is calculated according to the formula:

$$S = P / (4\pi R^2)$$

Where S = power density in mW/cm²

P = Radiated transmit power in mW

G = numeric gain of transmit antenna

R = distance (cm)

As we can see from the test report 200702409SHA-001&200702409SHA-002:

Mode	Frequency Bands (MHz)	P (dBm)	P (mW)	R (cm)	S (mW/cm ²)	Limit (mW/cm ²)
WIFI	2400~2483.5	17.12	51.52	20	0.0103	1
Zigbee	2400~2483.5	9.57	9.06	20	0.0018	1

Consider all radio transmitters co-located with each module may increase the RF exposure level, the worst configuration is the WIFI+Zigbee, then the max S (power density) is 0.0103+0.0005= 0.0121 mW/cm².

Conclusion: This device complies with requirements of 2014/53/EU (Article 3.1a, human exposure to Electromagnetic Fields).

Appendix II

Definition below must be outlined in the User Manual:

To satisfy RF exposure requirements, a separation distance of **20 cm** or more should be maintained between this device and persons during device operation.

To ensure compliance, operations at closer than this distance is not recommended. The antenna used for this transmitter must not be co-located in conjunction with any other antenna or transmitter

Appendix III

Assessment methods & Limit for Electromagnetic Exposure Evaluation

Assessment methods:

- Far field calculation
- Near field calculation
- Simulation with/without a phantom
- Numerical modeling
- Body/limb current
- SAR
- E and H measurement
- Source modeling
- Direct measurement of physical properties: Contact current

Reference levels for electric, magnetic and electromagnetic fields (Table 2 of 1999/519/EC)

Frequency range	E-field strength (V/m)	H-field strength (A/m)	B-field (uT)	Equivalent plane wave power density S_{eq} (W/m ²)
0-1 Hz	-	$3,2 \times 10^4$	4×10^4	-
1-8 Hz	10 000	$3,2 \times 10^4/f^2$	$4 \times 10^4/f^2$	-
8-25 Hz	10 000	$4\ 000/f$	$5\ 000/f$	-
0,025-0,8 kHz	$250/f$	$4/f$	$5/f$	-
0,8-3 kHz	$250/f$	5	6,25	-
3-150 kHz	87	5	6,25	-
0,15-1 MHz	87	$0,73/f$	$0,92/f$	-
1-10 MHz	$87/f^{1/2}$	$0,73/f$	$0,92/f$	-
10-400 MHz	28	0,073	0,092	2
400-2 000 MHz	$1,375 f^{1/2}$	$0,0037 f^{1/2}$	$0,0046 f^{1/2}$	$f/200$
2-300 GHz	61	0,16	0,20	10

Notes:

1. *f* as indicated in the frequency range column.
2. For frequencies between 100 kHz and 10 GHz, S_{eq} , E^2 , H^2 , and B^2 are to be averaged over any six-minute period.
3. For frequencies exceeding 10 GHz, S_{eq} , E^2 , H^2 , and B^2 are to be averaged over any $68/f^{1.05}$ - minute period (*f* in GHz).
4. No E-field value is provided for frequencies < 1 Hz, which are effectively static electric fields. For most people the annoying perception of surface electric charges will not occur at field strengths less than 25 kV/m. Spark discharges causing stress or annoyance should be avoided.
5. The shading grid stands for the applied limit in this report.

***** END *****