

CE SAR EVALUATION REPORT

**In accordance with the requirements of
EN50360, EN50566, EN62209-1/-2, EN62479 and COUNCIL
RECOMMENDATION 1999/519/EC**

Product Name : Smart Phone

Trademark : Blackview

Model Name : BL8800 Pro

Family Model : BL8800

Report No. : STR220218001014E

Prepared for

DOKE COMMUNICATION (HK) LIMITED.

RM 1902 EASEY COMM BLDG 253-261 HENNESSY ROAD WANCHAI
HK CHINA.

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.

1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street,
Bao'an District, Shenzhen 518126 P.R.China.

Tel. 400-800-6106, 0755-2320 0050, 0755-2320 0090

Website: <http://www.ntek.org.cn>

TEST RESULT CERTIFICATION

Applicant's name : DOKE COMMUNICATION (HK) LIMITED.

Address : RM 1902 EASEY COMM BLDG 253-261 HENNESSY ROAD
WANCHAI HK CHINA.

Manufacturer's Name : Shenzhen DOKE Electronic Co.,Ltd.

Address : Room 801, Building 3, 7th Industrial Zone, Yulv Community,
Yutang Street, Guangming District, Shenzhen City, Guangdong
Province, China.

Product description

Product name : Smart Phone

Trademark : Blackview

Model and/or type reference : BL8800 Pro

Family Model : BL8800

EN 50360:2017;

EN 50566:2017;

Standards : EN 62209-1:2016;

EN 62209-2:2010;

EN 62479:2010;

This device described above has been tested by Shenzhen NTEK. In accordance with the measurement methods and procedures specified in EN62209. Testing has shown that this device is capable of compliance with localized specific absorption rate (SAR) specified in COUNCIL 1999/519/EC. The test results in this report apply only to the tested sample of the stated device/equipment. Other similar device/equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

This report shall not be reproduced except in full, without the written approval of Shenzhen NTEK, this document may be altered or revised by Shenzhen NTEK, personal only, and shall be noted in the revision of the document.

Date of Test

Date (s) of performance of tests : Feb. 25, 2022 ~ Mar. 10, 2022

Date of Issue : Mar. 12, 2022

Test Result : **Pass**

Prepared By
(Test Engineer) : Jacob . chen
(Jacob Chen)

Approved By
(Lab Manager) : Alex
(Alex Li)

※ ※ Revision History ※ ※

REV.	DESCRIPTION	ISSUED DATE	REMARK
Rev.1.0	Initial Test Report Release	Mar. 12, 2022	Jacob Chen

TABLE OF CONTENTS

1.	General Information	6
1.1.	RF exposure limits	6
1.2.	Statement of Compliance.....	7
1.3.	7 EUT Description	7
1.4.	Test specification(s)	10
1.5.	Ambient Condition.....	10
2.	SAR Measurement System	11
2.1.	SATIMO SAR Measurement Set-up Diagram	11
2.2.	Robot	12
2.3.	E-Field Probe.....	13
2.3.1.	E-Field Probe Calibration.....	13
2.4.	SAM phantoms	14
2.4.1.	Technical Data	15
2.5.	Device Holder	16
2.6.	Test Equipment List	17
3.	SAR Measurement Procedures	19
3.1.	Power Reference.....	19
3.2.	Area scan & Zoom scan	19
3.3.	Description of interpolation/extrapolation scheme	20
3.4.	Volumetric Scan	20
3.5.	Power Drift	20
4.	System Verification Procedure.....	21
4.1.	Tissue Verification.....	21
4.1.1.	Tissue Dielectric Parameter Check Results	22
4.2.	System Verification Procedure	23
4.2.1.	System Verification Results	24
5.	SAR Measurement Uncertainty.....	25
6.	RF Exposure Positions	26
6.1.	Ear and handset reference point.....	26
6.2.	Definition of the cheek position.....	26
6.3.	Definition of the tilt position.....	28
6.4.	Body-worn device	28
7.	RF Output Power	29
7.1.	GSM Conducted Power	29
7.2.	WCDMA Conducted Power.....	30
7.3.	LTE Conducted Power.....	30
7.4.	NR Conducted Power	38
7.5.	WLAN & Bluetooth Output Power.....	50
8.	Assessment of the compliance of low power equipment.....	52

9. SAR Results	52
9.1. SAR measurement results	52
9.1.1. SAR measurement Result of GSM 900.....	52
9.1.2. SAR measurement Result of GSM 1800.....	53
9.1.3. SAR measurement Result of WCDMA Band 1.....	54
9.1.4. SAR measurement Result of WCDMA Band 8.....	54
9.1.5. SAR measurement Result of LTE Band 1	55
9.1.6. SAR measurement Result of LTE Band 3	55
9.1.7. SAR measurement Result of LTE Band 7	56
9.1.8. SAR measurement Result of LTE Band 8	57
9.1.9. SAR measurement Result of LTE Band 20	58
9.1.10. SAR measurement Result of LTE Band 28	59
9.1.11. SAR measurement Result of LTE Band 40	60
9.1.12. SAR measurement Result of NR N1	60
9.1.13. SAR measurement Result of NR N3	61
9.1.14. SAR measurement Result of NR N8	62
9.1.15. SAR measurement Result of NR N20	63
9.1.16. SAR measurement Result of NR N28	64
9.1.17. SAR measurement Result of NR N38	64
9.1.18. SAR measurement Result of NR N77	65
9.1.19. SAR measurement Result of NR N78	66
9.1.20. SAR measurement Result of WLAN 2.4G	67
9.1.21. SAR measurement Result of WLAN 5.2G	68
9.1.22. SAR measurement Result of WLAN 5.8G.....	69
9.2. Simultaneous Transmission Analysis	69
9.3. Exposure Conditions	70
10. Appendix A. Photo documentation	72
11. Appendix B. System Check Plots	74
12. Appendix C. Plots of High SAR Measurement	95
13. Appendix D. Calibration Certificate	185

1. General Information

1.1. RF exposure limits

(A).Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	10.0	20.0

(B).Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	2.0	4.0

NOTE: **Whole-Body SAR** is averaged over the entire body, **partial-body SAR** is averaged over any 10 gram of tissue defined as a tissue volume in the shape of a cube.

SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

Occupational/Controlled Environments:

Are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

General Population/Uncontrolled Environments:

Are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

NOTE

HEAD AND TRUNK LIMIT

2.0 W/kg AND MEMBER LIMIT 4.0 W/kg

APPLIED TO THIS EUT

1.2. Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for BL8800 Pro are as follows.

Max SAR Value(W/kg)			
RF Exposure Conditions	10-g Head	10-g Body & Hotspot (Separation distance of 5mm)	10-g Member DAS (See note ³) (Separation distance of 0mm)
	0.573	0.995	1.944
Max Simultaneous Tx	1.019	1.410	2.478

- NOTE: 1. The Max Simultaneous Tx is calculated based on the same configuration and test position.
 2. This device is in compliance with Specific Absorption Rate (SAR) for general population / uncontrolled exposure limits (2.0 W/kg for head and body, 4.0 W/kg for member) specified in COUNCIL RECOMMENDATION 1999/519/EC, and had been tested in accordance with the measurement methods and procedures specified in EN 62209-1:2016 & EN 62209-2:2010.
 3. The member DAS, It is only an assessment required by the ANFR (Sell to France).

1.3. 7 EUT Description

Device Information			
Product Name	Smart Phone		
Trademark	Blackview		
Model Name	BL8800 Pro		
Family Model	BL8800		
Device Phase	Identical Prototype		
Exposure Category	General population / Uncontrolled environment		
Antenna Type	PIFA Antenna		
Battery Information	DC 3.85V, 8380mAh, 32.263Wh		
Hardware version	TF929-B1-V1.1		
Software version	BL8800 Pro_EEA_TF929_V1.0		
Device Operating Configurations			
Supporting Mode(s)	GSM 900/1800, WCDMA Band 1/8, LTE Band 1/3/7/8/20/28/40, NR SA N1/N3/N8/N20/N28/N38/N77/N78, NR NSA N78+LTE Band 1, WLAN 2.4G/5G, Bluetooth, GPS, FM, NFC		
Test Modulation	GSM(GMSK/8PSK), WCDMA(QPSK), LTE(QPSK/16-QAM), NR(DFT-s-OFDM: Pi/2 BPSK, QPSK, 16QAM, 64QAM, 256QAM / CP-OFDM: QPSK, 16QAM, 64QAM, 256QAM), WLAN(DSSS/OFDM), Bluetooth(GFSK, π/4-DQPSK, 8DPSK), GPS(BPSK), FM(FM), NFC(ASK)		
Device Class	B		
Operating Frequency Range(s)	Band	Tx (MHz)	Rx (MHz)

	GSM 900	880-915	925-960
	GSM 1800	1710-1785	1805-1880
	WCDMA Band 1	1920-1980	2110-2170
	WCDMA Band 8	880-915	925-960
	LTE Band 1	1920-1980	2110-2170
	LTE Band 3	1710-1785	1805-1880
	LTE Band 7	2500-2570	2620-2690
	LTE Band 8	880- 915	925- 960
	LTE Band 20	832-862	791-821
	LTE Band 28	703-748	758-803
	LTE Band 40	2300-2400	
	NR N1	1920-1980	2110-2170
	NR N3	1710-1785	1805-1880
	NR N8	880-915	925-960
	NR N20	832-862	791-821
	NR N28	703-748	758-803
	NR N38	2570-2620	
	NR N77	3300-4200	
	NR N78	3300-3800	
	WLAN 2.4G	2412-2472	
	WLAN 5.2G	5180-5240	
	WLAN 5.8G	5745-5825	
	Bluetooth	2402-2480	
	NFC	13.56	
	FM	N/A	87.5-108
	GPS	N/A	1575.42
GPRS Multislot Class(12)	Max Number of Timeslots in Uplink		4
	Max Number of Timeslots in Downlink		4
	Max Total Timeslot		5
EGPRS Multislot Class(12)	Max Number of Timeslots in Uplink		4
	Max Number of Timeslots in Downlink		4
	Max Total Timeslot		5
Power Class	4, tested with power level 5(GSM 900)		
	1, tested with power level 0(GSM 1800)		
	3, tested with power control "all 1"(WCDMA Band 1)		
	3, tested with power control "all 1"(WCDMA Band 8)		
	3, tested with power control all Max.(LTE Band 1)		
	3, tested with power control all Max.(LTE Band 3)		
	3, tested with power control all Max.(LTE Band 7)		
	3, tested with power control all Max.(LTE Band 8)		

	3, tested with power control all Max.(LTE Band 20)
	3, tested with power control all Max.(LTE Band 28)
	3, tested with power control all Max.(LTE Band 40)
	3, tested with power control all Max.(NR N1)
	3, tested with power control all Max.(NR N3)
	3, tested with power control all Max.(NR N8)
	3, tested with power control all Max.(NR N20)
	3, tested with power control all Max.(NR N28)
	3, tested with power control all Max.(NR N38)
	3, tested with power control all Max.(NR N77)
	3, tested with power control all Max.(NR N78)

1.4. Test specification(s)


EN 50360:2017	Product standard to demonstrate the compliance of wireless communication devices, with the basic restrictions and exposure limit values related to human exposure to electromagnetic fields in the frequency range from 300 MHz to 6 GHz: devices used next to the ear
EN 50566:2017	Product standard to demonstrate the compliance of wireless communication devices with the basic restrictions and exposure limit values related to human exposure to electromagnetic fields in the frequency range from 30 MHz to 6 GHz: hand-held and body mounted devices in close proximity to the human body
EN 62209-1:2016	Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Part 1: Devices used next to the ear (Frequency range of 300 MHz to 6 GHz)
EN 62209-2:2010	Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices – Human models, instrumentation, and procedures –Part 2: Procedure to determine the Specific Absorption Rate (SAR) in the head and body for 30MHz to 6GHz Handheld and Body-Mounted Devices used in close proximity to the body
EN 62479:2010	Assessment of the compliance of low-power electronic and electrical equipment with the restrictions related to human exposure to electromagnetic fields(10 MHz to 300 GHz)

1.5. Ambient Condition

Ambient temperature	20°C – 24°C
Relative Humidity	30% – 70%

2. SAR Measurement System

2.1. SATIMO SAR Measurement Set-up Diagram



These measurements were performed with the automated near-field scanning system OPENSAR from SATIMO. The system is based on a high precision robot (working range: 901 mm), which positions the probes with a positional repeatability of better than ± 0.03 mm. The SAR measurements were conducted with dosimetric probe (manufactured by SATIMO), designed in the classical triangular configuration and optimized for dosimetric evaluation.

The first step of the field measurement is the evaluation of the voltages induced on the probe by the device under test. Probe diode detectors are nonlinear. Below the diode compression point, the output voltage is proportional to the square of the applied E-field; above the diode compression point, it is linear to the applied E-field. The compression point depends on the diode, and a calibration procedure is necessary for each sensor of the probe.

The Keithley multimeter reads the voltage of each sensor and send these three values to the PC. The corresponding E field value is calculated using the probe calibration factors, which are stored in the working directory. This evaluation includes linearization of the diode characteristics. The field calculation is done separately for each sensor. Each component of the E field is displayed on the "Dipole Area Scan Interface" and the total E field is displayed on the "3D Interface".

2.2. Robot

The SATIMO SAR system uses the high precision robots from KUKA. For the 6-axis controller system, the robot controller version (KUKA) from KUKA is used. The KUKA robot series have many features that are important for our application:



- High precision (repeatability ± 0.03 mm)
- High reliability (industrial design)
- Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)

2.3. E-Field Probe

This E-field detection probe is composed of three orthogonal dipoles linked to special Schottky diodes with low detection thresholds. The probe allows the measurement of electric fields in liquids such as the one defined in the IEEE and CENELEC standards.

For the measurements the Specific Dosimetric E-Field Probe SN 08/16 EPGO287 with following specifications is used



- Dynamic range: 0.01-100 W/kg
 - Tip Diameter : 2.5 mm
 - Distance between probe tip and sensor center: 1 mm
 - Distance between sensor center and the inner phantom surface: 2 mm (repeatability better than ± 1 mm).
 - Probe linearity: ± 0.08 dB
 - Axial isotropy: ± 0.01 dB
 - Hemispherical Isotropy: ± 0.01 dB
 - Calibration range: 650MHz to 5900MHz for head & body simulating liquid.
 - Lower detection limit: 8mW/kg
- Angle between probe axis (evaluation axis) and surface normal line: less than 30°.

2.3.1. E-Field Probe Calibration

Each probe needs to be calibrated according to a dosimetric assessment procedure with accuracy better than $\pm 10\%$. The spherical isotropy shall be evaluated and within ± 0.25 dB. The sensitivity parameters (Norm X, Norm Y, and Norm Z), the diode compression parameter (DCP) and the conversion factor (Conv F) of the probe are tested. The calibration data can be referred to appendix D of this report.

2.4. SAM phantoms


Photo of SAM phantom SN 16/15 SAM119



The SAM phantom is used to measure the SAR relative to people exposed to electro-magnetic field radiated by mobile phones.

2.4.1. Technical Data

Serial Number	Shell thickness	Filling volume	Dimensions	Positioner Material	Permittivity	Loss Tangent
SN 16/15 SAM119	2 mm ±0.2 mm	27 liters	Length:1000 mm Width:500 mm Height:200 mm	Gelcoat with fiberglass	3.4	0.02




Serial Number	Left Head(mm)		Right Head(mm)		Flat Part(mm)	
SN 16/15 SAM119	2	2.02	2	2.08	1	2.09
	3	2.05	3	2.06	2	2.06
	4	2.07	4	2.07	3	2.08
	5	2.08	5	2.08	4	2.10
	6	2.05	6	2.07	5	2.10
	7	2.05	7	2.05	6	2.07
	8	2.07	8	2.06	7	2.07
	9	2.08	9	2.06	-	-

The test, based on ultrasonic system, allows measuring the thickness with an accuracy of 10 µm.

2.5. Device Holder

The positioning system allows obtaining cheek and tilting position with a very good accuracy. In compliance with CENELEC, the tilt angle uncertainty is lower than 1 degree.



Serial Number	Holder Material	Permittivity	Loss Tangent
SN 16/15 MSH100	Delrin	3.7	0.005

2.6. Test Equipment List

This table gives a complete overview of the SAR measurement equipment.

Devices used during the test described are marked

	Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
					Last Cal.	Due Date
<input checked="" type="checkbox"/>	MVG	E FIELD PROBE	SSE2	SN 08/16 EPGO287	Feb. 01, 2022	Jan. 31, 2023
<input checked="" type="checkbox"/>	MVG	750 MHz Dipole	SID750	SN 03/15 DIP 0G750-355	Mar. 01, 2021	Feb. 28, 2024
<input type="checkbox"/>	MVG	835 MHz Dipole	SID835	SN 03/15 DIP 0G835-347	Mar. 01, 2021	Feb. 28, 2024
<input checked="" type="checkbox"/>	MVG	900 MHz Dipole	SID900	SN 03/15 DIP 0G900-348	Mar. 01, 2021	Feb. 28, 2024
<input checked="" type="checkbox"/>	MVG	1800 MHz Dipole	SID1800	SN 03/15 DIP 1G800-349	Mar. 01, 2021	Feb. 28, 2024
<input type="checkbox"/>	MVG	1900 MHz Dipole	SID1900	SN 03/15 DIP 1G900-350	Mar. 01, 2021	Feb. 28, 2024
<input checked="" type="checkbox"/>	MVG	2000 MHz Dipole	SID2000	SN 03/15 DIP 2G000-351	Mar. 01, 2021	Feb. 28, 2024
<input checked="" type="checkbox"/>	MVG	2300 MHz Dipole	SID2300	SN 03/16 DIP 2G300-358	Mar. 01, 2021	Feb. 28, 2024
<input checked="" type="checkbox"/>	MVG	2450 MHz Dipole	SID2450	SN 03/15 DIP 2G450-352	Mar. 01, 2021	Feb. 28, 2024
<input checked="" type="checkbox"/>	MVG	2600 MHz Dipole	SID2600	SN 03/15 DIP 2G600-356	Mar. 01, 2021	Feb. 28, 2024
<input checked="" type="checkbox"/>	MVG	3700 MHz Dipole	SID3700	SN 09/12 DIP 3G/700-361	Oct. 19 2020	Oct. 18 2023
<input checked="" type="checkbox"/>	MVG	5000 MHz Dipole	SWG5500	SN 13/14 WGA 33	Mar. 01, 2021	Feb. 28, 2024
<input checked="" type="checkbox"/>	MVG	Liquid measurement Kit	SCLMP	SN 21/15 OCPG 72	NCR	NCR
<input checked="" type="checkbox"/>	MVG	Power Amplifier	N.A	AMPLISAR_28/14_003	NCR	NCR
<input checked="" type="checkbox"/>	KEITHLEY	Millivoltmeter	2000	4072790	NCR	NCR
<input checked="" type="checkbox"/>	R&S	Universal radio communication tester	CMU200	117858	Jul. 01, 2021	Jun. 30, 2022
<input checked="" type="checkbox"/>	R&S	Wideband radio communication	CMW500	103917	Jul. 01, 2021	Jun. 30, 2022

		tester				
<input checked="" type="checkbox"/>	HP	Network Analyzer	8753D	3410J01136	Jul. 01, 2021	Jun. 30, 2022
<input checked="" type="checkbox"/>	Agilent	PSG Analog Signal Generator	E8257D	MY51110112	Jul. 01, 2021	Jun. 30, 2022
<input checked="" type="checkbox"/>	Agilent	Power meter	E4419B	MY45102538	Jul. 01, 2021	Jun. 30, 2022
<input checked="" type="checkbox"/>	Agilent	Power sensor	E9301A	MY41495644	Jul. 01, 2021	Jun. 30, 2022
<input checked="" type="checkbox"/>	Agilent	Power sensor	E9301A	US39212148	Jul. 01, 2021	Jun. 30, 2022
<input checked="" type="checkbox"/>	MCLI/USA	Directional Coupler	CB11-20	0D2L51502	Jul. 17, 2020	Jul. 16, 2023
<input checked="" type="checkbox"/>	Anritsu	Radio Communication Analyzer	MT8821C	SN 6262186364	Nov. 04, 2021	Nov. 03, 2022
<input checked="" type="checkbox"/>	Anritsu	Radio Communication Test Station	MT8000A	SN 6262192315	Nov. 04, 2021	Nov. 03, 2022

3. SAR Measurement Procedures

The measurement procedures are as follows:

- (a) Use base station simulator (if applicable) or engineering software to transmit RF power continuously (continuous Tx) in the middle channel.
- (b) Keep EUT to radiate maximum output power or 100% duty factor (if applicable)
- (c) Measure output power through RF cable and power meter.
- (d) Place the EUT in the positions as setup photos demonstrates.
- (e) Set scan area, grid size and other setting on the OPENSAR software.
- (f) Measure SAR transmitting at the middle channel for all applicable exposure positions.
- (g) Identify the exposure position and device configuration resulting the highest SAR
- (h) Measure SAR at the lowest and highest channels at the worst exposure position and device configuration.

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

3.1. Power Reference

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

3.2. Area scan & Zoom scan

The area scan is a 2D scan to find the hot spot location on the DUT. The zoom scan is a 3D scan above the hot spot to calculate the 1g and 10g SAR value.

Measurement of the SAR distribution with a grid of 8 to 16 mm * 8 to 16 mm and a constant distance to the inner surface of the phantom. Since the sensors cannot directly measure at the inner phantom surface, the values between the sensors and the inner phantom surface are extrapolated. With these values the area of the maximum SAR is calculated by an interpolation scheme. Around this point, a cube of 30 * 30 * 30 mm or 32 * 32 * 32 mm is assessed by measuring 5 or 8 * 5 or 8 * 4 or 5 mm. With these data, the peak spatial-average SAR value can be calculated.

From the scanned SAR distribution, identify the position of the maximum SAR value, in addition identify the positions of any local maxima with SAR values within 2 dB of the maximum value that will not be within the zoom scan of other peaks; additional peaks shall be measured only when the primary peak is within 2 dB of the SAR compliance limit (e.g., 1 W/kg for 1,6 W/kg 1 g limit, or 1,26 W/kg for 2 W/kg, 10 g limit).

3.3. Description of interpolation/extrapolation scheme

The local SAR inside the phantom is measured using small dipole sensing elements inside a probe body. The probe tip must not be in contact with the phantom surface in order to minimise measurements errors, but the highest local SAR will occur at the surface of the phantom.

An extrapolation is used to determine these highest local SAR values. The extrapolation is based on a fourth-order least-square polynomial fit of measured data. The local SAR value is then extrapolated from the liquid surface with a 1 mm step.

The measurements have to be performed over a limited time (due to the duration of the battery) so the step of measurement is high. It could vary between 5 and 8 mm. To obtain an accurate assessment of the maximum SAR averaged over 10 grams and 1 gram requires a very fine resolution in the three dimensional scanned data array.

3.4. Volumetric Scan

The volumetric scan consists to a full 3D scan over a specific area. This 3D scan is useful for multi Tx SAR measurement. Indeed, it is possible with OpenSAR to add, point by point, several volumetric scans to calculate the SAR value of the combined measurement as it is defined in the standard IEEE1528 and IEC62209.

3.5. Power Drift

All SAR testing is under the EUT installed full charged battery and transmit maximum output power. In OpenSAR measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in V/m. If the power drifts more than $\pm 5\%$, the SAR will be retested.


4. System Verification Procedure

4.1. Tissue Verification

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

Ingredients (% of weight)	Head Tissue								
Frequency Band (MHz)	750	835	900	1800	1900	2000	2450	2600	5000
Water	34.40	34.40	34.40	55.36	55.36	71.88	71.88	71.88	65.53
NaCl	0.79	0.79	0.79	0.35	0.35	0.16	0.16	0.16	0.00
1,2-Propanediol	64.81	64.81	64.81	0.00	0.00	0.00	0.00	0.00	0.00
Triton X-100	0.00	0.00	0.00	30.45	30.45	19.97	19.97	19.97	17.24
DGBE	0.00	0.00	0.00	13.84	13.84	7.99	7.99	7.99	0.00

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid depth from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm.



4.1.1. Tissue Dielectric Parameter Check Results

The simulating liquids should be checked at the beginning of a series of SAR measurements to determine if the dielectric parameter are within the tolerances of the specified target values. The measured conductivity and relative permittivity should be within $\pm 5\%$ of the target values.


Tissue Type	Measured Frequency (MHz)	Target Tissue		Measured Tissue		Liquid Temp.	Test Date
		ϵ_r ($\pm 5\%$)	σ (S/m) ($\pm 5\%$)	ϵ_r	σ (S/m)		
Head 750	750	41.96 (39.86~44.06)	0.89 (0.85~0.93)	41.30	0.91	21.7 °C	Feb. 25, 2022
Head 900	900	41.50 (39.43~43.58)	0.97 (0.92~1.02)	41.49	0.99	21.3 °C	Mar. 07, 2022
Head 1800	1800	40.00 (38.00~42.00)	1.40 (1.33~1.47)	39.08	1.40	21.4 °C	Feb. 26, 2022
Head 2000	2000	40.00 (38.00~42.00)	1.40 (1.33~1.47)	41.34	1.38	21.3 °C	Feb. 28, 2022
Head 2300	2300	39.47 (37.50~41.44)	1.66 (1.58~1.74)	39.38	1.72	21.4 °C	Mar. 01, 2022
Head 2450	2450	39.20 (37.24~41.16)	1.80 (1.71~1.89)	38.94	1.81	21.2 °C	Mar. 02, 2022
Head 2600	2600	39.01 (37.06~40.96)	1.96 (1.86~2.06)	38.75	2.03	21.8 °C	Mar. 03, 2022
Head 3700	3700	37.70 (35.82~39.59)	3.12 (2.97~3.27)	37.87	3.04	21.7°C	Mar. 10, 2022
Head 5200	5200	36.00 (34.20~37.80)	4.66 (4.43~4.89)	36.74	4.77	21.2 °C	Mar. 08, 2022
Head 5800	5800	35.30 (33.54~37.07)	5.27 (5.01~5.53)	35.65	5.44	21.5 °C	Mar. 09, 2022

NOTE: The dielectric parameters of the tissue-equivalent liquid should be measured under similar ambient conditions and within 2 °C of the conditions expected during the SAR evaluation to satisfy protocol requirements.

4.2. System Verification Procedure

The system verification is performed for verifying the accuracy of the complete measurement system and performance of the software. The dipole is connected to the signal source consisting of signal generator and amplifier via a directional coupler, N-connector cable and adaption to SMA. It is fed with a power of 100mW (below 5GHz) or 100mW (above 5GHz). To adjust this power a power meter is used. The power sensor is connected to the cable before the system verification to measure the power at this point and do adjustments at the signal generator. At the outputs of the directional coupler both return loss as well as forward power are controlled during the system verification to make sure that emitted power at the dipole is kept constant. This can also be checked by the power drift measurement after the test (result on plot).

The system verification is shown as below picture:



4.2.1. System Verification Results

Comparing to the original SAR value provided by SATIMO, the verification data should be within its specification of $\pm 10\%$. Below table shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance verification can meet the variation criterion and the plots can be referred to Appendix B of this report.

System Verification	Target SAR (1W) ($\pm 10\%$)		Measured SAR (Normalized to 1W)		Liquid Temp.	Test Date
	1-g (W/Kg)	10-g (W/Kg)	1-g (W/Kg)	10-g (W/Kg)		
750MHz	8.53 (7.68~9.38)	5.56 (5.01~6.11)	8.66	5.95	21.7 °C	Feb. 25, 2022
900MHz	11.08 (9.98~12.18)	6.81 (6.13~7.49)	10.05	7.07	21.3 °C	Mar. 07, 2022
1800MHz	37.96 (34.17~41.75)	19.81 (17.83~21.79)	35.78	19.95	21.4 °C	Feb. 26, 2022
2000MHz	41.26 (37.14~45.38)	20.52 (18.47~22.57)	42.75	21.46	21.3 °C	Feb. 28, 2022
2300MHz	50.65 (45.59~55.71)	23.55 (21.20~25.90)	48.22	25.14	21.4 °C	Mar. 01, 2022
2450MHz	53.69 (48.33~59.05)	23.94 (21.55~26.33)	56.15	24.09	21.2 °C	Mar. 02, 2022
2600MHz	55.83 (50.25~61.41)	24.19 (21.78~26.60)	59.55	23.87	21.8 °C	Mar. 03, 2022
3700MHz	66.30 (59.67~72.93)	24.16 (22.96~26.57)	66.89	25.38	21.7°C	Mar. 10, 2022
5200MHz	162.34 (146.11~178.57)	55.42 (49.88~60.96)	171.12	59.90	21.2 °C	Mar. 08, 2022
5800MHz	178.89 (161.01~196.77)	59.32 (53.39~65.25)	170.07	62.36	21.5 °C	Mar. 09, 2022

5. SAR Measurement Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in IEEE 1528: 2003. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Uncertainty Component	Tol. (±%)	Prob. Dist.	Div.	Ci (1 g)	Ci (10 g)	1 g Ui (±%)	10 g Ui (±%)	Vi
Measurement System								
Probe Calibration	5.8	N	1	1	1	5.80	5.80	∞
Axial Isotropy	3.5	R	$\sqrt{3}$	0.7	0.7	1.43	1.43	∞
Hemispherical Isotropy	5.9	R	$\sqrt{3}$	0.7	0.7	2.41	2.41	∞
Boundary Effect	1	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Linearity	4.7	R	$\sqrt{3}$	1	1	2.71	2.71	∞
System Detection Limits	1	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Modulation response	3	N	1	1	1	3.00	3.00	∞
Readout Electronics	0.5	N	1	1	1	0.50	0.50	∞
Response Time	0	R	$\sqrt{3}$	1	1	0.00	0.00	∞
Integration Time	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
RF Ambient Conditions - Noise	3	R	$\sqrt{3}$	1	1	1.73	1.73	∞
RF Ambient Conditions - Reflections	3	R	$\sqrt{3}$	1	1	1.73	1.73	∞
Probe Positioner Mechanical Tolerance	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Probe Positioning with respect to Phantom Shell	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Extrapolation, interpolation and Integration Algorithms for Max. SAR Evaluation	2.3	R	$\sqrt{3}$	1	1	1.33	1.33	∞
Test sample Related								
Test Sample Positioning	2.6	N	1	1	1	2.60	2.60	11
Device Holder Uncertainty	3	N	1	1	1	3.00	3.00	7
Output Power Variation - SAR drift measurement	5	R	$\sqrt{3}$	1	1	2.89	2.89	∞
SAR scaling	2	R	$\sqrt{3}$	1	1	1.15	1.15	∞
Phantom and Tissue Parameters								
Phantom Uncertainty (shape and thickness tolerances)	4	R	$\sqrt{3}$	1	1	2.31	2.31	∞
Uncertainty in SAR correction for deviation (in permittivity and conductivity)	2	N	1	1	0.84	2.00	1.68	∞
Liquid Conductivity (temperature uncertainty)	2.5	N	1	0.78	0.71	1.95	1.78	5
Liquid conductivity - measurement uncertainty	4	N	1	0.23	0.26	0.92	1.04	5
Liquid permittivity (temperature uncertainty)	2.5	N	1	0.78	0.71	1.95	1.78	∞
Liquid permittivity - measurement uncertainty	5	N	1	0.23	0.26	1.15	1.30	∞
Combined Standard Uncertainty			RSS			10.63	10.54	
Expanded Uncertainty (95% Confidence interval)		k				21.26	21.08	

6. RF Exposure Positions

6.1. Ear and handset reference point

Figure 6.1.1 shows the front, back, and side views of the SAM phantom. The center-of-mouth reference point is labeled “M”, the left ear reference point (ERP) is marked “LE”, and the right ERP is marked “RE”.




Fig 6.1.1 Front, back, and side views of SAM phantom

6.2. Definition of the cheek position

1. Define two imaginary lines on the handset, the vertical centerline and the horizontal line. The vertical centerline passes through two points on the front side of the handset: the midpoint of the width w_t of the handset at the level of the acoustic output (point A in Figure 6.2.1 and Figure 6.2.2), and the midpoint of the width w_b of the bottom of the handset (point B). The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output (see Figure 6.2.1). The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset (see Figure 6.2.2), especially for clamshell handsets, handsets with flip covers, and other irregularly-shaped handsets.
2. Position the handset close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 6.2.3), such that the plane defined by the vertical centerline and the horizontal line of the handset is approximately parallel to the sagittal plane of the phantom.
3. Translate the handset towards the phantom along the line passing through RE and LE until handset point A touches the pinna at the ERP
4. While maintaining the handset in this plane, rotate it around the LE-RE line until the vertical centerline is in the plane normal to the plane containing B-M and N-F lines, i.e., the Reference Plane.
5. Rotate the handset around the vertical centerline until the handset (horizontal line) is parallel to the N-F line.

6. While maintaining the vertical centerline in the Reference Plane, keeping point A on the line passing through RE and LE, and maintaining the handset contact with the pinna, rotate the handset about the N-F line until any point on the handset is in contact with a phantom point below the pinna on the cheek. See Figure 6.2.3. The actual rotation angles should be documented in the test report.




Fig 6.2.1 Handset vertical and horizontal reference lines—“fixed case”




Fig 6.2.2 Handset vertical and horizontal reference lines—“clam-shell case”




Fig 6.2.3 cheek or touch position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which establish the Reference Plane for handset positioning, are indicated.

6.3. Definition of the tilt position

1. While maintaining the orientation of the handset, retract the handset parallel to the reference plane far enough away from the phantom to enable a rotation of the device by 15 degree.
2. Rotate the Handset around the horizontal line by 15 degree (see Figure 6.3.1).
3. While maintaining the orientation of the handset, move the handset towards the phantom on a line passing through RE and LE until any part of the handset touches the ear. The tilt position is obtained when the contact is on the pinna. If the contact is at any location other than the pinna, e.g., the antenna with the back of the phantom head, the angle of the handset shall be reduced. In this case, the tilt position is obtained if any part of the handset is in contact with the pinna as well as a second part of the handset is in contact with the phantom, e.g., the antenna with the back of the head.




Figure 6.3.1 – Tilt position of the wireless device on the left side of SAM

6.4. Body-worn device

A typical example of a body-worn device is a mobile phone, wireless enabled PDA or other battery operated wireless device with the ability to transmit while mounted on a person's body using a carry accessory approved by the wireless device manufacturer. The device shall be positioned as intended at the distance to the outer surface of the phantom that corresponds to the specified distance (See figure 6.1). Adjust the distance between the device surface and the flat phantom to 5mm.




Figure 6.1 – Test positions for Body-worn device

7. RF Output Power

7.1. GSM Conducted Power

Band GSM900	Burst-Averaged output Power (dBm)				Frame-Averaged output Power (dBm)			
	Tune -	975	38	124	Tune -	975	38	124
Frequency (MHz)	up	880.2	897.6	914.8	up	880.2	897.6	914.8
GSM Voice(GMSK)		33.00	32.62	32.81		23.97	23.59	23.78
GPRS(GMSK, 1 TS)	33.00	32.68	32.84	32.88	23.97	23.65	23.81	23.85
GPRS(GMSK, 2 TS)	32.50	32.10	32.22	32.27	26.48	26.08	26.20	26.25
GPRS(GMSK, 3 TS)	31.00	30.54	30.68	30.68	26.74	26.28	26.42	26.42
GPRS(GMSK, 4 TS)	29.50	29.32	29.46	29.46	26.49	26.31	26.45	26.45
EGPRS(8PSK, 1 TS)	27.50	26.89	26.82	27.16	18.47	17.86	17.79	18.13
EGPRS(8PSK, 2 TS)	27.00	26.43	26.32	26.64	20.98	20.41	20.30	20.62
EGPRS(8PSK, 3 TS)	24.00	23.81	23.75	23.99	19.74	19.55	19.49	19.73
EGPRS(8PSK, 4 TS)	23.00	22.51	22.39	22.64	19.99	19.50	19.38	19.63
Band GSM1800	Burst-Averaged output Power (dBm)				Frame-Averaged output Power (dBm)			
	Tune -	512	698	885	Tune -	512	698	885
Frequency (MHz)	up	1710.2	1747.4	1784.8	up	1710.2	1747.4	1784.8
GSM Voice(GMSK)		30.50	30.27	30.29		21.47	21.24	21.26
GPRS(GMSK, 1 TS)	30.50	30.32	30.32	30.31	21.47	21.29	21.29	21.28
GPRS(GMSK, 2 TS)	30.00	29.73	29.76	29.73	23.98	23.71	23.74	23.71
GPRS(GMSK, 3 TS)	28.00	27.94	27.96	27.90	23.74	23.68	23.70	23.64
GPRS(GMSK, 4 TS)	27.00	26.94	26.88	26.89	23.99	23.93	23.87	23.88
EGPRS(8PSK, 1 TS)	26.50	25.88	26.49	26.25	17.47	16.85	17.46	17.22
EGPRS(8PSK, 2 TS)	26.50	25.39	26.01	25.76	20.48	19.37	19.99	19.74
EGPRS(8PSK, 3 TS)	25.50	24.54	25.14	24.89	21.24	20.28	20.88	20.63
EGPRS(8PSK, 4 TS)	25.00	23.95	24.60	24.34	21.99	20.94	21.59	21.33

Note: The frame-averaged power is linearly scaled the maximum burst averaged power over 8 time slots. The calculated method are shown as below:

Frame-averaged power = Maximum burst averaged power (1 Tx Slot) - 9.03 dB

Frame-averaged power = Maximum burst averaged power (2 Tx Slots) - 6.02 dB

Frame-averaged power = Maximum burst averaged power (3 Tx Slots) - 4.26 dB

Frame-averaged power = Maximum burst averaged power (4 Tx Slots) - 3.01 dB

7.2. WCDMA Conducted Power

WCDMA Band 1		Burst-Averaged output Power (dBm)		
Tx Channel	Tune - up	9612	9750	9888
Frequency (MHz)		1922.4	1950	1977.6
RMC 12.2Kbps	24.50	24.20	24.03	24.02
HSDPA Sub 1	23.50	23.30	23.16	23.13
HSDPA Sub 2	23.00	22.68	22.59	22.61
HSDPA Sub 3	22.00	21.74	21.85	21.30
HSDPA Sub 4	22.00	21.93	21.60	21.62
HSUPA Sub 1	23.50	23.09	23.00	22.91
HSUPA Sub 2	23.50	23.09	23.00	23.06
HSUPA Sub 3	22.00	21.88	21.94	21.79
HSUPA Sub 4	23.50	23.28	23.17	23.12
HSUPA Sub 5	23.00	22.69	22.44	22.46
WCDMA Band 8		Burst-Averaged output Power (dBm)		
Tx Channel	Tune - up	2712	2788	2863
Frequency (MHz)		882.4	897.6	912.6
RMC 12.2Kbps	23.50	23.15	23.33	23.15
HSDPA Sub 1	22.50	22.29	22.38	22.34
HSDPA Sub 2	22.50	21.88	21.96	22.03
HSDPA Sub 3	21.00	20.35	20.94	20.29
HSDPA Sub 4	21.50	20.82	21.04	20.84
HSUPA Sub 1	22.50	20.84	22.27	22.25
HSUPA Sub 2	22.50	22.27	22.27	22.28
HSUPA Sub 3	21.50	20.49	21.36	21.03
HSUPA Sub 4	22.50	22.34	22.43	22.38
HSUPA Sub 5	22.00	20.63	21.74	21.55

7.3. LTE Conducted Power

Band	Bandwidth (MHz)	UL Channel	RB Size	RB Position	Modulation	Tune-up (dBm)	Power (dBm)
Band1	5	18025	1	#0	QPSK	23.50	23.08
Band1	5	18025	8	#0	QPSK	23.50	22.99
Band1	5	18025	25	#0	QPSK	23.50	21.91
Band1	5	18025	1	#0	QAM16	23.50	22.18
Band1	5	18025	8	#0	QAM16	23.50	21.92
Band1	5	18025	25	#0	QAM16	23.50	20.87

Band1	5	18300	1	#0	QPSK	23.50	22.99
Band1	5	18300	8	#0	QPSK	23.50	23.00
Band1	5	18300	25	#0	QPSK	23.50	21.93
Band1	5	18300	1	#0	QAM16	23.50	22.16
Band1	5	18300	8	#0	QAM16	23.50	22.04
Band1	5	18300	25	#0	QAM16	23.50	20.92
Band1	5	18575	1	#0	QPSK	23.50	22.54
Band1	5	18575	8	#0	QPSK	23.50	22.61
Band1	5	18575	25	#0	QPSK	23.50	21.56
Band1	5	18575	1	#0	QAM16	23.50	21.69
Band1	5	18575	8	#0	QAM16	23.50	21.56
Band1	5	18575	25	#0	QAM16	23.50	20.59
Band1	20	18100	1	#0	QPSK	23.50	22.96
Band1	20	18100	18	#0	QPSK	23.50	22.84
Band1	20	18100	100	#0	QPSK	23.50	21.81
Band1	20	18100	1	#0	QAM16	23.50	22.04
Band1	20	18100	18	#0	QAM16	23.50	21.85
Band1	20	18100	100	#0	QAM16	23.50	20.80
Band1	20	18300	1	#0	QPSK	23.50	22.97
Band1	20	18300	18	#0	QPSK	23.50	22.90
Band1	20	18300	100	#0	QPSK	23.50	21.83
Band1	20	18300	1	#0	QAM16	23.50	21.81
Band1	20	18300	18	#0	QAM16	23.50	21.88
Band1	20	18300	100	#0	QAM16	23.50	20.81
Band1	20	18500	1	#0	QPSK	23.50	22.33
Band1	20	18500	18	#0	QPSK	23.50	22.39
Band1	20	18500	100	#0	QPSK	23.50	21.34
Band1	20	18500	1	#0	QAM16	23.50	21.21
Band1	20	18500	18	#0	QAM16	23.50	21.35
Band1	20	18500	100	#0	QAM16	23.50	20.34
Band20	5	24175	1	#0	QPSK	23.50	23.41
Band20	5	24175	8	#0	QPSK	23.50	23.38
Band20	5	24175	25	#0	QPSK	23.50	22.34
Band20	5	24175	1	#0	QAM16	23.50	22.51
Band20	5	24175	8	#0	QAM16	23.50	22.34
Band20	5	24175	25	#0	QAM16	23.50	21.33
Band20	5	24300	1	#0	QPSK	23.50	23.42
Band20	5	24300	8	#0	QPSK	23.50	23.41
Band20	5	24300	25	#0	QPSK	23.50	22.31
Band20	5	24300	1	#0	QAM16	23.50	22.51

Band20	5	24300	8	#0	QAM16	23.50	22.36
Band20	5	24300	25	#0	QAM16	23.50	21.28
Band20	5	24425	1	#0	QPSK	23.50	23.32
Band20	5	24425	8	#0	QPSK	23.50	23.39
Band20	5	24425	25	#0	QPSK	23.50	22.37
Band20	5	24425	1	#0	QAM16	23.50	22.53
Band20	5	24425	8	#0	QAM16	23.50	22.43
Band20	5	24425	25	#0	QAM16	23.50	21.38
Band20	20	24250	1	#0	QPSK	23.50	23.27
Band20	20	24250	18	#0	QPSK	23.50	23.16
Band20	20	24250	100	#0	QPSK	23.50	22.24
Band20	20	24250	1	#0	QAM16	23.50	22.36
Band20	20	24250	18	#0	QAM16	23.50	22.16
Band20	20	24250	100	#0	QAM16	23.50	21.18
Band20	20	24300	1	#0	QPSK	23.50	23.23
Band20	20	24300	18	#0	QPSK	23.50	23.14
Band20	20	24300	100	#0	QPSK	23.50	22.42
Band20	20	24300	1	#0	QAM16	23.50	22.04
Band20	20	24300	18	#0	QAM16	23.50	22.14
Band20	20	24300	100	#0	QAM16	23.50	21.39
Band20	20	24350	1	#0	QPSK	23.50	23.08
Band20	20	24350	18	#0	QPSK	23.50	23.25
Band20	20	24350	100	#0	QPSK	23.50	22.27
Band20	20	24350	1	#0	QAM16	23.50	21.95
Band20	20	24350	18	#0	QAM16	23.50	22.22
Band20	20	24350	100	#0	QAM16	23.50	21.25
Band28	3	27225	1	#0	QPSK	24.00	23.83
Band28	3	27225	4	#0	QPSK	24.00	23.72
Band28	3	27225	15	#0	QPSK	24.00	22.74
Band28	3	27225	1	#0	QAM16	24.00	23.07
Band28	3	27225	4	#0	QAM16	24.00	22.76
Band28	3	27225	15	#0	QAM16	24.00	21.71
Band28	3	27375	1	#0	QPSK	24.00	23.66
Band28	3	27375	4	#0	QPSK	24.00	23.63
Band28	3	27375	15	#0	QPSK	24.00	22.61
Band28	3	27375	1	#0	QAM16	24.00	22.86
Band28	3	27375	4	#0	QAM16	24.00	22.83
Band28	3	27375	15	#0	QAM16	24.00	21.48
Band28	3	27645	1	#0	QPSK	24.00	23.69
Band28	3	27645	4	#0	QPSK	24.00	23.62

Band28	3	27645	15	#0	QPSK	24.00	22.62
Band28	3	27645	1	#0	QAM16	24.00	22.60
Band28	3	27645	4	#0	QAM16	24.00	22.52
Band28	3	27645	15	#0	QAM16	24.00	21.62
Band28	5	27235	1	#0	QPSK	24.00	23.86
Band28	5	27235	8	#0	QPSK	24.00	23.78
Band28	5	27235	25	#0	QPSK	24.00	22.73
Band28	5	27235	1	#0	QAM16	24.00	23.00
Band28	5	27235	8	#0	QAM16	24.00	22.78
Band28	5	27235	25	#0	QAM16	24.00	21.77
Band28	5	27385	1	#0	QPSK	24.00	23.72
Band28	5	27385	8	#0	QPSK	24.00	23.72
Band28	5	27385	25	#0	QPSK	24.00	22.68
Band28	5	27385	1	#0	QAM16	24.00	22.88
Band28	5	27385	8	#0	QAM16	24.00	22.73
Band28	5	27385	25	#0	QAM16	24.00	21.65
Band28	5	27635	1	#0	QPSK	24.00	23.69
Band28	5	27635	8	#0	QPSK	24.00	23.72
Band28	5	27635	25	#0	QPSK	24.00	22.69
Band28	5	27635	1	#0	QAM16	24.00	22.90
Band28	5	27635	8	#0	QAM16	24.00	22.77
Band28	5	27635	25	#0	QAM16	24.00	21.68
Band28	20	27310	1	#0	QPSK	24.00	23.77
Band28	20	27310	18	#0	QPSK	24.00	23.50
Band28	20	27310	100	#0	QPSK	24.00	22.64
Band28	20	27310	1	#0	QAM16	24.00	22.84
Band28	20	27310	18	#0	QAM16	24.00	22.63
Band28	20	27310	100	#0	QAM16	24.00	21.59
Band28	20	27460	1	#0	QPSK	24.00	23.66
Band28	20	27460	18	#0	QPSK	24.00	23.57
Band28	20	27460	100	#0	QPSK	24.00	22.58
Band28	20	27460	1	#0	QAM16	24.00	22.44
Band28	20	27460	18	#0	QAM16	24.00	22.54
Band28	20	27460	100	#0	QAM16	24.00	21.56
Band28	20	27560	1	#0	QPSK	24.00	23.46
Band28	20	27560	18	#0	QPSK	24.00	23.57
Band28	20	27560	100	#0	QPSK	24.00	22.70
Band28	20	27560	1	#0	QAM16	24.00	22.34
Band28	20	27560	18	#0	QAM16	24.00	22.56
Band28	20	27560	100	#0	QAM16	24.00	21.70

Band3	1.4	19207	1	#0	QPSK	23.50	23.30
Band3	1.4	19207	5	#0	QPSK	23.50	23.36
Band3	1.4	19207	6	#0	QPSK	23.50	22.32
Band3	1.4	19207	1	#0	QAM16	23.50	22.25
Band3	1.4	19207	5	#0	QAM16	23.50	22.44
Band3	1.4	19207	6	#0	QAM16	23.50	21.39
Band3	1.4	19575	1	#0	QPSK	23.50	23.25
Band3	1.4	19575	5	#0	QPSK	23.50	23.31
Band3	1.4	19575	6	#0	QPSK	23.50	22.31
Band3	1.4	19575	1	#0	QAM16	23.50	22.35
Band3	1.4	19575	5	#0	QAM16	23.50	22.58
Band3	1.4	19575	6	#0	QAM16	23.50	21.20
Band3	1.4	19943	1	#0	QPSK	23.50	23.38
Band3	1.4	19943	5	#0	QPSK	23.50	23.27
Band3	1.4	19943	6	#0	QPSK	23.50	22.33
Band3	1.4	19943	1	#0	QAM16	23.50	22.35
Band3	1.4	19943	5	#0	QAM16	23.50	22.40
Band3	1.4	19943	6	#0	QAM16	23.50	21.31
Band3	5	19225	1	#0	QPSK	23.50	23.50
Band3	5	19225	8	#0	QPSK	23.50	23.47
Band3	5	19225	25	#0	QPSK	23.50	22.32
Band3	5	19225	1	#0	QAM16	23.50	22.56
Band3	5	19225	8	#0	QAM16	23.50	22.39
Band3	5	19225	25	#0	QAM16	23.50	21.37
Band3	5	19575	1	#0	QPSK	23.50	23.39
Band3	5	19575	8	#0	QPSK	23.50	23.41
Band3	5	19575	25	#0	QPSK	23.50	22.27
Band3	5	19575	1	#0	QAM16	23.50	22.56
Band3	5	19575	8	#0	QAM16	23.50	22.37
Band3	5	19575	25	#0	QAM16	23.50	21.23
Band3	5	19925	1	#0	QPSK	23.50	23.32
Band3	5	19925	8	#0	QPSK	23.50	23.42
Band3	5	19925	25	#0	QPSK	23.50	22.34
Band3	5	19925	1	#0	QAM16	23.50	22.51
Band3	5	19925	8	#0	QAM16	23.50	22.40
Band3	5	19925	25	#0	QAM16	23.50	21.35
Band3	20	19300	1	#0	QPSK	23.50	23.40
Band3	20	19300	18	#0	QPSK	23.50	23.20
Band3	20	19300	100	#0	QPSK	23.50	22.12
Band3	20	19300	1	#0	QAM16	23.50	22.40

Band3	20	19300	18	#0	QAM16	23.50	22.21
Band3	20	19300	100	#0	QAM16	23.50	21.11
Band3	20	19575	1	#0	QPSK	23.50	23.34
Band3	20	19575	18	#0	QPSK	23.50	23.31
Band3	20	19575	100	#0	QPSK	23.50	22.23
Band3	20	19575	1	#0	QAM16	23.50	22.17
Band3	20	19575	18	#0	QAM16	23.50	22.25
Band3	20	19575	100	#0	QAM16	23.50	21.21
Band3	20	19850	1	#0	QPSK	23.50	22.92
Band3	20	19850	18	#0	QPSK	23.50	23.05
Band3	20	19850	100	#0	QPSK	23.50	22.21
Band3	20	19850	1	#0	QAM16	23.50	21.84
Band3	20	19850	18	#0	QAM16	23.50	22.06
Band3	20	19850	100	#0	QAM16	23.50	21.21
Band40	5	38675	1	#0	QPSK	23.50	22.35
Band40	5	38675	8	#0	QPSK	23.50	22.20
Band40	5	38675	25	#0	QPSK	23.50	21.35
Band40	5	38675	1	#0	QAM16	23.50	21.24
Band40	5	38675	8	#0	QAM16	23.50	21.11
Band40	5	38675	25	#0	QAM16	23.50	20.42
Band40	5	39150	1	#0	QPSK	23.50	22.72
Band40	5	39150	8	#0	QPSK	23.50	22.87
Band40	5	39150	25	#0	QPSK	23.50	22.04
Band40	5	39150	1	#0	QAM16	23.50	21.91
Band40	5	39150	8	#0	QAM16	23.50	21.90
Band40	5	39150	25	#0	QAM16	23.50	21.00
Band40	5	39625	1	#0	QPSK	23.50	23.26
Band40	5	39625	8	#0	QPSK	23.50	23.38
Band40	5	39625	25	#0	QPSK	23.50	22.54
Band40	5	39625	1	#0	QAM16	23.50	22.54
Band40	5	39625	8	#0	QAM16	23.50	22.36
Band40	5	39625	25	#0	QAM16	23.50	21.52
Band40	20	38750	1	#0	QPSK	23.50	21.91
Band40	20	38750	18	#0	QPSK	23.50	22.28
Band40	20	38750	100	#0	QPSK	23.50	22.23
Band40	20	38750	1	#0	QAM16	23.50	21.08
Band40	20	38750	18	#0	QAM16	23.50	21.31
Band40	20	38750	100	#0	QAM16	23.50	21.24
Band40	20	39150	1	#0	QPSK	23.50	21.89
Band40	20	39150	18	#0	QPSK	23.50	22.07

Band40	20	39150	100	#0	QPSK	23.50	21.98
Band40	20	39150	1	#0	QAM16	23.50	20.81
Band40	20	39150	18	#0	QAM16	23.50	21.02
Band40	20	39150	100	#0	QAM16	23.50	21.00
Band40	20	39550	1	#0	QPSK	23.50	21.74
Band40	20	39550	18	#0	QPSK	23.50	21.92
Band40	20	39550	100	#0	QPSK	23.50	21.83
Band40	20	39550	1	#0	QAM16	23.50	20.56
Band40	20	39550	18	#0	QAM16	23.50	20.93
Band40	20	39550	100	#0	QAM16	23.50	20.83
Band7	5	20775	1	#0	QPSK	24.50	23.48
Band7	5	20775	8	#0	QPSK	24.50	23.49
Band7	5	20775	25	#0	QPSK	24.50	22.40
Band7	5	20775	1	#0	QAM16	24.50	22.60
Band7	5	20775	8	#0	QAM16	24.50	22.42
Band7	5	20775	25	#0	QAM16	24.50	21.42
Band7	5	21100	1	#0	QPSK	24.50	24.46
Band7	5	21100	8	#0	QPSK	24.50	24.42
Band7	5	21100	25	#0	QPSK	24.50	23.30
Band7	5	21100	1	#0	QAM16	24.50	23.56
Band7	5	21100	8	#0	QAM16	24.50	23.37
Band7	5	21100	25	#0	QAM16	24.50	22.29
Band7	5	21425	1	#0	QPSK	24.50	24.15
Band7	5	21425	8	#0	QPSK	24.50	24.22
Band7	5	21425	25	#0	QPSK	24.50	23.22
Band7	5	21425	1	#0	QAM16	24.50	23.34
Band7	5	21425	8	#0	QAM16	24.50	23.23
Band7	5	21425	25	#0	QAM16	24.50	22.24
Band7	20	20850	1	#0	QPSK	24.50	23.37
Band7	20	20850	18	#0	QPSK	24.50	23.24
Band7	20	20850	100	#0	QPSK	24.50	22.47
Band7	20	20850	1	#0	QAM16	24.50	22.46
Band7	20	20850	18	#0	QAM16	24.50	22.27
Band7	20	20850	100	#0	QAM16	24.50	21.46
Band7	20	21100	1	#0	QPSK	24.50	24.31
Band7	20	21100	18	#0	QPSK	24.50	24.31
Band7	20	21100	100	#0	QPSK	24.50	23.30
Band7	20	21100	1	#0	QAM16	24.50	23.18
Band7	20	21100	18	#0	QAM16	24.50	23.35
Band7	20	21100	100	#0	QAM16	24.50	22.30

Band7	20	21350	1	#0	QPSK	24.50	23.57
Band7	20	21350	18	#0	QPSK	24.50	23.75
Band7	20	21350	100	#0	QPSK	24.50	23.05
Band7	20	21350	1	#0	QAM16	24.50	22.52
Band7	20	21350	18	#0	QAM16	24.50	22.71
Band7	20	21350	100	#0	QAM16	24.50	22.06
Band8	1.4	21457	1	#0	QPSK	24.00	23.28
Band8	1.4	21457	5	#0	QPSK	24.00	23.36
Band8	1.4	21457	6	#0	QPSK	24.00	22.34
Band8	1.4	21457	1	#0	QAM16	24.00	22.23
Band8	1.4	21457	5	#0	QAM16	24.00	22.47
Band8	1.4	21457	6	#0	QAM16	24.00	21.46
Band8	1.4	21625	1	#0	QPSK	24.00	23.61
Band8	1.4	21625	5	#0	QPSK	24.00	23.70
Band8	1.4	21625	6	#0	QPSK	24.00	22.71
Band8	1.4	21625	1	#0	QAM16	24.00	22.77
Band8	1.4	21625	5	#0	QAM16	24.00	23.00
Band8	1.4	21625	6	#0	QAM16	24.00	21.61
Band8	1.4	21793	1	#0	QPSK	24.00	23.44
Band8	1.4	21793	5	#0	QPSK	24.00	23.33
Band8	1.4	21793	6	#0	QPSK	24.00	22.43
Band8	1.4	21793	1	#0	QAM16	24.00	22.54
Band8	1.4	21793	5	#0	QAM16	24.00	22.51
Band8	1.4	21793	6	#0	QAM16	24.00	21.44
Band8	5	21475	1	#0	QPSK	24.00	23.50
Band8	5	21475	8	#0	QPSK	24.00	23.52
Band8	5	21475	25	#0	QPSK	24.00	22.44
Band8	5	21475	1	#0	QAM16	24.00	22.56
Band8	5	21475	8	#0	QAM16	24.00	22.48
Band8	5	21475	25	#0	QAM16	24.00	21.50
Band8	5	21625	1	#0	QPSK	24.00	23.88
Band8	5	21625	8	#0	QPSK	24.00	23.77
Band8	5	21625	25	#0	QPSK	24.00	22.73
Band8	5	21625	1	#0	QAM16	24.00	22.96
Band8	5	21625	8	#0	QAM16	24.00	22.73
Band8	5	21625	25	#0	QAM16	24.00	21.69
Band8	5	21775	1	#0	QPSK	24.00	23.54
Band8	5	21775	8	#0	QPSK	24.00	23.56
Band8	5	21775	25	#0	QPSK	24.00	22.42
Band8	5	21775	1	#0	QAM16	24.00	22.77

Band8	5	21775	8	#0	QAM16	24.00	22.57
Band8	5	21775	25	#0	QAM16	24.00	21.42
Band8	10	21500	1	#0	QPSK	24.00	23.53
Band8	10	21500	12	#0	QPSK	24.00	23.47
Band8	10	21500	50	#0	QPSK	24.00	22.60
Band8	10	21500	1	#0	QAM16	24.00	22.69
Band8	10	21500	12	#0	QAM16	24.00	22.50
Band8	10	21500	50	#0	QAM16	24.00	21.58
Band8	10	21625	1	#0	QPSK	24.00	23.74
Band8	10	21625	12	#0	QPSK	24.00	23.75
Band8	10	21625	50	#0	QPSK	24.00	22.74
Band8	10	21625	1	#0	QAM16	24.00	22.88
Band8	10	21625	12	#0	QAM16	24.00	22.76
Band8	10	21625	50	#0	QAM16	24.00	21.71
Band8	10	21750	1	#0	QPSK	24.00	23.68
Band8	10	21750	12	#0	QPSK	24.00	23.65
Band8	10	21750	50	#0	QPSK	24.00	22.56
Band8	10	21750	1	#0	QAM16	24.00	22.62
Band8	10	21750	12	#0	QAM16	24.00	22.65
Band8	10	21750	50	#0	QAM16	24.00	21.52

7.4. NR Conducted Power

NR

Band	SCS (kHz)	Bandwidth (MHz)	UL Channel	RB Allocation	Modulation	Tune-up	Power (dBm)
n1	30	10	385000	12@6	DFT_BPSK	23.50	22.95
n1	30	10	385000	1@1	DFT_BPSK	23.50	23.09
n1	30	10	385000	1@22	DFT_BPSK	23.50	23.06
n1	30	10	385000	12@6	DFT_QPSK	23.50	22.98
n1	30	10	385000	1@1	DFT_QPSK	23.50	22.79
n1	30	10	385000	1@22	DFT_QPSK	23.50	22.85
n1	30	10	390000	12@6	DFT_BPSK	23.50	22.89
n1	30	10	390000	1@1	DFT_BPSK	23.50	22.93
n1	30	10	390000	1@22	DFT_BPSK	23.50	22.95
n1	30	10	390000	12@6	DFT_QPSK	23.50	22.93
n1	30	10	390000	1@1	DFT_QPSK	23.50	22.67
n1	30	10	390000	1@22	DFT_QPSK	23.50	22.74
n1	30	10	395000	12@6	DFT_BPSK	23.50	22.74
n1	30	10	395000	1@1	DFT_BPSK	23.50	22.87

n1	30	10	395000	1@22	DFT_BPSK	23.50	22.90
n1	30	10	395000	12@6	DFT_QPSK	23.50	22.80
n1	30	10	395000	1@1	DFT_QPSK	23.50	22.72
n1	30	10	395000	1@22	DFT_QPSK	23.50	22.76
n1	30	15	385500	18@9	DFT_BPSK	23.50	22.93
n1	30	15	385500	1@1	DFT_BPSK	23.50	22.90
n1	30	15	385500	1@36	DFT_BPSK	23.50	22.84
n1	30	15	385500	18@9	DFT_QPSK	23.50	22.95
n1	30	15	385500	1@1	DFT_QPSK	23.50	22.86
n1	30	15	385500	1@36	DFT_QPSK	23.50	22.80
n1	30	15	390000	18@9	DFT_BPSK	23.50	22.83
n1	30	15	390000	1@1	DFT_BPSK	23.50	22.78
n1	30	15	390000	1@36	DFT_BPSK	23.50	22.85
n1	30	15	390000	18@9	DFT_QPSK	23.50	22.88
n1	30	15	390000	1@1	DFT_QPSK	23.50	22.74
n1	30	15	390000	1@36	DFT_QPSK	23.50	22.79
n1	30	15	394500	18@9	DFT_BPSK	23.50	22.80
n1	30	15	394500	1@1	DFT_BPSK	23.50	22.81
n1	30	15	394500	1@36	DFT_BPSK	23.50	22.91
n1	30	15	394500	18@9	DFT_QPSK	23.50	22.82
n1	30	15	394500	1@1	DFT_QPSK	23.50	22.58
n1	30	15	394500	1@36	DFT_QPSK	23.50	22.63
n1	30	20	386000	25@12	DFT_BPSK	23.50	22.91
n1	30	20	386000	1@1	DFT_BPSK	23.50	22.95
n1	30	20	386000	1@49	DFT_BPSK	23.50	22.82
n1	30	20	386000	25@12	DFT_QPSK	23.50	22.94
n1	30	20	386000	1@1	DFT_QPSK	23.50	22.72
n1	30	20	386000	1@49	DFT_QPSK	23.50	22.64
n1	30	20	390000	25@12	DFT_BPSK	23.50	22.88
n1	30	20	390000	1@1	DFT_BPSK	23.50	22.70
n1	30	20	390000	1@49	DFT_BPSK	23.50	22.77
n1	30	20	390000	25@12	DFT_QPSK	23.50	22.90
n1	30	20	390000	1@1	DFT_QPSK	23.50	22.64
n1	30	20	390000	1@49	DFT_QPSK	23.50	22.75
n1	30	20	394000	25@12	DFT_BPSK	23.50	22.76
n1	30	20	394000	1@1	DFT_BPSK	23.50	22.77
n1	30	20	394000	1@49	DFT_BPSK	23.50	22.80
n1	30	20	394000	25@12	DFT_QPSK	23.50	22.76
n1	30	20	394000	1@1	DFT_QPSK	23.50	22.60
n1	30	20	394000	1@49	DFT_QPSK	23.50	22.63

n20	30	10	167400	12@6	DFT_BPSK	24.50	23.33
n20	30	10	167400	1@1	DFT_BPSK	24.50	23.21
n20	30	10	167400	1@22	DFT_BPSK	24.50	23.38
n20	30	10	167400	12@6	DFT_QPSK	24.50	23.35
n20	30	10	167400	1@1	DFT_QPSK	24.50	23.44
n20	30	10	167400	1@22	DFT_QPSK	24.50	23.52
n20	30	10	169400	12@6	DFT_BPSK	24.50	23.60
n20	30	10	169400	1@1	DFT_BPSK	24.50	23.38
n20	30	10	169400	1@22	DFT_BPSK	24.50	23.57
n20	30	10	169400	12@6	DFT_QPSK	24.50	19.69
n20	30	10	169400	1@1	DFT_QPSK	24.50	23.63
n20	30	10	169400	1@22	DFT_QPSK	24.50	23.78
n20	30	10	171400	12@6	DFT_BPSK	24.50	23.63
n20	30	10	171400	1@1	DFT_BPSK	24.50	23.61
n20	30	10	171400	1@22	DFT_BPSK	24.50	23.49
n20	30	10	171400	12@6	DFT_QPSK	24.50	22.69
n20	30	10	171400	1@1	DFT_QPSK	24.50	24.12
n20	30	10	171400	1@22	DFT_QPSK	24.50	23.96
n20	30	15	167900	18@9	DFT_BPSK	24.50	23.38
n20	30	15	167900	1@1	DFT_BPSK	24.50	23.26
n20	30	15	167900	1@36	DFT_BPSK	24.50	23.57
n20	30	15	167900	18@9	DFT_QPSK	24.50	23.46
n20	30	15	167900	1@1	DFT_QPSK	24.50	23.73
n20	30	15	167900	1@36	DFT_QPSK	24.50	24.18
n20	30	15	169400	18@9	DFT_BPSK	24.50	23.63
n20	30	15	169400	1@1	DFT_BPSK	24.50	23.42
n20	30	15	169400	1@36	DFT_BPSK	24.50	23.62
n20	30	15	169400	18@9	DFT_QPSK	24.50	22.67
n20	30	15	169400	1@1	DFT_QPSK	24.50	23.82
n20	30	15	169400	1@36	DFT_QPSK	24.50	24.19
n20	30	15	170900	18@9	DFT_BPSK	24.50	23.62
n20	30	15	170900	1@1	DFT_BPSK	24.50	23.58
n20	30	15	170900	1@36	DFT_BPSK	24.50	23.45
n20	30	15	170900	18@9	DFT_QPSK	24.50	22.10
n20	30	15	170900	1@1	DFT_QPSK	24.50	23.77
n20	30	15	170900	1@36	DFT_QPSK	24.50	23.61
n20	30	20	168400	25@12	DFT_BPSK	24.50	23.52
n20	30	20	168400	1@1	DFT_BPSK	24.50	23.15
n20	30	20	168400	1@49	DFT_BPSK	24.50	23.53
n20	30	20	168400	25@12	DFT_QPSK	24.50	21.26

n20	30	20	168400	1@1	DFT_QPSK	24.50	23.34
n20	30	20	168400	1@49	DFT_QPSK	24.50	23.71
n20	30	20	169400	25@12	DFT_BPSK	24.50	23.67
n20	30	20	169400	1@1	DFT_BPSK	24.50	23.24
n20	30	20	169400	1@49	DFT_BPSK	24.50	23.44
n20	30	20	169400	25@12	DFT_QPSK	24.50	22.67
n20	30	20	169400	1@1	DFT_QPSK	24.50	23.37
n20	30	20	169400	1@49	DFT_QPSK	24.50	23.68
n20	30	20	170400	25@12	DFT_BPSK	24.50	23.62
n20	30	20	170400	1@1	DFT_BPSK	24.50	23.38
n20	30	20	170400	1@49	DFT_BPSK	24.50	23.41
n20	30	20	170400	25@12	DFT_QPSK	24.50	22.16
n20	30	20	170400	1@1	DFT_QPSK	24.50	23.56
n20	30	20	170400	1@49	DFT_QPSK	24.50	23.58
n28	30	10	141600	12@6	DFT_BPSK	25.00	23.64
n28	30	10	141600	1@1	DFT_BPSK	25.00	23.55
n28	30	10	141600	1@22	DFT_BPSK	25.00	23.53
n28	30	10	141600	12@6	DFT_QPSK	25.00	23.62
n28	30	10	141600	1@1	DFT_QPSK	25.00	24.22
n28	30	10	141600	1@22	DFT_QPSK	25.00	24.30
n28	30	10	145100	12@6	DFT_BPSK	25.00	23.65
n28	30	10	145100	1@1	DFT_BPSK	25.00	23.58
n28	30	10	145100	1@22	DFT_BPSK	25.00	23.58
n28	30	10	145100	12@6	DFT_QPSK	25.00	21.43
n28	30	10	145100	1@1	DFT_QPSK	25.00	23.92
n28	30	10	145100	1@22	DFT_QPSK	25.00	24.09
n28	30	10	148600	12@6	DFT_BPSK	25.00	23.78
n28	30	10	148600	1@1	DFT_BPSK	25.00	23.61
n28	30	10	148600	1@22	DFT_BPSK	25.00	23.67
n28	30	10	148600	12@6	DFT_QPSK	25.00	23.77
n28	30	10	148600	1@1	DFT_QPSK	25.00	24.56
n28	30	10	148600	1@22	DFT_QPSK	25.00	24.63
n28	30	15	142100	18@9	DFT_BPSK	25.00	23.62
n28	30	15	142100	1@1	DFT_BPSK	25.00	23.53
n28	30	15	142100	1@36	DFT_BPSK	25.00	23.62
n28	30	15	142100	18@9	DFT_QPSK	25.00	21.42
n28	30	15	142100	1@1	DFT_QPSK	25.00	24.36
n28	30	15	142100	1@36	DFT_QPSK	25.00	24.31
n28	30	15	145100	18@9	DFT_BPSK	25.00	23.63
n28	30	15	145100	1@1	DFT_BPSK	25.00	23.58

n28	30	15	145100	1@36	DFT_BPSK	25.00	23.47
n28	30	15	145100	18@9	DFT_QPSK	25.00	23.69
n28	30	15	145100	1@1	DFT_QPSK	25.00	23.81
n28	30	15	145100	1@36	DFT_QPSK	25.00	23.80
n28	30	15	148100	18@9	DFT_BPSK	25.00	23.69
n28	30	15	148100	1@1	DFT_BPSK	25.00	23.52
n28	30	15	148100	1@36	DFT_BPSK	25.00	23.60
n28	30	15	148100	18@9	DFT_QPSK	25.00	22.19
n28	30	15	148100	1@1	DFT_QPSK	25.00	23.95
n28	30	15	148100	1@36	DFT_QPSK	25.00	24.05
n28	30	20	142600	25@12	DFT_BPSK	25.00	23.64
n28	30	20	142600	1@1	DFT_BPSK	25.00	23.40
n28	30	20	142600	1@49	DFT_BPSK	25.00	23.51
n28	30	20	142600	25@12	DFT_QPSK	25.00	21.40
n28	30	20	142600	1@1	DFT_QPSK	25.00	23.66
n28	30	20	142600	1@49	DFT_QPSK	25.00	23.74
n28	30	20	145100	25@12	DFT_BPSK	25.00	23.62
n28	30	20	145100	1@1	DFT_BPSK	25.00	23.50
n28	30	20	145100	1@49	DFT_BPSK	25.00	23.38
n28	30	20	145100	25@12	DFT_QPSK	25.00	20.68
n28	30	20	145100	1@1	DFT_QPSK	25.00	23.72
n28	30	20	145100	1@49	DFT_QPSK	25.00	23.81
n28	30	20	147600	25@12	DFT_BPSK	25.00	23.77
n28	30	20	147600	1@1	DFT_BPSK	25.00	23.54
n28	30	20	147600	1@49	DFT_BPSK	25.00	23.56
n28	30	20	147600	25@12	DFT_QPSK	25.00	23.73
n28	30	20	147600	1@1	DFT_QPSK	25.00	23.77
n28	30	20	147600	1@49	DFT_QPSK	25.00	23.99
n3	30	10	343000	12@6	DFT_BPSK	25.00	23.29
n3	30	10	343000	1@1	DFT_BPSK	25.00	23.70
n3	30	10	343000	1@22	DFT_BPSK	25.00	23.83
n3	30	10	343000	12@6	DFT_QPSK	25.00	23.91
n3	30	10	343000	1@1	DFT_QPSK	25.00	24.63
n3	30	10	343000	1@22	DFT_QPSK	25.00	24.79
n3	30	10	349500	12@6	DFT_BPSK	25.00	23.50
n3	30	10	349500	1@1	DFT_BPSK	25.00	23.41
n3	30	10	349500	1@22	DFT_BPSK	25.00	23.56
n3	30	10	349500	12@6	DFT_QPSK	25.00	23.04
n3	30	10	349500	1@1	DFT_QPSK	25.00	23.77
n3	30	10	349500	1@22	DFT_QPSK	25.00	23.97

n3	30	10	356000	12@6	DFT_BPSK	25.00	23.11
n3	30	10	356000	1@1	DFT_BPSK	25.00	22.98
n3	30	10	356000	1@22	DFT_BPSK	25.00	22.98
n3	30	10	356000	12@6	DFT_QPSK	25.00	23.12
n3	30	10	356000	1@1	DFT_QPSK	25.00	23.59
n3	30	10	356000	1@22	DFT_QPSK	25.00	24.07
n3	30	20	344000	25@12	DFT_BPSK	25.00	23.82
n3	30	20	344000	1@1	DFT_BPSK	25.00	23.55
n3	30	20	344000	1@49	DFT_BPSK	25.00	23.57
n3	30	20	344000	25@12	DFT_QPSK	25.00	23.89
n3	30	20	344000	1@1	DFT_QPSK	25.00	23.97
n3	30	20	344000	1@49	DFT_QPSK	25.00	23.86
n3	30	20	349500	25@12	DFT_BPSK	25.00	23.49
n3	30	20	349500	1@1	DFT_BPSK	25.00	23.32
n3	30	20	349500	1@49	DFT_BPSK	25.00	23.51
n3	30	20	349500	25@12	DFT_QPSK	25.00	23.55
n3	30	20	349500	1@1	DFT_QPSK	25.00	23.59
n3	30	20	349500	1@49	DFT_QPSK	25.00	23.74
n3	30	20	355000	25@12	DFT_BPSK	25.00	23.12
n3	30	20	355000	1@1	DFT_BPSK	25.00	23.22
n3	30	20	355000	1@49	DFT_BPSK	25.00	22.89
n3	30	20	355000	25@12	DFT_QPSK	25.00	23.17
n3	30	20	355000	1@1	DFT_QPSK	25.00	23.81
n3	30	20	355000	1@49	DFT_QPSK	25.00	23.71
n3	30	30	345000	36@18	DFT_BPSK	25.00	23.73
n3	30	30	345000	1@1	DFT_BPSK	25.00	23.49
n3	30	30	345000	1@76	DFT_BPSK	25.00	23.14
n3	30	30	345000	36@18	DFT_QPSK	25.00	23.80
n3	30	30	345000	1@1	DFT_QPSK	25.00	24.39
n3	30	30	345000	1@76	DFT_QPSK	25.00	23.88
n3	30	30	349500	36@18	DFT_BPSK	25.00	23.52
n3	30	30	349500	1@1	DFT_BPSK	25.00	23.21
n3	30	30	349500	1@76	DFT_BPSK	25.00	23.36
n3	30	30	349500	36@18	DFT_QPSK	25.00	23.54
n3	30	30	349500	1@1	DFT_QPSK	25.00	23.99
n3	30	30	349500	1@76	DFT_QPSK	25.00	24.04
n3	30	30	354000	36@18	DFT_BPSK	25.00	23.23
n3	30	30	354000	1@1	DFT_BPSK	25.00	23.17
n3	30	30	354000	1@76	DFT_BPSK	25.00	22.67
n3	30	30	354000	36@18	DFT_QPSK	25.00	23.24

n3	30	30	354000	1@1	DFT_QPSK	25.00	23.40
n3	30	30	354000	1@76	DFT_QPSK	25.00	23.02
n38	30	10	515000	12@6	DFT_BPSK	24.50	24.21
n38	30	10	515000	1@1	DFT_BPSK	24.50	24.04
n38	30	10	515000	1@22	DFT_BPSK	24.50	24.22
n38	30	10	515000	12@6	DFT_QPSK	24.50	24.20
n38	30	10	515000	1@1	DFT_QPSK	24.50	23.99
n38	30	10	515000	1@22	DFT_QPSK	24.50	24.15
n38	30	10	519000	12@6	DFT_BPSK	24.50	23.99
n38	30	10	519000	1@1	DFT_BPSK	24.50	23.96
n38	30	10	519000	1@22	DFT_BPSK	24.50	23.84
n38	30	10	519000	12@6	DFT_QPSK	24.50	23.98
n38	30	10	519000	1@1	DFT_QPSK	24.50	23.88
n38	30	10	519000	1@22	DFT_QPSK	24.50	23.80
n38	30	10	523000	12@6	DFT_BPSK	24.50	23.87
n38	30	10	523000	1@1	DFT_BPSK	24.50	23.69
n38	30	10	523000	1@22	DFT_BPSK	24.50	23.82
n38	30	10	523000	12@6	DFT_QPSK	24.50	23.86
n38	30	10	523000	1@1	DFT_QPSK	24.50	23.67
n38	30	10	523000	1@22	DFT_QPSK	24.50	23.78
n38	30	15	515500	18@9	DFT_BPSK	24.50	24.23
n38	30	15	515500	1@1	DFT_BPSK	24.50	24.03
n38	30	15	515500	1@36	DFT_BPSK	24.50	24.21
n38	30	15	515500	18@9	DFT_QPSK	24.50	24.24
n38	30	15	515500	1@1	DFT_QPSK	24.50	24.00
n38	30	15	515500	1@36	DFT_QPSK	24.50	24.18
n38	30	15	519000	18@9	DFT_BPSK	24.50	24.00
n38	30	15	519000	1@1	DFT_BPSK	24.50	24.04
n38	30	15	519000	1@36	DFT_BPSK	24.50	23.74
n38	30	15	519000	18@9	DFT_QPSK	24.50	23.99
n38	30	15	519000	1@1	DFT_QPSK	24.50	23.97
n38	30	15	519000	1@36	DFT_QPSK	24.50	23.70
n38	30	15	522500	18@9	DFT_BPSK	24.50	23.91
n38	30	15	522500	1@1	DFT_BPSK	24.50	23.73
n38	30	15	522500	1@36	DFT_BPSK	24.50	23.94
n38	30	15	522500	18@9	DFT_QPSK	24.50	23.91
n38	30	15	522500	1@1	DFT_QPSK	24.50	23.68
n38	30	15	522500	1@36	DFT_QPSK	24.50	23.92
n38	30	20	516000	25@12	DFT_BPSK	24.50	24.36
n38	30	20	516000	1@1	DFT_BPSK	24.50	24.06

n38	30	20	516000	1@49	DFT_BPSK	24.50	24.12
n38	30	20	516000	25@12	DFT_QPSK	24.50	24.38
n38	30	20	516000	1@1	DFT_QPSK	24.50	24.03
n38	30	20	516000	1@49	DFT_QPSK	24.50	24.11
n38	30	20	519000	25@12	DFT_BPSK	24.50	24.11
n38	30	20	519000	1@1	DFT_BPSK	24.50	24.20
n38	30	20	519000	1@49	DFT_BPSK	24.50	23.81
n38	30	20	519000	25@12	DFT_QPSK	24.50	24.11
n38	30	20	519000	1@1	DFT_QPSK	24.50	24.14
n38	30	20	519000	1@49	DFT_QPSK	24.50	23.79
n38	30	20	522000	25@12	DFT_BPSK	24.50	23.91
n38	30	20	522000	1@1	DFT_BPSK	24.50	23.73
n38	30	20	522000	1@49	DFT_BPSK	24.50	23.94
n38	30	20	522000	25@12	DFT_QPSK	24.50	23.91
n38	30	20	522000	1@1	DFT_QPSK	24.50	23.68
n38	30	20	522000	1@49	DFT_QPSK	24.50	23.86
n77	30	10	620334	12@6	DFT_BPSK	25.00	23.78
n77	30	10	620334	1@1	DFT_BPSK	25.00	23.65
n77	30	10	620334	1@22	DFT_BPSK	25.00	23.70
n77	30	10	620334	12@6	DFT_QPSK	25.00	23.83
n77	30	10	620334	1@1	DFT_QPSK	25.00	23.66
n77	30	10	620334	1@22	DFT_QPSK	25.00	23.69
n77	30	10	650000	12@6	DFT_BPSK	25.00	24.21
n77	30	10	650000	1@1	DFT_BPSK	25.00	24.04
n77	30	10	650000	1@22	DFT_BPSK	25.00	24.16
n77	30	10	650000	12@6	DFT_QPSK	25.00	24.21
n77	30	10	650000	1@1	DFT_QPSK	25.00	24.03
n77	30	10	650000	1@22	DFT_QPSK	25.00	24.18
n77	30	10	679666	12@6	DFT_BPSK	25.00	24.58
n77	30	10	679666	1@1	DFT_BPSK	25.00	24.54
n77	30	10	679666	1@22	DFT_BPSK	25.00	24.54
n77	30	10	679666	12@6	DFT_QPSK	25.00	24.60
n77	30	10	679666	1@1	DFT_QPSK	25.00	24.50
n77	30	10	679666	1@22	DFT_QPSK	25.00	24.55
n77	30	50	621668	64@32	DFT_BPSK	25.00	23.77
n77	30	50	621668	1@1	DFT_BPSK	25.00	23.35
n77	30	50	621668	1@131	DFT_BPSK	25.00	23.57
n77	30	50	621668	64@32	DFT_QPSK	25.00	23.79
n77	30	50	621668	1@1	DFT_QPSK	25.00	23.32
n77	30	50	621668	1@131	DFT_QPSK	25.00	23.50

n77	30	50	650000	64@32	DFT_BPSK	25.00	24.20
n77	30	50	650000	1@1	DFT_BPSK	25.00	23.71
n77	30	50	650000	1@131	DFT_BPSK	25.00	23.95
n77	30	50	650000	64@32	DFT_QPSK	25.00	24.21
n77	30	50	650000	1@1	DFT_QPSK	25.00	23.68
n77	30	50	650000	1@131	DFT_QPSK	25.00	23.93
n77	30	50	678332	64@32	DFT_BPSK	25.00	24.36
n77	30	50	678332	1@1	DFT_BPSK	25.00	23.92
n77	30	50	678332	1@131	DFT_BPSK	25.00	24.15
n77	30	50	678332	64@32	DFT_QPSK	25.00	24.39
n77	30	50	678332	1@1	DFT_QPSK	25.00	23.85
n77	30	50	678332	1@131	DFT_QPSK	25.00	24.15
n77	30	100	623334	135@67	DFT_BPSK	25.00	23.85
n77	30	100	623334	1@1	DFT_BPSK	25.00	22.60
n77	30	100	623334	1@271	DFT_BPSK	25.00	22.71
n77	30	100	623334	135@67	DFT_QPSK	25.00	23.87
n77	30	100	623334	1@1	DFT_QPSK	25.00	22.57
n77	30	100	623334	1@271	DFT_QPSK	25.00	22.71
n77	30	100	650000	135@67	DFT_BPSK	25.00	24.09
n77	30	100	650000	1@1	DFT_BPSK	25.00	22.65
n77	30	100	650000	1@271	DFT_BPSK	25.00	23.58
n77	30	100	650000	135@67	DFT_QPSK	25.00	24.10
n77	30	100	650000	1@1	DFT_QPSK	25.00	22.62
n77	30	100	650000	1@271	DFT_QPSK	25.00	23.54
n77	30	100	676666	135@67	DFT_BPSK	25.00	24.24
n77	30	100	676666	1@1	DFT_BPSK	25.00	23.42
n77	30	100	676666	1@271	DFT_BPSK	25.00	23.49
n77	30	100	676666	135@67	DFT_QPSK	25.00	24.23
n77	30	100	676666	1@1	DFT_QPSK	25.00	23.41
n77	30	100	676666	1@271	DFT_QPSK	25.00	23.45
n78	30	10	647000	12@6	DFT_BPSK	25.00	23.96
n78	30	10	647000	1@1	DFT_BPSK	25.00	23.86
n78	30	10	647000	1@22	DFT_BPSK	25.00	23.96
n78	30	10	647000	12@6	DFT_QPSK	25.00	24.01
n78	30	10	647000	1@1	DFT_QPSK	25.00	23.86
n78	30	10	647000	1@22	DFT_QPSK	25.00	23.96
n78	30	10	650000	12@6	DFT_BPSK	25.00	24.46
n78	30	10	650000	1@1	DFT_BPSK	25.00	24.31
n78	30	10	650000	1@22	DFT_BPSK	25.00	24.42
n78	30	10	650000	12@6	DFT_QPSK	25.00	24.50

n78	30	10	650000	1@1	DFT_QPSK	25.00	24.29
n78	30	10	650000	1@22	DFT_QPSK	25.00	24.43
n78	30	10	653000	12@6	DFT_BPSK	25.00	24.77
n78	30	10	653000	1@1	DFT_BPSK	25.00	24.65
n78	30	10	653000	1@22	DFT_BPSK	25.00	24.75
n78	30	10	653000	12@6	DFT_QPSK	25.00	24.79
n78	30	10	653000	1@1	DFT_QPSK	25.00	24.67
n78	30	10	653000	1@22	DFT_QPSK	25.00	24.75
n78	30	50	648333	64@32	DFT_BPSK	25.00	24.10
n78	30	50	648333	1@1	DFT_BPSK	25.00	23.57
n78	30	50	648333	1@131	DFT_BPSK	25.00	24.06
n78	30	50	648333	64@32	DFT_QPSK	25.00	24.12
n78	30	50	648333	1@1	DFT_QPSK	25.00	23.55
n78	30	50	648333	1@131	DFT_QPSK	25.00	24.05
n78	30	50	650000	64@32	DFT_BPSK	25.00	24.44
n78	30	50	650000	1@1	DFT_BPSK	25.00	23.92
n78	30	50	650000	1@131	DFT_BPSK	25.00	24.38
n78	30	50	650000	64@32	DFT_QPSK	25.00	24.48
n78	30	50	650000	1@1	DFT_QPSK	25.00	23.91
n78	30	50	650000	1@131	DFT_QPSK	25.00	24.34
n78	30	50	651667	64@32	DFT_BPSK	25.00	24.66
n78	30	50	651667	1@1	DFT_BPSK	25.00	24.18
n78	30	50	651667	1@131	DFT_BPSK	25.00	24.70
n78	30	50	651667	64@32	DFT_QPSK	25.00	24.68
n78	30	50	651667	1@1	DFT_QPSK	25.00	24.16
n78	30	50	651667	1@131	DFT_QPSK	25.00	24.67
n78	30	100	650000	135@67	DFT_BPSK	25.00	21.40
n78	30	100	650000	1@1	DFT_BPSK	25.00	22.92
n78	30	100	650000	1@271	DFT_BPSK	25.00	24.07
n78	30	100	650000	135@67	DFT_QPSK	25.00	24.41
n78	30	100	650000	1@1	DFT_QPSK	25.00	22.90
n78	30	100	650000	1@271	DFT_QPSK	25.00	24.03
n8	30	10	177000	12@6	DFT_BPSK	25.00	23.91
n8	30	10	177000	1@1	DFT_BPSK	25.00	23.83
n8	30	10	177000	1@22	DFT_BPSK	25.00	23.83
n8	30	10	177000	12@6	DFT_QPSK	25.00	23.96
n8	30	10	177000	1@1	DFT_QPSK	25.00	24.09
n8	30	10	177000	1@22	DFT_QPSK	25.00	24.06
n8	30	10	179500	12@6	DFT_BPSK	25.00	23.58
n8	30	10	179500	1@1	DFT_BPSK	25.00	23.56

n8	30	10	179500	1@22	DFT_BPSK	25.00	23.43
n8	30	10	179500	12@6	DFT_QPSK	25.00	23.52
n8	30	10	179500	1@1	DFT_QPSK	25.00	23.74
n8	30	10	179500	1@22	DFT_QPSK	25.00	21.59
n8	30	10	182000	12@6	DFT_BPSK	25.00	23.82
n8	30	10	182000	1@1	DFT_BPSK	25.00	23.57
n8	30	10	182000	1@22	DFT_BPSK	25.00	23.73
n8	30	10	182000	12@6	DFT_QPSK	25.00	23.81
n8	30	10	182000	1@1	DFT_QPSK	25.00	24.22
n8	30	10	182000	1@22	DFT_QPSK	25.00	24.58
n8	30	15	177500	18@9	DFT_BPSK	25.00	23.75
n8	30	15	177500	1@1	DFT_BPSK	25.00	23.67
n8	30	15	177500	1@36	DFT_BPSK	25.00	23.63
n8	30	15	177500	18@9	DFT_QPSK	25.00	23.83
n8	30	15	177500	1@1	DFT_QPSK	25.00	24.01
n8	30	15	177500	1@36	DFT_QPSK	25.00	23.78
n8	30	15	179500	18@9	DFT_BPSK	25.00	23.49
n8	30	15	179500	1@1	DFT_BPSK	25.00	23.63
n8	30	15	179500	1@36	DFT_BPSK	25.00	23.48
n8	30	15	179500	18@9	DFT_QPSK	25.00	23.59
n8	30	15	179500	1@1	DFT_QPSK	25.00	23.82
n8	30	15	179500	1@36	DFT_QPSK	25.00	23.77
n8	30	15	181500	18@9	DFT_BPSK	25.00	23.68
n8	30	15	181500	1@1	DFT_BPSK	25.00	23.38
n8	30	15	181500	1@36	DFT_BPSK	25.00	23.68
n8	30	15	181500	18@9	DFT_QPSK	25.00	20.70
n8	30	15	181500	1@1	DFT_QPSK	25.00	24.38
n8	30	15	181500	1@36	DFT_QPSK	25.00	24.73
n8	30	20	178000	25@12	DFT_BPSK	25.00	23.77
n8	30	20	178000	1@1	DFT_BPSK	25.00	23.70
n8	30	20	178000	1@49	DFT_BPSK	25.00	23.40
n8	30	20	178000	25@12	DFT_QPSK	25.00	22.27
n8	30	20	178000	1@1	DFT_QPSK	25.00	24.59
n8	30	20	178000	1@49	DFT_QPSK	25.00	24.28
n8	30	20	179500	25@12	DFT_BPSK	25.00	23.59
n8	30	20	179500	1@1	DFT_BPSK	25.00	23.67
n8	30	20	179500	1@49	DFT_BPSK	25.00	23.53
n8	30	20	179500	25@12	DFT_QPSK	25.00	23.68
n8	30	20	179500	1@1	DFT_QPSK	25.00	24.18
n8	30	20	179500	1@49	DFT_QPSK	25.00	24.26

n8	30	20	181000	25@12	DFT_BPSK	25.00	23.64
n8	30	20	181000	1@1	DFT_BPSK	25.00	23.45
n8	30	20	181000	1@49	DFT_BPSK	25.00	23.65
n8	30	20	181000	25@12	DFT_QPSK	25.00	19.68
n8	30	20	181000	1@1	DFT_QPSK	25.00	24.15
n8	30	20	181000	1@49	DFT_QPSK	25.00	24.51

EN-DC

Band	SCS (kHz)	Bandwidth (MHz)	UL Channel	RB Allocation	Modulation	Power (dBm)
Band1	30	5	18025	1@LOW	QPSK	22.63
n78	30	10	647000	1@0	DFT_BPSK	22.41
Sum	30					25.53
Band1	30	5	18025	8@LOW	QPSK	22.73
n78	30	10	647000	12@6	DFT_BPSK	22.97
Sum	30					25.86
Band1	30	5	18025	1@LOW	QPSK	22.69
n78	30	10	647000	1@0	DFT_QPSK	22.49
Sum	30					25.6
Band1	30	5	18025	8@LOW	QPSK	22.74
n78	30	10	647000	12@6	DFT_QPSK	23.09
Sum	30					25.92
Band1	30	5	18300	8@LOW	QPSK	22.85
n78	30	10	650000	12@6	DFT_BPSK	23.03
Sum	30					25.95
Band1	30	5	18300	8@LOW	QPSK	22.84
n78	30	10	650000	12@6	DFT_QPSK	23.04
Sum	30					25.95
Band1	30	5	18575	1@HIGH	QPSK	22.77
n78	30	10	653000	1@23	DFT_BPSK	22.71
Sum	30					25.75
Band1	30	5	18575	8@HIGH	QPSK	22.7
n78	30	10	653000	12@6	DFT_BPSK	23.12
Sum	30					25.92
Band1	30	5	18575	1@HIGH	QPSK	22.78
n78	30	10	653000	1@23	DFT_QPSK	22.73
Sum	30					25.76
Band1	30	5	18575	8@HIGH	QPSK	22.72
n78	30	10	653000	12@6	DFT_QPSK	23.15
Sum	30					25.95

Band1	30	20	18100	1@LOW	QPSK	22.7
n78	30	100	650000	1@0	DFT_BPSK	21.47
Sum	30					25.13
Band1	30	20	18100	18@LOW	QPSK	22.68
n78	30	100	650000	135@67	DFT_BPSK	23.03
Sum	30					25.86
Band1	30	20	18100	1@LOW	QPSK	22.61
n78	30	100	650000	1@0	DFT_QPSK	21.54
Sum	30					25.11
Band1	30	20	18100	18@LOW	QPSK	22.7
n78	30	100	650000	135@67	DFT_QPSK	23.03
Sum	30					25.87

7.5. WLAN & Bluetooth Output Power

Mode	Channel	Frequency (MHz)	Tune - up	Output Power (dBm)
802.11b	1	2412	16.50	15.80
	7	2442	16.50	15.98
	13	2472	16.50	16.09
802.11g	1	2412	15.00	13.74
	7	2442	15.00	14.49
	13	2472	15.00	14.54
802.11n (HT20)	1	2412	14.00	12.77
	7	2442	14.00	13.36
	13	2472	14.00	13.58
802.11n (HT40)	3	2422	13.50	13.44
	7	2442	13.50	13.02
	11	2462	13.50	12.79

NOTE: Power measurement results of WLAN 2.4G.

Mode	Channel	Frequency (MHz)	Tune-up	Output Power (dBm)
802.11a	36	5180	10.00	9.74
	40	5200	10.00	9.70
	48	5240	10.00	9.65
802.11n HT20	36	5180	10.00	9.61
	40	5200	10.00	9.46
	48	5240	10.00	9.45
802.11n HT40	38	5190	9.50	8.41
	46	5230	9.50	9.35

802.11ac VHT20	36	5180	9.50	9.08
	40	5200	9.50	8.95
	48	5240	9.50	8.76
802.11ac VHT40	38	5190	8.50	8.42
	46	5230	8.50	8.24
802.11ac VHT80	42	5210	8.50	8.24

NOTE: Power measurement results of WLAN 5.2G.

Mode	Channel	Frequency (MHz)	Tune-up	Output Power (dBm)
802.11a	149	5745	10.50	9.34
	157	5785	10.50	9.76
	165	5825	10.50	10.02
802.11n HT20	149	5745	10.50	9.22
	157	5785	10.50	9.62
	165	5825	10.50	10.27
802.11n HT40	151	5755	10.50	9.54
	159	5795	10.50	10.01
802.11ac VHT20	149	5745	10.50	9.43
	157	5785	10.50	9.41
	165	5825	10.50	10.03
802.11ac VHT40	151	5755	10.00	9.22
	159	5795	10.00	9.70
802.11ac VHT80	155	5775	9.00	8.52

NOTE: Power measurement results of WLAN 5.8G.

BR+EDR	Data Rates	Tune - up	Output Power (dBm)
	GFSK DH5	10.00	9.61
	Pi/4 DQPSK DH5	7.00	6.79
	8DPSK DH5	7.00	6.51

BLE	Channel	Tune - up	Output Power (dBm)	
			Data Rates 1M	Data Rates 2M
	0CH	-7.00	-7.30	-7.27
	19CH	-7.00	-7.25	-7.24
	39CH	-7.00	-7.88	-7.88

NOTE: Power measurement results of Bluetooth. Refer to EN 62479, the available power of this EUT is 10.00dBm (10.00mW), the power is less than the low-power exclusion level defined in 4.2 (P max: 20mW), So Bluetooth stand-alone SAR is not required.

8. Assessment of the compliance of low power equipment

According to EN 62479 Clause 4.1& 4.2, these require does not apply to the receivers that has no transmit. So the FM and GPS is compliance.

NFC	Frequency (MHz)	H-Field(dBuA/m)@3m	Output Power (dBm)	Output Power (mW)	Limits (mW)
	13.56MHz	30.95	0.05	1.01	20

NOTE: Refer to EN 62479, the available power of this EUT is 0.05dBm (1.01mW), the power is less than the low-power exclusion level defined in 4.2 (P max: 20mW), So the NFC is compliance.

9. SAR Results

9.1. SAR measurement results

9.1.1. SAR measurement Result of GSM 900

Test Position	Test channel /Freq.	Mode	Separation distance (mm)	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 10-g (W/Kg)	Date
				1-g	10-g					
Head										
Left Cheek	38/897.6	GPRS(GMSK 3TS)	0	0.323	0.274	3.03	30.68	31.00	0.295	2022/3/07
Left Tilt 15 Degree	38/897.6	GPRS(GMSK 3TS)	0	0.166	0.138	1.15	30.68	31.00	0.149	2022/3/07
Right Cheek	38/897.6	GPRS(GMSK 3TS)	0	0.304	0.258	4.21	30.68	31.00	0.278	2022/3/07
Right Tilt 15 Degree	38/897.6	GPRS(GMSK 3TS)	0	0.165	0.137	-3.78	30.68	31.00	0.147	2022/3/07
Extremity										
Front Side	38/897.6	GPRS(GMSK 3TS)	0	0.893	0.462	-3.22	30.68	31.00	0.497	2022/3/07
Back Side	38/897.6	GPRS(GMSK 3TS)	0	1.396	0.753	1.78	30.68	31.00	0.811	2022/3/07
Left Side	38/897.6	GPRS(GMSK 3TS)	0	0.544	0.282	-3.28	30.68	31.00	0.304	2022/3/07
Right Side	38/897.6	GPRS(GMSK 3TS)	0	0.349	0.181	2.86	30.68	31.00	0.195	2022/3/07
Top Side	38/897.6	GPRS(GMSK 3TS)	0	0.209	0.113	-0.09	30.68	31.00	0.122	2022/3/07

Bottom Side	38/897.6	GPRS(GMSK 3TS)	0	0.712	0.380	3.49	30.68	31.00	0.409	2022/3/07
Body & Hotspot with 5mm (Worst-case position for 0mm)										
Back Side	38/897.6	GPRS(GMSK 3TS)	5	0.824	0.427	-0.96	30.68	31.00	0.460	2022/3/07

9.1.2. SAR measurement Result of GSM 1800

Test Position	Test channel /Freq.	Mode	Separation distance (mm)	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 10-g (W/Kg)	Date
				1-g	10-g					
Head										
Left Cheek	698/1747.4	GPRS(GMSK 4TS)	0	0.130	0.087	0.95	26.88	27.00	0.089	2022/2/26
Left Tilt 15 Degree	698/1747.4	GPRS(GMSK 4TS)	0	0.077	0.052	3.51	26.88	27.00	0.053	2022/2/26
Right Cheek	698/1747.4	GPRS(GMSK 4TS)	0	0.119	0.078	-1.40	26.88	27.00	0.080	2022/2/26
Right Tilt 15 Degree	698/1747.4	GPRS(GMSK 4TS)	0	0.055	0.037	1.18	26.88	27.00	0.038	2022/2/26
Extremity										
Front Side	698/1747.4	GPRS(GMSK 4TS)	0	1.050	0.517	3.75	26.88	27.00	0.531	2022/2/26
Back Side	698/1747.4	GPRS(GMSK 4TS)	0	1.693	0.859	1.90	26.88	27.00	0.883	2022/2/26
Left Side	698/1747.4	GPRS(GMSK 4TS)	0	0.626	0.308	-1.31	26.88	27.00	0.317	2022/2/26
Right Side	698/1747.4	GPRS(GMSK 4TS)	0	0.491	0.242	-0.97	26.88	27.00	0.249	2022/2/26
Top Side	698/1747.4	GPRS(GMSK 4TS)	0	0.237	0.119	-2.64	26.88	27.00	0.122	2022/2/26
Bottom Side	698/1747.4	GPRS(GMSK 4TS)	0	0.931	0.458	1.49	26.88	27.00	0.471	2022/2/26
Body & Hotspot with 5mm (Worst-case position for 0mm)										
Back Side	698/1747.4	GPRS(GMSK 4TS)	5	0.982	0.473	2.09	26.88	27.00	0.486	2022/2/26

9.1.3. SAR measurement Result of WCDMA Band 1

Test Position	Test channel /Freq	Mode	Separation distance (mm)	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 10-g (W/Kg)	Date
				1-g	10-g					
Head										
Left Cheek	9750/1950	RMC12.2K	0	0.087	0.056	-4.10	24.03	24.50	0.062	2022/2/28
Left Tilt 15 Degree	9750/1950	RMC12.2K	0	0.050	0.032	5.56	24.03	24.50	0.036	2022/2/28
Right Cheek	9750/1950	RMC12.2K	0	0.080	0.051	-3.82	24.03	24.50	0.057	2022/2/28
Right Tilt 15 Degree	9750/1950	RMC12.2K	0	0.044	0.028	3.50	24.03	24.50	0.031	2022/2/28
Extremity										
Front Side	9750/1950	RMC12.2K	0	1.256	0.579	-1.94	24.03	24.50	0.645	2022/2/28
Back Side	9750/1950	RMC12.2K	0	1.962	0.914	-0.95	24.03	24.50	1.018	2022/2/28
Left Side	9750/1950	RMC12.2K	0	0.726	0.331	1.98	24.03	24.50	0.369	2022/2/28
Right Side	9750/1950	RMC12.2K	0	0.589	0.272	1.70	24.03	24.50	0.303	2022/2/28
Top Side	9750/1950	RMC12.2K	0	0.216	0.096	1.56	24.03	24.50	0.107	2022/2/28
Bottom Side	9750/1950	RMC12.2K	0	1.079	0.483	-2.18	24.03	24.50	0.538	2022/2/28
Body & Hotspot with 5mm (Worst-case position for 0mm)										
Back Side	9750/1950	RMC12.2K	5	1.177	0.548	-1.99	24.03	24.50	0.611	2022/2/28

9.1.4. SAR measurement Result of WCDMA Band 8

Test Position	Test channel /Freq	Mode	Separation distance (mm)	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 10-g (W/Kg)	Date
				1-g	10-g					
Head										
Left Cheek	2788/897.6	RMC12.2K	0	0.193	0.167	0.42	23.33	23.50	0.174	2022/3/07
Left Tilt 15 Degree	2788/897.6	RMC12.2K	0	0.111	0.092	-3.52	23.33	23.50	0.096	2022/3/07
Right Cheek	2788/897.6	RMC12.2K	0	0.170	0.147	-0.43	23.33	23.50	0.153	2022/3/07
Right Tilt 15 Degree	2788/897.6	RMC12.2K	0	0.077	0.064	-2.65	23.33	23.50	0.067	2022/3/07
Extremity										
Front Side	2788/897.6	RMC12.2K	0	0.719	0.392	-1.54	23.33	23.50	0.408	2022/3/07
Back Side	2788/897.6	RMC12.2K	0	1.159	0.644	-1.65	23.33	23.50	0.670	2022/3/07
Left Side	2788/897.6	RMC12.2K	0	0.429	0.238	-0.63	23.33	23.50	0.248	2022/3/07
Right Side	2788/897.6	RMC12.2K	0	0.290	0.158	-0.21	23.33	23.50	0.164	2022/3/07
Top Side	2788/897.6	RMC12.2K	0	0.139	0.074	-2.70	23.33	23.50	0.077	2022/3/07
Bottom Side	2788/897.6	RMC12.2K	0	0.626	0.334	-2.04	23.33	23.50	0.347	2022/3/07

Body & Hotspot with 5mm (Worst-case position for 0mm)										
Back Side	2788/897.6	RMC12.2K	5	0.661	0.353	3.17	23.33	23.50	0.367	2022/3/07

9.1.5. SAR measurement Result of LTE Band 1

Test Position	Test channel /Freq.	Mode	Separation distance (mm)	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 10-g (W/Kg)	Date
				1-g	10-g					
Head										
Left Cheek	18300/1950	20M QPSK(1,0)	0	0.082	0.053	3.22	22.97	23.50	0.060	2022/2/28
Left Tilt 15 Degree	18300/1950	20M QPSK(1,0)	0	0.045	0.028	-1.80	22.97	23.50	0.032	2022/2/28
Right Cheek	18300/1950	20M QPSK(1,0)	0	0.071	0.044	-3.49	22.97	23.50	0.050	2022/2/28
Right Tilt 15 Degree	18300/1950	20M QPSK(1,0)	0	0.034	0.021	-4.32	22.97	23.50	0.024	2022/2/28
Extremity										
Front Side	18300/1950	20M QPSK(1,0)	0	1.074	0.481	-0.18	22.97	23.50	0.543	2022/2/28
Back Side	18300/1950	20M QPSK(1,0)	0	1.678	0.783	-1.06	22.97	23.50	0.885	2022/2/28
Left Side	18300/1950	20M QPSK(1,0)	0	0.638	0.286	0.30	22.97	23.50	0.323	2022/2/28
Right Side	18300/1950	20M QPSK(1,0)	0	0.470	0.217	3.65	22.97	23.50	0.245	2022/2/28
Top Side	18300/1950	20M QPSK(1,0)	0	0.168	0.077	-2.31	22.97	23.50	0.087	2022/2/28
Bottom Side	18300/1950	20M QPSK(1,0)	0	0.889	0.415	3.59	22.97	23.50	0.469	2022/2/28
Body & Hotspot with 5mm (Worst-case position for 0mm)										
Back Side	18300/1950	20M QPSK(1,0)	5	0.956	0.433	-3.73	22.97	23.50	0.489	2022/2/28

9.1.6. SAR measurement Result of LTE Band 3

Test Position	Test channel	Mode	Separation	SAR Value	Power	Conducted	Tune-up	Scaled	Date
---------------	--------------	------	------------	-----------	-------	-----------	---------	--------	------

	/Freq.		distance (mm)	(W/kg)		Drift(%)	Power (dBm)	Power (dBm)	SAR 10-g (W/Kg)	
				1-g	10-g					
Head										
Left Cheek	19575/1747.5	20M QPSK(1,0)	0	0.124	0.085	-3.31	23.34	23.50	0.088	2022/2/26
Left Tilt 15 Degree	19575/1747.5	20M QPSK(1,0)	0	0.070	0.046	5.15	23.34	23.50	0.048	2022/2/26
Right Cheek	19575/1747.5	20M QPSK(1,0)	0	0.117	0.076	1.89	23.34	23.50	0.079	2022/2/26
Right Tilt 15 Degree	19575/1747.5	20M QPSK(1,0)	0	0.053	0.035	2.90	23.34	23.50	0.036	2022/2/26
Extremity										
Front Side	19575/1747.5	20M QPSK(1,0)	0	0.925	0.472	3.43	23.34	23.50	0.490	2022/2/26
Back Side	19575/1747.5	20M QPSK(1,0)	0	1.446	0.753	-0.52	23.34	23.50	0.781	2022/2/26
Left Side	19575/1747.5	20M QPSK(1,0)	0	0.506	0.263	1.18	23.34	23.50	0.273	2022/2/26
Right Side	19575/1747.5	20M QPSK(1,0)	0	0.405	0.200	-2.65	23.34	23.50	0.208	2022/2/26
Top Side	19575/1747.5	20M QPSK(1,0)	0	0.174	0.089	-2.15	23.34	23.50	0.092	2022/2/26
Bottom Side	19575/1747.5	20M QPSK(1,0)	0	0.723	0.361	-0.42	23.34	23.50	0.375	2022/2/26
Body & Hotspot with 5mm (Worst-case position for 0mm)										
Back Side	19575/1747.5	20M QPSK(1,0)	5	0.839	0.419	0.28	23.34	23.50	0.435	2022/2/26

9.1.7. SAR measurement Result of LTE Band 7

Test Position	Test channel /Freq.	Mode	Separation distance (mm)	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 10-g (W/Kg)	Date
				1-g	10-g					
Head										
Left Cheek	21100/2535	20M QPSK(1,0)	0	0.093	0.056	-1.63	24.31	24.50	0.059	2022/3/03
Left Tilt 15 Degree	21100/2535	20M	0	0.049	0.029	-0.03	24.31	24.50	0.030	2022/3/03

		QPSK(1,0)								
Right Cheek	21100/2535	20M QPSK(1,0)	0	0.083	0.048	-1.42	24.31	24.50	0.050	2022/3/03
Right Tilt 15 Degree	21100/2535	20M QPSK(1,0)	0	0.040	0.023	-3.18	24.31	24.50	0.024	2022/3/03
Extremity										
Front Side	21100/2535	20M QPSK(1,0)	0	1.749	0.773	-2.64	24.31	24.50	0.808	2022/3/03
Back Side	21100/2535	20M QPSK(1,0)	0	2.915	1.356	-1.02	24.31	24.50	1.417	2022/3/03
Left Side	21100/2535	20M QPSK(1,0)	0	1.049	0.488	2.70	24.31	24.50	0.510	2022/3/03
Right Side	21100/2535	20M QPSK(1,0)	0	0.875	0.387	2.58	24.31	24.50	0.404	2022/3/03
Top Side	21100/2535	20M QPSK(1,0)	0	0.437	0.197	-2.94	24.31	24.50	0.206	2022/3/03
Bottom Side	21100/2535	20M QPSK(1,0)	0	1.574	0.732	-3.00	24.31	24.50	0.765	2022/3/03
Body & Hotspot with 5mm (Worst-case position for 0mm)										
Back Side	21100/2535	20M QPSK(1,0)	5	1.720	0.768	2.55	24.31	24.50	0.802	2022/3/03

9.1.8. SAR measurement Result of LTE Band 8

Test Position	Test channel /Freq.	Mode	Separation distance (mm)	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 10-g (W/Kg)	Date
				1-g	10-g					
Head										
Left Cheek	21625/897.5	10M QPSK(1,0)	0	0.219	0.189	-1.09	23.74	24.00	0.201	2022/3/07
Left Tilt 15 Degree	21625/897.5	10M QPSK(1,0)	0	0.120	0.104	-1.64	23.74	24.00	0.110	2022/3/07
Right Cheek	21625/897.5	10M QPSK(1,0)	0	0.190	0.162	-0.83	23.74	24.00	0.172	2022/3/07
Right Tilt 15 Degree	21625/897.5	10M QPSK(1,0)	0	0.087	0.071	-3.46	23.74	24.00	0.075	2022/3/07
Extremity										
Front Side	21625/897.5	10M	0	0.790	0.440	-2.42	23.74	24.00	0.467	2022/3/07

		QPSK(1,0)								
Back Side	21625/897.5	10M QPSK(1,0)	0	1.274	0.716	-0.43	23.74	24.00	0.760	2022/3/07
Left Side	21625/897.5	10M QPSK(1,0)	0	0.497	0.274	3.58	23.74	24.00	0.291	2022/3/07
Right Side	21625/897.5	10M QPSK(1,0)	0	0.319	0.177	1.62	23.74	24.00	0.188	2022/3/07
Top Side	21625/897.5	10M QPSK(1,0)	0	0.127	0.071	0.50	23.74	24.00	0.075	2022/3/07
Bottom Side	21625/897.5	10M QPSK(1,0)	0	0.662	0.368	2.84	23.74	24.00	0.391	2022/3/07
Body & Hotspot with 5mm (Worst-case position for 0mm)										
Back Side	21625/897.5	10M QPSK(1,0)	5	0.764	0.425	2.91	23.74	24.00	0.451	2022/3/07

9.1.9. SAR measurement Result of LTE Band 20

Test Position	Test channel /Freq.	Mode	Separation distance (mm)	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 10-g (W/Kg)	Date
				1-g	10-g					
Head										
Left Cheek	24300/847	20M QPSK(1,0)	0	0.194	0.171	-1.24	23.23	23.50	0.182	2022/3/07
Left Tilt 15 Degree	24300/847	20M QPSK(1,0)	0	0.114	0.096	0.39	23.23	23.50	0.102	2022/3/07
Right Cheek	24300/847	20M QPSK(1,0)	0	0.183	0.161	4.99	23.23	23.50	0.171	2022/3/07
Right Tilt 15 Degree	24300/847	20M QPSK(1,0)	0	0.095	0.080	-3.71	23.23	23.50	0.085	2022/3/07
Extremity										
Front Side	24300/847	20M QPSK(1,0)	0	0.670	0.369	1.19	23.23	23.50	0.393	2022/3/07
Back Side	24300/847	20M QPSK(1,0)	0	1.080	0.600	-0.53	23.23	23.50	0.638	2022/3/07
Left Side	24300/847	20M QPSK(1,0)	0	0.421	0.234	-3.53	23.23	23.50	0.249	2022/3/07
Right Side	24300/847	20M QPSK(1,0)	0	0.313	0.167	-3.20	23.23	23.50	0.178	2022/3/07

Top Side	24300/847	20M QPSK(1,0)	0	0.140	0.077	2.36	23.23	23.50	0.082	2022/3/07
Bottom Side	24300/847	20M QPSK(1,0)	0	0.562	0.297	2.24	23.23	23.50	0.316	2022/3/07
Body & Hotspot with 5mm (Worst-case position for 0mm)										
Back Side	24300/847	20M QPSK(1,0)	5	0.616	0.342	-2.03	23.23	23.50	0.364	2022/3/07

9.1.10. SAR measurement Result of LTE Band 28

Test Position	Test channel /Freq.	Mode	Separation distance (mm)	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 10-g (W/Kg)	Date
				1-g	10-g					
Head										
Left Cheek	27460/728	20M QPSK(1,0)	0	0.230	0.206	-3.09	23.66	24.00	0.223	2022/2/25
Left Tilt 15 Degree	27460/728	20M QPSK(1,0)	0	0.125	0.109	-1.11	23.66	24.00	0.118	2022/2/25
Right Cheek	27460/728	20M QPSK(1,0)	0	0.198	0.176	-0.04	23.66	24.00	0.190	2022/2/25
Right Tilt 15 Degree	27460/728	20M QPSK(1,0)	0	0.104	0.093	-0.07	23.66	24.00	0.101	2022/2/25
Extremity										
Front Side	27460/728	20M QPSK(1,0)	0	0.695	0.368	-2.99	23.66	24.00	0.398	2022/2/25
Back Side	27460/728	20M QPSK(1,0)	0	1.158	0.638	-1.10	23.66	24.00	0.690	2022/2/25
Left Side	27460/728	20M QPSK(1,0)	0	0.405	0.223	0.71	23.66	24.00	0.241	2022/2/25
Right Side	27460/728	20M QPSK(1,0)	0	0.290	0.155	3.13	23.66	24.00	0.168	2022/2/25
Top Side	27460/728	20M QPSK(1,0)	0	0.127	0.070	-2.24	23.66	24.00	0.076	2022/2/25
Bottom Side	27460/728	20M QPSK(1,0)	0	0.637	0.344	3.56	23.66	24.00	0.372	2022/2/25
Body & Hotspot with 5mm (Worst-case position for 0mm)										
Back Side	27460/728	20M QPSK(1,0)	5	0.683	0.365	-2.86	23.66	24.00	0.395	2022/2/25

9.1.11. SAR measurement Result of LTE Band 40

Test Position	Test channel /Freq.	Mode	Separation distance (mm)	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 10-g (W/Kg)	Date
				1-g	10-g					
Head										
Left Cheek	39150/2350	20M QPSK(1,0)	0	0.057	0.035	-2.49	21.89	23.50	0.051	2022/3/01
Left Tilt 15 Degree	39150/2350	20M QPSK(1,0)	0	0.029	0.017	4.10	21.89	23.50	0.025	2022/3/01
Right Cheek	39150/2350	20M QPSK(1,0)	0	0.049	0.030	2.87	21.89	23.50	0.043	2022/3/01
Right Tilt 15 Degree	39150/2350	20M QPSK(1,0)	0	0.024	0.014	-4.96	21.89	23.50	0.020	2022/3/01
Extremity										
Front Side	39150/2350	20M QPSK(1,0)	0	1.533	0.653	2.26	21.89	23.50	0.946	2022/3/01
Back Side	39150/2350	20M QPSK(1,0)	0	2.473	1.098	0.67	21.89	23.50	1.591	2022/3/01
Left Side	39150/2350	20M QPSK(1,0)	0	0.989	0.417	0.65	21.89	23.50	0.604	2022/3/01
Right Side	39150/2350	20M QPSK(1,0)	0	0.717	0.312	3.54	21.89	23.50	0.452	2022/3/01
Top Side	39150/2350	20M QPSK(1,0)	0	0.346	0.152	-3.98	21.89	23.50	0.220	2022/3/01
Bottom Side	39150/2350	20M QPSK(1,0)	0	1.311	0.570	1.33	21.89	23.50	0.826	2022/3/01
Body & Hotspot with 5mm (Worst-case position for 0mm)										
Back Side	39150/2350	20M QPSK(1,0)	5	1.574	0.664	-1.16	21.89	23.50	0.962	2022/3/01

9.1.12. SAR measurement Result of NR N1

Test Position	Test channel /Freq.	Mode	Separation distance (mm)	SAR Value (W/kg)		Power Drift(%)	Conducted	Tune-up	Scaled	Date
				1-g	10-g		Power (dBm)	Power (dBm)	SAR 10-g (W/Kg)	

Head										
Left Cheek	390000/1950	30kHz 20M QPSK(1,1)	0	0.061	0.042	-3.62	22.64	23.50	0.051	2022/2/28
Left Tilt 15 Degree	390000/1950	30kHz 20M QPSK(1,1)	0	0.034	0.023	5.13	22.64	23.50	0.028	2022/2/28
Right Cheek	390000/1950	30kHz 20M QPSK(1,1)	0	0.056	0.038	2.81	22.64	23.50	0.046	2022/2/28
Right Tilt 15 Degree	390000/1950	30kHz 20M QPSK(1,1)	0	0.028	0.019	-4.75	22.64	23.50	0.023	2022/2/28
Extremity										
Front Side	390000/1950	30kHz 20M QPSK(1,1)	0	0.746	0.331	-2.42	22.64	23.50	0.403	2022/2/28
Back Side	390000/1950	30kHz 20M QPSK(1,1)	0	1.223	0.565	-0.98	22.64	23.50	0.689	2022/2/28
Left Side	390000/1950	30kHz 20M QPSK(1,1)	0	0.428	0.188	0.12	22.64	23.50	0.229	2022/2/28
Right Side	390000/1950	30kHz 20M QPSK(1,1)	0	0.355	0.164	2.76	22.64	23.50	0.200	2022/2/28
Top Side	390000/1950	30kHz 20M QPSK(1,1)	0	0.135	0.060	-0.35	22.64	23.50	0.073	2022/2/28
Bottom Side	390000/1950	30kHz 20M QPSK(1,1)	0	0.673	0.305	1.32	22.64	23.50	0.372	2022/2/28
Body & Hotspot with 5mm (Worst-case position for 0mm)										
Back Side	390000/1950	30kHz 20M QPSK(1,1)	5	0.709	0.311	-0.85	22.64	23.50	0.379	2022/2/28

9.1.13. SAR measurement Result of NR N3

Test Position	Test channel /Freq.	Mode	Separation distance (mm)	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 10-g (W/Kg)	Date
				1-g	10-g					
Head										
Left Cheek	349500/1747.5	30kHz 30M QPSK(1,1)	0	0.111	0.074	-2.58	23.99	25.00	0.093	2022/2/26
Left Tilt 15 Degree	349500/1747.5	30kHz 30M QPSK(1,1)	0	0.064	0.042	1.04	23.99	25.00	0.053	2022/2/26
Right Cheek	349500/1747.5	30kHz 30M QPSK(1,1)	0	0.100	0.064	4.51	23.99	25.00	0.081	2022/2/26

Right Tilt 15 Degree	349500/1747.5	30kHz 30M QPSK(1,1)	0	0.053	0.034	-1.41	23.99	25.00	0.043	2022/2/26
Extremity										
Front Side	349500/1747.5	30kHz 30M QPSK(1,1)	0	0.801	0.398	0.21	23.99	25.00	0.502	2022/2/26
Back Side	349500/1747.5	30kHz 30M QPSK(1,1)	0	1.252	0.641	-1.47	23.99	25.00	0.809	2022/2/26
Left Side	349500/1747.5	30kHz 30M QPSK(1,1)	0	0.476	0.234	1.81	23.99	25.00	0.295	2022/2/26
Right Side	349500/1747.5	30kHz 30M QPSK(1,1)	0	0.338	0.170	3.40	23.99	25.00	0.215	2022/2/26
Top Side	349500/1747.5	30kHz 30M QPSK(1,1)	0	0.175	0.089	-0.67	23.99	25.00	0.112	2022/2/26
Bottom Side	349500/1747.5	30kHz 30M QPSK(1,1)	0	0.639	0.317	-0.96	23.99	25.00	0.400	2022/2/26
Body & Hotspot with 5mm (Worst-case position for 0mm)										
Back Side	349500/1747.5	30kHz 30M QPSK(1,1)	5	0.739	0.359	0.06	23.99	25.00	0.453	2022/2/26

9.1.14. SAR measurement Result of NR N8

Test Position	Test channel /Freq.	Mode	Separation distance (mm)	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 10-g (W/Kg)	Date
				1-g	10-g					
Head										
Left Cheek	179500/897.5	30kHz 20M QPSK(1,1)	0	0.161	0.139	-4.87	24.18	25.00	0.168	2022/3/07
Left Tilt 15 Degree	179500/897.5	30kHz 20M QPSK(1,1)	0	0.088	0.074	4.97	24.18	25.00	0.089	2022/3/07
Right Cheek	179500/897.5	30kHz 20M QPSK(1,1)	0	0.153	0.125	3.57	24.18	25.00	0.151	2022/3/07
Right Tilt 15 Degree	179500/897.5	30kHz 20M QPSK(1,1)	0	0.072	0.061	-2.09	24.18	25.00	0.074	2022/3/07
Extremity										
Front Side	179500/897.5	30kHz 20M QPSK(1,1)	0	0.572	0.309	-0.66	24.18	25.00	0.373	2022/3/07
Back Side	179500/897.5	30kHz 20M QPSK(1,1)	0	0.922	0.508	-0.82	24.18	25.00	0.614	2022/3/07

Left Side	179500/897.5	30kHz 20M QPSK(1,1)	0	0.323	0.178	3.32	24.18	25.00	0.215	2022/3/07
Right Side	179500/897.5	30kHz 20M QPSK(1,1)	0	0.258	0.139	-3.79	24.18	25.00	0.168	2022/3/07
Top Side	179500/897.5	30kHz 20M QPSK(1,1)	0	0.138	0.074	0.71	24.18	25.00	0.089	2022/3/07
Bottom Side	179500/897.5	30kHz 20M QPSK(1,1)	0	0.507	0.279	-3.58	24.18	25.00	0.337	2022/3/07
Body & Hotspot with 5mm (Worst-case position for 0mm)										
Back Side	179500/897.5	30kHz 20M QPSK(1,1)	5	0.526	0.281	0.13	24.18	25.00	0.339	2022/3/07

9.1.15. SAR measurement Result of NR N20

Test Position	Test channel /Freq.	Mode	Separation distance (mm)	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 10-g (W/Kg)	Date
				1-g	10-g					
Head										
Left Cheek	169400/847	30kHz 20M QPSK(1,1)	0	0.139	0.121	-0.56	23.37	24.50	0.157	2022/3/07
Left Tilt 15 Degree	169400/847	30kHz 20M QPSK(1,1)	0	0.074	0.063	3.03	23.37	24.50	0.082	2022/3/07
Right Cheek	169400/847	30kHz 20M QPSK(1,1)	0	0.128	0.109	-3.91	23.37	24.50	0.141	2022/3/07
Right Tilt 15 Degree	169400/847	30kHz 20M QPSK(1,1)	0	0.065	0.055	0.47	23.37	24.50	0.071	2022/3/07
Extremity										
Front Side	169400/847	30kHz 20M QPSK(1,1)	0	0.443	0.253	3.11	23.37	24.50	0.328	2022/3/07
Back Side	169400/847	30kHz 20M QPSK(1,1)	0	0.727	0.424	-0.04	23.37	24.50	0.550	2022/3/07
Left Side	169400/847	30kHz 20M QPSK(1,1)	0	0.269	0.154	-1.96	23.37	24.50	0.200	2022/3/07
Right Side	169400/847	30kHz 20M QPSK(1,1)	0	0.189	0.108	-1.86	23.37	24.50	0.140	2022/3/07
Top Side	169400/847	30kHz 20M QPSK(1,1)	0	0.080	0.044	-2.98	23.37	24.50	0.057	2022/3/07
Bottom Side	169400/847	30kHz 20M	0	0.400	0.229	-1.75	23.37	24.50	0.297	2022/3/07

		QPSK(1,1)								
Body & Hotspot with 5mm (Worst-case position for 0mm)										
Back Side	169400/847	30kHz 20M QPSK(1,1)	5	0.422	0.234	1.41	23.37	24.50	0.304	2022/3/07

9.1.16. SAR measurement Result of NR N28

Test Position	Test channel /Freq.	Mode	Separation distance (mm)	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 10-g (W/Kg)	Date
				1-g	10-g					
Head										
Left Cheek	145100/725.5	30kHz 20M QPSK(1,1)	0	0.175	0.134	-2.95	23.72	25.00	0.180	2022/2/25
Left Tilt 15 Degree	145100/725.5	30kHz 20M QPSK(1,1)	0	0.073	0.067	4.95	23.72	25.00	0.090	2022/2/25
Right Cheek	145100/725.5	30kHz 20M QPSK(1,1)	0	0.133	0.118	-3.83	23.72	25.00	0.158	2022/2/25
Right Tilt 15 Degree	145100/725.5	30kHz 20M QPSK(1,1)	0	0.065	0.060	2.80	23.72	25.00	0.081	2022/2/25
Extremity										
Front Side	145100/725.5	30kHz 20M QPSK(1,1)	0	0.505	0.283	0.34	23.72	25.00	0.380	2022/2/25
Back Side	145100/725.5	30kHz 20M QPSK(1,1)	0	0.802	0.463	-0.72	23.72	25.00	0.622	2022/2/25
Left Side	145100/725.5	30kHz 20M QPSK(1,1)	0	0.321	0.185	-1.64	23.72	25.00	0.248	2022/2/25
Right Side	145100/725.5	30kHz 20M QPSK(1,1)	0	0.201	0.113	1.13	23.72	25.00	0.152	2022/2/25
Top Side	145100/725.5	30kHz 20M QPSK(1,1)	0	0.080	0.046	-0.02	23.72	25.00	0.062	2022/2/25
Bottom Side	145100/725.5	30kHz 20M QPSK(1,1)	0	0.441	0.250	-2.62	23.72	25.00	0.336	2022/2/25
Body & Hotspot with 5mm (Worst-case position for 0mm)										
Back Side	145100/725.5	30kHz 20M QPSK(1,1)	5	0.481	0.269	3.04	23.72	25.00	0.361	2022/2/25

9.1.17. SAR measurement Result of NR N38

Test Position	Test channel /Freq.	Mode	Separation distance (mm)	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 10-g (W/Kg)	Date
				1-g	10-g					
Head										
Left Cheek	519000/2595	30kHz 20M QPSK(1,1)	0	0.119	0.068	1.34	24.14	24.50	0.074	2022/3/03
Left Tilt 15 Degree	519000/2595	30kHz 20M QPSK(1,1)	0	0.070	0.039	-2.86	24.14	24.50	0.042	2022/3/03
Right Cheek	519000/2595	30kHz 20M QPSK(1,1)	0	0.109	0.062	3.79	24.14	24.50	0.067	2022/3/03
Right Tilt 15 Degree	519000/2595	30kHz 20M QPSK(1,1)	0	0.055	0.031	-3.88	24.14	24.50	0.034	2022/3/03
Extremity										
Front Side	519000/2595	30kHz 20M QPSK(1,1)	0	1.373	0.577	3.15	24.14	24.50	0.627	2022/3/03
Back Side	519000/2595	30kHz 20M QPSK(1,1)	0	2.214	0.940	0.51	24.14	24.50	1.021	2022/3/03
Left Side	519000/2595	30kHz 20M QPSK(1,1)	0	0.886	0.361	-2.18	24.14	24.50	0.392	2022/3/03
Right Side	519000/2595	30kHz 20M QPSK(1,1)	0	0.598	0.249	3.69	24.14	24.50	0.271	2022/3/03
Top Side	519000/2595	30kHz 20M QPSK(1,1)	0	0.266	0.107	3.97	24.14	24.50	0.116	2022/3/03
Bottom Side	519000/2595	30kHz 20M QPSK(1,1)	0	1.151	0.464	-1.93	24.14	24.50	0.504	2022/3/03
Body & Hotspot with 5mm (Worst-case position for 0mm)										
Back Side	519000/2595	30kHz 20M QPSK(1,1)	5	1.284	0.523	2.38	24.14	24.50	0.568	2022/3/03

9.1.18. SAR measurement Result of NR N77

Test Position	Test channel /Freq.	Mode	Separation distance (mm)	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 10-g (W/Kg)	Date
				1-g	10-g					
Head										
Left Cheek	650000/3750	30kHz 100M QPSK(1,1)	0	0.750	0.258	1.77	22.62	25.00	0.446	2022/3/10

Left Tilt 15 Degree	650000/3750	30kHz 100M QPSK(1,1)	0	0.413	0.142	-0.27	22.62	25.00	0.246	2022/3/10
Right Cheek	650000/3750	30kHz 100M QPSK(1,1)	0	0.665	0.220	-3.83	22.62	25.00	0.381	2022/3/10
Right Tilt 15 Degree	650000/3750	30kHz 100M QPSK(1,1)	0	0.319	0.110	1.90	22.62	25.00	0.190	2022/3/10
Extremity										
Front Side	650000/3750	30kHz 100M QPSK(1,1)	0	2.040	0.658	2.08	22.62	25.00	1.138	2022/3/10
Back Side	650000/3750	30kHz 100M QPSK(1,1)	0	3.344	1.124	-0.11	22.62	25.00	1.944	2022/3/10
Left Side	650000/3750	30kHz 100M QPSK(1,1)	0	1.639	0.534	2.39	22.62	25.00	0.924	2022/3/10
Right Side	650000/3750	30kHz 100M QPSK(1,1)	0	0.669	0.223	3.36	22.62	25.00	0.386	2022/3/10
Top Side	650000/3750	30kHz 100M QPSK(1,1)	0	1.204	0.405	-1.69	22.62	25.00	0.701	2022/3/10
Bottom Side	650000/3750	30kHz 100M QPSK(1,1)	0	0.468	0.149	3.14	22.62	25.00	0.258	2022/3/10
Body & Hotspot with 5mm (Worst-case position for 0mm)										
Back Side	650000/3750	30kHz 100M QPSK(1,1)	5	1.906	0.575	-2.82	22.62	25.00	0.995	2022/3/10

9.1.19. SAR measurement Result of NR N78

Front Side	650000/3750	30kHz 100M QPSK(1,1)	0	1.388	0.492	1.23	22.90	25.00	0.798	2022/3/10
Back Side	650000/3750	30kHz 100M QPSK(1,1)	0	2.313	0.829	-1.11	22.90	25.00	1.344	2022/3/10
Left Side	650000/3750	30kHz 100M QPSK(1,1)	0	1.133	0.390	-3.36	22.90	25.00	0.633	2022/3/10
Right Side	650000/3750	30kHz 100M QPSK(1,1)	0	0.439	0.156	0.33	22.90	25.00	0.253	2022/3/10
Top Side	650000/3750	30kHz 100M QPSK(1,1)	0	0.856	0.295	3.24	22.90	25.00	0.478	2022/3/10
Bottom Side	650000/3750	30kHz 100M QPSK(1,1)	0	0.254	0.086	-2.82	22.90	25.00	0.139	2022/3/10
Body & Hotspot with 5mm (Worst-case position for 0mm)										
Back Side	650000/3750	30kHz 100M QPSK(1,1)	5	1.388	0.492	-1.14	22.90	25.00	0.798	2022/3/10

9.1.20. SAR measurement Result of WLAN 2.4G

Test Position	Test channel /Freq.	Mode	Separation distance (mm)	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 10-g (W/Kg)	Date
				1-g	10-g					
Head										
Left Cheek	7/2442	802.11 b	0	0.191	0.099	0.41	15.98	16.50	0.112	2022/3/02
Left Tilt 15 Degree	7/2442	802.11 b	0	0.096	0.047	0.62	15.98	16.50	0.053	2022/3/02
Right Cheek	7/2442	802.11 b	0	0.176	0.091	0.57	15.98	16.50	0.103	2022/3/02
Right Tilt 15 Degree	7/2442	802.11 b	0	0.093	0.047	2.53	15.98	16.50	0.053	2022/3/02
Extremity										
Front Side	7/2442	802.11 b	0	0.170	0.079	-0.36	15.98	16.50	0.089	2022/3/02
Back Side	7/2442	802.11 b	0	0.265	0.130	-1.95	15.98	16.50	0.147	2022/3/02
Left Side	7/2442	802.11 b	0	0.048	0.024	-2.81	15.98	16.50	0.027	2022/3/02
Right Side	7/2442	802.11	0	0.119	0.055	-2.06	15.98	16.50	0.062	2022/3/02

		b								
Top Side	7/2442	802.11 b	0	0.154	0.073	1.70	15.98	16.50	0.082	2022/3/02
Bottom Side	7/2442	802.11 b	0	0.034	0.016	-1.92	15.98	16.50	0.018	2022/3/02
Body & Hotspot with 5mm (Worst-case position for 0mm)										
Back Side	7/2442	802.11 b	5	0.140	0.066	-0.09	15.98	16.50	0.074	2022/3/02

9.1.21. SAR measurement Result of WLAN 5.2G

Test Position	Test channel /Freq	Mode	Separation distance (mm)	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 10-g (W/Kg)	Date
				1-g	10-g					
Head										
Left Cheek	40/5200	802.11 a	0	0.233	0.105	-0.30	9.70	10.00	0.113	2022/3/08
Left Tilt 15 Degree	40/5200	802.11 a	0	0.136	0.059	-2.92	9.70	10.00	0.063	2022/3/08
Right Cheek	40/5200	802.11 a	0	0.208	0.090	4.00	9.70	10.00	0.096	2022/3/08
Right Tilt 15 Degree	40/5200	802.11 a	0	0.102	0.046	1.10	9.70	10.00	0.049	2022/3/08
Extremity										
Front Side	40/5200	802.11 a	0	0.185	0.068	-0.64	9.70	10.00	0.073	2022/3/08
Back Side	40/5200	802.11 a	0	0.284	0.108	-4.51	9.70	10.00	0.116	2022/3/08
Left Side	40/5200	802.11 a	0	0.043	0.016	-3.98	9.70	10.00	0.017	2022/3/08
Right Side	40/5200	802.11 a	0	0.136	0.051	3.48	9.70	10.00	0.055	2022/3/08
Top Side	40/5200	802.11 a	0	0.162	0.061	3.84	9.70	10.00	0.065	2022/3/08
Bottom Side	40/5200	802.11 a	0	0.034	0.013	1.80	9.70	10.00	0.014	2022/3/08
Body & Hotspot with 5mm (Worst-case position for 0mm)										
Back Side	40/5200	802.11	5	0.156	0.058	1.84	9.70	10.00	0.062	2022/3/08

a

9.1.22. SAR measurement Result of WLAN 5.8G

Test Position	Test channel /Freq	Mode	Separation distance (mm)	SAR Value (W/kg)		Power Drift(%)	Conducted Power (dBm)	Tune-up Power (dBm)	Scaled SAR 10-g (W/Kg)	Date
				1-g	10-g					
Head										
Left Cheek	157/5785	802.11 a	0	1.525	0.483	-2.28	9.76	10.50	0.573	2022/3/09
Left Tilt 15 Degree	157/5785	802.11 a	0	0.793	0.239	5.99	9.76	10.50	0.283	2022/3/09
Right Cheek	157/5785	802.11 a	0	1.371	0.430	-1.66	9.76	10.50	0.510	2022/3/09
Right Tilt 15 Degree	157/5785	802.11 a	0	0.699	0.210	2.30	9.76	10.50	0.249	2022/3/09
Extremity										
Front Side	157/5785	802.11 a	0	0.389	0.133	-2.52	9.76	10.50	0.158	2022/3/09
Back Side	157/5785	802.11 a	0	0.598	0.210	0.51	9.76	10.50	0.249	2022/3/09
Left Side	157/5785	802.11 a	0	0.096	0.033	-1.00	9.76	10.50	0.039	2022/3/09
Right Side	157/5785	802.11 a	0	0.275	0.095	-3.47	9.76	10.50	0.113	2022/3/09
Top Side	157/5785	802.11 a	0	0.359	0.125	-0.53	9.76	10.50	0.148	2022/3/09
Bottom Side	157/5785	802.11 a	0	0.072	0.024	-2.75	9.76	10.50	0.028	2022/3/09
Body & Hotspot with 5mm (Worst-case position for 0mm)										
Back Side	157/5785	802.11 a	5	0.311	0.104	0.72	9.76	10.50	0.123	2022/3/09

9.2. Simultaneous Transmission Analysis

Refer to EN 62209-2:2010 Annex K, the secondary transmitter SAR test exclusion thresholds are determined by:

$$P_{\text{available}} = P_{\text{th,m}} \left(\frac{\text{SAR}_{\text{lim}} - \text{SAR}_1}{\text{SAR}_{\text{lim}}} \right)$$

$P_{th, m}$ is the threshold exclusion power level taken from Annex B of EN 62479.

Mode	P_{max} (dBm)	P_{max} (mW)	$P_{th, m}$ (mW)	SAR_{lim} (W/Kg)	SAR_1 (W/Kg)	Calculation Result (mW)	Simultaneous Transmission Exclusion
Bluetooth	10.00	10.00	20	2	0.995	10.05	YES
NFC	0.05	1.01	20	2	0.995	10.05	YES
Bluetooth	10.00	10.00	40	4	1.944	20.56	YES
NFC	0.05	1.01	40	4	1.944	20.56	YES

9.3. Exposure Conditions

Exposure Position		WWAN Band	WLAN Band	Simultaneous Tx SAR(W/Kg)
		SAR(W/Kg)	SAR(W/Kg)	
Head	Left Cheek	0.446	0.573	1.019
	Left Tilt 15 Degree	0.246	0.283	0.529
	Right Cheek	0.381	0.510	0.891
	Right Tilt 15 Degree	0.190	0.249	0.439
Member	Front Side	1.138	0.158	1.296
	Back Side	1.944	0.249	2.193
	Left Side	0.924	0.039	0.963
	Right Side	0.452	0.113	0.565
	Top Side	0.701	0.148	0.849
	Bottom Side	0.826	0.028	0.854
Body&Hotspot	Back Side	0.995	0.123	1.118




Exposure Position		LTE Band 1	NR N78	WLAN Band	Simultaneous Tx SAR(W/Kg)
		SAR(W/Kg)	SAR(W/Kg)	SAR(W/Kg)	
Head	Left Cheek	0.060	0.214	0.573	0.847
	Left Tilt 15 Degree	0.032	0.114	0.283	0.429
	Right	0.050	0.190	0.510	0.750




	Cheek				
	Right Tilt 15 Degree	0.024	0.099	0.249	0.372
Member	Front Side	0.543	0.798	0.158	1.499
	Back Side	0.885	1.344	0.249	2.478
	Left Side	0.323	0.633	0.039	0.995
	Right Side	0.245	0.253	0.113	0.611
	Top Side	0.087	0.478	0.148	0.713
	Bottom Side	0.469	0.139	0.028	0.636
	Body&Hotspot	0.489	0.798	0.123	1.410

NOTE: The Simultaneous Tx is calculated based on the same configuration and test position.

10. Appendix A. Photo documentation

Test Positions

Left Cheek		Left Tilt 15 Degree	
Right Cheek		Right Tilt 15 Degree	
Front Side (Separation distance of 0mm)		Back Side (Separation distance of 0mm)	

Left Side (Separation distance of 0mm)	Right Side (Separation distance of 0mm)
	
Top Side (Separation distance of 0mm)	Bottom Side (Separation distance of 0mm)
	
Back Side (Separation distance of 5mm)	N/A
	N/A

11. Appendix B. System Check Plots

Table of contents

MEASUREMENT 1 System Performance Check - 750MHz

MEASUREMENT 2 System Performance Check - 900MHz

MEASUREMENT 3 System Performance Check - 1800MHz

MEASUREMENT 4 System Performance Check - 2000MHz

MEASUREMENT 5 System Performance Check - 2300MHz

MEASUREMENT 6 System Performance Check - 2450MHz

MEASUREMENT 7 System Performance Check - 2600MHz

MEASUREMENT 8 System Performance Check - 3700MHz

MEASUREMENT 9 System Performance Check - 5200MHz

MEASUREMENT 10 System Performance Check - 5800MHz

MEASUREMENT 1


Date of measurement: 25/2/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>$dx=15\text{mm}$ $dy=15\text{mm}$, $h= 5.00 \text{ mm}$</u>
<u>ZoomScan</u>	<u>$5\times 5\times 7, dx=8\text{mm}$ $dy=8\text{mm}$ $dz=5\text{mm}$</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW750</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	750.000000
Relative permittivity (real part)	41.301298
Relative permittivity (imaginary part)	21.793206
Conductivity (S/m)	0.908050
Variation (%)	0.140000



Maximum location: X=3.00, Y=3.00
SAR Peak: 1.30 W/kg

SAR 10g (W/Kg)	0.595120
SAR 1g (W/Kg)	0.866299

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	1.2988	0.9667	0.6796	0.4882	0.3417	0.2508	0.1811



MEASUREMENT 2


Date of measurement: 7/3/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>$dx=15\text{mm}$ $dy=15\text{mm}$, $h= 5.00 \text{ mm}$</u>
<u>ZoomScan</u>	<u>$5\times 5\times 7, dx=8\text{mm}$ $dy=8\text{mm}$ $dz=5\text{mm}$</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	900.000000
Relative permittivity (real part)	41.489386
Relative permittivity (imaginary part)	19.878546
Conductivity (S/m)	0.993927
Variation (%)	1.490000



Maximum location: X=3.00, Y=3.00

SAR Peak: 1.90 W/kg

SAR 10g (W/Kg)	0.707027
SAR 1g (W/Kg)	1.005322



MEASUREMENT 3


Date of measurement: 26/2/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>$dx=15\text{mm}$ $dy=15\text{mm}$, $h= 5.00 \text{ mm}$</u>
<u>ZoomScan</u>	<u>$5\times 5\times 7, dx=8\text{mm}$ $dy=8\text{mm}$ $dz=5\text{mm}$</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW1800</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	1800.000000
Relative permittivity (real part)	39.083004
Relative permittivity (imaginary part)	13.953003
Conductivity (S/m)	1.395300
Variation (%)	-3.340000



Maximum location: X=3.00, Y=2.00

SAR Peak: 6.82 W/kg

SAR 10g (W/Kg)	1.995238
SAR 1g (W/Kg)	3.578229



MEASUREMENT 4


Date of measurement: 28/2/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>$dx=15\text{mm}$ $dy=15\text{mm}$, $h= 5.00 \text{ mm}$</u>
<u>ZoomScan</u>	<u>$5\times 5\times 7, dx=8\text{mm}$ $dy=8\text{mm}$ $dz=5\text{mm}$</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW2000</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	2000.000000
Relative permittivity (real part)	41.337114
Relative permittivity (imaginary part)	12.412843
Conductivity (S/m)	1.379205
Variation (%)	-1.310000



Maximum location: X=1.00, Y=2.00

SAR Peak: 7.65 W/kg

SAR 10g (W/Kg)	2.146374
SAR 1g (W/Kg)	4.275039



MEASUREMENT 5


Date of measurement: 1/3/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW2300</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	2300.000000
Relative permittivity (real part)	39.378609
Relative permittivity (imaginary part)	13.429270
Conductivity (S/m)	1.715962
Variation (%)	1.130000



Maximum location: X=1.00, Y=1.00

SAR Peak: 7.04 W/kg

SAR 10g (W/Kg)	2.514213
SAR 1g (W/Kg)	4.822195



MEASUREMENT 6


Date of measurement: 2/3/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>$dx=12\text{mm}$ $dy=12\text{mm}$, $h= 5.00 \text{ mm}$</u>
<u>ZoomScan</u>	<u>$7\times7\times7$, $dx=5\text{mm}$ $dy=5\text{mm}$ $dz=5\text{mm}$</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW2450</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	2450.000000
Relative permittivity (real part)	38.935840
Relative permittivity (imaginary part)	13.282516
Conductivity (S/m)	1.807898
Variation (%)	0.740000



Maximum location: X=0.00, Y=1.00

SAR Peak: 8.14 W/kg

SAR 10g (W/Kg)	2.409076
SAR 1g (W/Kg)	5.615212



MEASUREMENT 7


Date of measurement: 3/3/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>$dx=12\text{mm}$ $dy=12\text{mm}$, $h= 5.00 \text{ mm}$</u>
<u>ZoomScan</u>	<u>$7\times 7\times 7$, $dx=5\text{mm}$ $dy=5\text{mm}$ $dz=5\text{mm}$</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW2600</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	2600.000000
Relative permittivity (real part)	38.747205
Relative permittivity (imaginary part)	14.041450
Conductivity (S/m)	2.028209
Variation (%)	3.220000



Maximum location: X=-1.00, Y=2.00

SAR Peak: 9.07 W/kg

SAR 10g (W/Kg)	2.387275
SAR 1g (W/Kg)	5.955238



MEASUREMENT 8


Date of measurement: 10/3/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>$dx=12mm$ $dy=12mm$, $h= 5.00 mm$</u>
<u>ZoomScan</u>	<u>$7x7x7, dx=5mm$ $dy=5mm$ $dz=5mm$</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW3700</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	3700.000000
Relative permittivity (real part)	37.872232
Relative permittivity (imaginary part)	14.773160
Conductivity (S/m)	3.036705
Variation (%)	0.900000



Maximum location: X=0.00, Y=1.00

SAR Peak: 8.42 W/kg

SAR 10g (W/Kg)	2.538205
SAR 1g (W/Kg)	6.689046



MEASUREMENT 9


Date of measurement: 8/3/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=10mm dy=10mm, h= 2.00 mm</u>
<u>ZoomScan</u>	<u>7x7x12,dx=4mm dy=4mm dz=2mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW5200</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	5200.000000
Relative permittivity (real part)	36.742442
Relative permittivity (imaginary part)	16.499774
Conductivity (S/m)	4.766601
Variation (%)	1.500000



Maximum location: X=0.00, Y=6.00
SAR Peak: 40.06 W/kg

SAR 10g (W/Kg)	5.990038
SAR 1g (W/Kg)	17.112276

Z (m m)	0.00	2.00	4.00	6.00	8.00	10.0 0	12.0 0	14.0 0	16.0 0	18.0 0	20.0 0	22.0 0
SA R (W/ Kg)	37.8 10	22.3 47	11.3 86	5.66 32	2.82 28	1.40 84	0.71 46	0.36 57	0.18 23	0.10 45	0.05 34	0.03 21



MEASUREMENT 10


Date of measurement: 9/3/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=10mm dy=10mm, h= 2.00 mm</u>
<u>ZoomScan</u>	<u>7x7x12,dx=4mm dy=4mm dz=2mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Dipole</u>
<u>Band</u>	<u>CW5800</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>CW (Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	5800.000000
Relative permittivity (real part)	35.653642
Relative permittivity (imaginary part)	16.884034
Conductivity (S/m)	5.440411
Variation (%)	2.930000



Maximum location: X=0.00, Y=6.00
SAR Peak: 57.37 W/kg

SAR 10g (W/Kg)	6.236025
SAR 1g (W/Kg)	17.007074

Z (m m)	0.00	2.00	4.00	6.00	8.00	10.0	12.0	14.0	16.0	18.0	20.0	22.0
SA R (W/ Kg)	54.0 66	31.9 24	16.1 96	8.17 18	4.08 07	2.05 31	1.03 77	0.51 93	0.27 54	0.15 23	0.07 72	0.04 06



12. Appendix C. Plots of High SAR Measurement

Table of contents

MEASUREMENT 1 GSM 900 Head

MEASUREMENT 2 GSM 900 Extremity

MEASUREMENT 3 GSM 1800 Head

MEASUREMENT 4 GSM 1800 Extremity

MEASUREMENT 5 WCDMA Band 1 Head

MEASUREMENT 6 WCDMA Band 1 Extremity

MEASUREMENT 7 WCDMA Band 8 Head

MEASUREMENT 8 WCDMA Band 8 Extremity

MEASUREMENT 9 WLAN 5.2G Head

MEASUREMENT 10 WLAN 5.8G Head

MEASUREMENT 11 WLAN 5.2G Extremity

MEASUREMENT 12 WLAN 5.8G Extremity

MEASUREMENT 13 WLAN 2.4G Head

MEASUREMENT 14 WLAN 2.4G Extremity

MEASUREMENT 15 LTE Band 1 Head

MEASUREMENT 16 LTE Band 1 Extremity

MEASUREMENT 17 LTE Band 3 Head

MEASUREMENT 18 LTE Band 3 Extremity

MEASUREMENT 19 LTE Band 7 Head

MEASUREMENT 20 LTE Band 7 Extremity

MEASUREMENT 21 LTE Band 8 Head

MEASUREMENT 22 LTE Band 8 Extremity

MEASUREMENT 23 LTE Band 20 Head

MEASUREMENT 24 LTE Band 20 Extremity

MEASUREMENT 25 LTE Band 28 Head

MEASUREMENT 26 LTE Band 28 Extremity

MEASUREMENT 27 LTE Band 40 Head

MEASUREMENT 28 LTE Band 40 Extremity

MEASUREMENT 29 NR N1 Head

MEASUREMENT 30 NR N1 Extremity

MEASUREMENT 31 NR N3 Head

MEASUREMENT 32 NR N3 Extremity

MEASUREMENT 33 NR N8 Head

MEASUREMENT 34 NR N8 Extremity

MEASUREMENT 35 NR N20 Head

MEASUREMENT 36 NR N20 Extremity

MEASUREMENT 37 NR N28 Head

MEASUREMENT 38 NR N28 Extremity**MEASUREMENT 39 NR N38 Head****MEASUREMENT 40 NR N38 Extremity****MEASUREMENT 41 NR N77 Head****MEASUREMENT 42 NR N77 Extremity****MEASUREMENT 43 NR N78 Head****MEASUREMENT 44 NR N78 Extremity**

MEASUREMENT 1


Date of measurement: 7/3/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>GSM900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>TDMA (Crest factor: 2.7)</u>



B. SAR Measurement Results

Frequency (MHz)	897.600000
Relative permittivity (real part)	41.569744
Relative permittivity (imaginary part)	19.932365
Conductivity (S/m)	0.993961
Variation (%)	3.030000



Maximum location: X=-52.00, Y=-25.00
SAR Peak: 0.37 W/kg

SAR 10g (W/Kg)	0.273566
SAR 1g (W/Kg)	0.322995



MEASUREMENT 2


Date of measurement: 7/3/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>GSM900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>TDMA (Crest factor: 2.7)</u>

B. SAR Measurement Results



Frequency (MHz)	897.600000
Relative permittivity (real part)	41.569744
Relative permittivity (imaginary part)	19.932365
Conductivity (S/m)	0.993961
Variation (%)	1.780000



Maximum location: X=6.00, Y=-7.00

SAR Peak: 2.34 W/kg

SAR 10g (W/Kg)	0.753126
SAR 1g (W/Kg)	1.396001



MEASUREMENT 3


Date of measurement: 26/2/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>$dx=15\text{mm}$ $dy=15\text{mm}$, $h= 5.00 \text{ mm}$</u>
<u>ZoomScan</u>	<u>$5\times 5\times 7, dx=8\text{mm}$ $dy=8\text{mm}$ $dz=5\text{mm}$</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>GSM1800</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>TDMA (Crest factor: 2.0)</u>

B. SAR Measurement Results



Frequency (MHz)	1747.400000
Relative permittivity (real part)	39.437466
Relative permittivity (imaginary part)	13.920883
Conductivity (S/m)	1.351408
Variation (%)	0.950000



Maximum location: X=-51.00, Y=-56.00

SAR Peak: 0.18 W/kg

SAR 10g (W/Kg)	0.087186
SAR 1g (W/Kg)	0.129843



MEASUREMENT 4


Date of measurement: 26/2/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>$dx=15\text{mm}$ $dy=15\text{mm}$, $h= 5.00 \text{ mm}$</u>
<u>ZoomScan</u>	<u>$5\times 5\times 7, dx=8\text{mm}$ $dy=8\text{mm}$ $dz=5\text{mm}$</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>GSM1800</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>TDMA (Crest factor: 2.0)</u>

B. SAR Measurement Results



Frequency (MHz)	1747.400000
Relative permittivity (real part)	39.437466
Relative permittivity (imaginary part)	13.920883
Conductivity (S/m)	1.351408
Variation (%)	1.900000



Maximum location: X=5.00, Y=-10.00

SAR Peak: 2.96 W/kg

SAR 10g (W/Kg)	0.859241
SAR 1g (W/Kg)	1.693192



MEASUREMENT 5


Date of measurement: 28/2/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>Band1 UMTS</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>WCDMA (Crest factor: 1.0)</u>



B. SAR Measurement Results

Frequency (MHz)	1950.000000
Relative permittivity (real part)	41.236614
Relative permittivity (imaginary part)	12.492943
Conductivity (S/m)	1.353402
Variation (%)	-4.100000



Maximum location: X=-49.00, Y=-53.00
SAR Peak: 0.13 W/kg

SAR 10g (W/Kg)	0.055813
SAR 1g (W/Kg)	0.087284



MEASUREMENT 6


Date of measurement: 28/2/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>Band1 UMTS</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>WCDMA (Crest factor: 1.0)</u>

B. SAR Measurement Results

Frequency (MHz)	1950.000000
Relative permittivity (real part)	41.236614
Relative permittivity (imaginary part)	12.492943
Conductivity (S/m)	1.353402
Variation (%)	-0.950000





Maximum location: X=19.00, Y=-11.00

SAR Peak: 3.49 W/kg

SAR 10g (W/Kg)	0.914450
SAR 1g (W/Kg)	1.961594

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	3.4349	2.1144	1.1092	0.5938	0.3224	0.1828	0.1051



MEASUREMENT 7


Date of measurement: 7/3/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>Band8 WCDMA900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>WCDMA (Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	897.600000
Relative permittivity (real part)	41.569744
Relative permittivity (imaginary part)	19.932365
Conductivity (S/m)	0.993961
Variation (%)	0.420000



Maximum location: X=-52.00, Y=-24.00

SAR Peak: 0.21 W/kg

SAR 10g (W/Kg)	0.166866
SAR 1g (W/Kg)	0.193438



MEASUREMENT 8


Date of measurement: 7/3/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>Band8 WCDMA900</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>WCDMA (Crest factor: 1.0)</u>

B. SAR Measurement Results

Frequency (MHz)	897.600000
Relative permittivity (real part)	41.569744
Relative permittivity (imaginary part)	19.932365
Conductivity (S/m)	0.993961
Variation (%)	-1.650000





Maximum location: X=3.00, Y=-10.00

SAR Peak: 1.83 W/kg

SAR 10g (W/Kg)	0.644348
SAR 1g (W/Kg)	1.159111

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	1.7240	1.1853	0.7541	0.5063	0.3544	0.2528	0.1860



MEASUREMENT 9


Date of measurement: 8/3/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=10mm dy=10mm, h= 2.00 mm</u>
<u>ZoomScan</u>	<u>7x7x12,dx=4mm dy=4mm dz=2mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>IEEE 802.11a U-NII</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>IEEE802.11a (Crest factor: 1.0)</u>

B. SAR Measurement Results

Frequency (MHz)	5200.000000
Relative permittivity (real part)	36.742443
Relative permittivity (imaginary part)	16.499775
Conductivity (S/m)	4.766601
Variation (%)	-0.300000





Maximum location: X=-8.00, Y=22.00

SAR Peak: 0.63 W/kg

SAR 10g (W/Kg)	0.105107
SAR 1g (W/Kg)	0.233328

Z (m m)	0.00	2.00	4.00	6.00	8.00	10.0	12.0	14.0	16.0	18.0	20.0	22.0
SA R (W/ Kg)	0.39 02	0.24 55	0.13 46	0.08 71	0.05 28	0.04 18	0.03 14	0.03 16	0.02 69	0.03 62	0.03 47	0.03 58



MEASUREMENT 10


Date of measurement: 9/3/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>$dx=10mm\ dy=10mm,\ h= 2.00\ mm$</u>
<u>ZoomScan</u>	<u>$7x7x12, dx=4mm\ dy=4mm\ dz=2mm$</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>IEEE 802.11a U-NII</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>IEEE802.11a (Crest factor: 1.0)</u>

B. SAR Measurement Results

Frequency (MHz)	5785.000000
Relative permittivity (real part)	35.729591
Relative permittivity (imaginary part)	16.759590
Conductivity (S/m)	5.386346
Variation (%)	-2.280000





Maximum location: X=-5.00, Y=23.00

SAR Peak: 4.52 W/kg

SAR 10g (W/Kg)	0.483416
SAR 1g (W/Kg)	1.524686

Z (m m)	0.00	2.00	4.00	6.00	8.00	10.0 0	12.0 0	14.0 0	16.0 0	18.0 0	20.0 0	22.0 0
SA R (W/ Kg)	2.75 94	1.55 25	0.69 47	0.30 76	0.16 21	0.09 66	0.06 09	0.04 69	0.04 58	0.03 93	0.03 84	0.03 82



MEASUREMENT 11


Date of measurement: 8/3/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>$dx=10\text{mm}$ $dy=10\text{mm}$, $h= 2.00 \text{ mm}$</u>
<u>ZoomScan</u>	<u>$7\times 7\times 12, dx=4\text{mm}$ $dy=4\text{mm}$ $dz=2\text{mm}$</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>IEEE 802.11a U-NII</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>IEEE802.11a (Crest factor: 1.0)</u>

B. SAR Measurement Results

Frequency (MHz)	5200.000000
Relative permittivity (real part)	36.742443
Relative permittivity (imaginary part)	16.499775
Conductivity (S/m)	4.766601
Variation (%)	-4.510000





Maximum location: X=-10.00, Y=9.00

SAR Peak: 0.90 W/kg

SAR 10g (W/Kg)	0.108015
SAR 1g (W/Kg)	0.283840

Z (m m)	0.00	2.00	4.00	6.00	8.00	10.0 0	12.0 0	14.0 0	16.0 0	18.0 0	20.0 0	22.0 0
SA R (W/ Kg)	0.86 09	0.50 60	0.19 69	0.14 01	0.07 27	0.05 52	0.03 84	0.02 81	0.03 61	0.03 45	0.03 43	0.03 35



MEASUREMENT 12


Date of measurement: 9/3/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>$dx=10\text{mm}$ $dy=10\text{mm}$, $h= 2.00 \text{ mm}$</u>
<u>ZoomScan</u>	<u>$7x7x12, dx=4\text{mm}$ $dy=4\text{mm}$ $dz=2\text{mm}$</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>IEEE 802.11a U-NII</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>IEEE802.11a (Crest factor: 1.0)</u>

B. SAR Measurement Results

Frequency (MHz)	5785.000000
Relative permittivity (real part)	35.729591
Relative permittivity (imaginary part)	16.759590
Conductivity (S/m)	5.386346
Variation (%)	0.510000





Maximum location: X=-11.00, Y=17.00

SAR Peak: 2.12 W/kg

SAR 10g (W/Kg)	0.209765
SAR 1g (W/Kg)	0.597878

Z (m m)	0.00	2.00	4.00	6.00	8.00	10.0	12.0	14.0	16.0	18.0	20.0	22.0
SA R (W/ Kg)	2.03	1.12	0.33	0.23	0.08	0.07	0.04	0.03	0.02	0.03	0.03	0.03



MEASUREMENT 13


Date of measurement: 2/3/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>IEEE 802.11b ISM</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>IEEE802.11b (Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	2442.000000
Relative permittivity (real part)	39.011139
Relative permittivity (imaginary part)	13.276016
Conductivity (S/m)	1.801113
Variation (%)	0.410000



Maximum location: X=-14.00, Y=22.00

SAR Peak: 0.35 W/kg

SAR 10g (W/Kg)	0.099098
SAR 1g (W/Kg)	0.191433



MEASUREMENT 14


Date of measurement: 2/3/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>$dx=12mm$ $dy=12mm$, $h= 5.00 mm$</u>
<u>ZoomScan</u>	<u>$7x7x7, dx=5mm$ $dy=5mm$ $dz=5mm$</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>IEEE 802.11b ISM</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>IEEE802.11b (Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	2442.000000
Relative permittivity (real part)	39.011139
Relative permittivity (imaginary part)	13.276016
Conductivity (S/m)	1.801113
Variation (%)	-1.950000



Maximum location: X=-16.00, Y=11.00

SAR Peak: 0.48 W/kg

SAR 10g (W/Kg)	0.130007
SAR 1g (W/Kg)	0.265251



MEASUREMENT 15


Date of measurement: 28/2/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>LTE band 1</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>



B. SAR Measurement Results

Frequency (MHz)	1950.000000
Relative permittivity (real part)	41.236614
Relative permittivity (imaginary part)	12.492943
Conductivity (S/m)	1.353402
Variation (%)	3.220000



Maximum location: X=-49.00, Y=-53.00
SAR Peak: 0.13 W/kg

SAR 10g (W/Kg)	0.053265
SAR 1g (W/Kg)	0.082039



MEASUREMENT 16


Date of measurement: 28/2/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>$dx=15\text{mm}$ $dy=15\text{mm}$, $h= 5.00 \text{ mm}$</u>
<u>ZoomScan</u>	<u>$5\times 5\times 7, dx=8\text{mm}$ $dy=8\text{mm}$ $dz=5\text{mm}$</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 1</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>

B. SAR Measurement Results

Frequency (MHz)	1950.000000
Relative permittivity (real part)	41.236614
Relative permittivity (imaginary part)	12.492943
Conductivity (S/m)	1.353402
Variation (%)	-1.060000





Maximum location: X=-9.00, Y=-12.00

SAR Peak: 3.01 W/kg

SAR 10g (W/Kg)	0.783072
SAR 1g (W/Kg)	1.678328

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	2.9615	1.7892	0.9194	0.4900	0.2739	0.1566	0.0926



MEASUREMENT 17


Date of measurement: 26/2/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>LTE band 3</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	1747.500000
Relative permittivity (real part)	39.436905
Relative permittivity (imaginary part)	13.919403
Conductivity (S/m)	1.350955
Variation (%)	-3.310000



Maximum location: X=-51.00, Y=-55.00

SAR Peak: 0.17 W/kg

SAR 10g (W/Kg)	0.084562
SAR 1g (W/Kg)	0.124171



MEASUREMENT 18


Date of measurement: 26/2/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>$dx=15\text{mm}$ $dy=15\text{mm}$, $h= 5.00 \text{ mm}$</u>
<u>ZoomScan</u>	<u>$5\times 5\times 7, dx=8\text{mm}$ $dy=8\text{mm}$ $dz=5\text{mm}$</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 3</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>

B. SAR Measurement Results

Frequency (MHz)	1747.500000
Relative permittivity (real part)	39.436905
Relative permittivity (imaginary part)	13.919403
Conductivity (S/m)	1.350955
Variation (%)	-0.520000





Maximum location: X=-6.00, Y=-10.00

SAR Peak: 2.46 W/kg

SAR 10g (W/Kg)	0.752738
SAR 1g (W/Kg)	1.446297

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	2.4112	1.4970	0.8007	0.4495	0.2575	0.1572	0.1005



MEASUREMENT 19


Date of measurement: 3/3/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>LTE band 7</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>



B. SAR Measurement Results

Frequency (MHz)	2535.000000
Relative permittivity (real part)	39.082504
Relative permittivity (imaginary part)	13.909350
Conductivity (S/m)	1.958900
Variation (%)	-1.630000



Maximum location: X=-46.00, Y=-54.00
SAR Peak: 0.15 W/kg

SAR 10g (W/Kg)	0.055994
SAR 1g (W/Kg)	0.093356



MEASUREMENT 20


Date of measurement: 3/3/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 7</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>



B. SAR Measurement Results

Frequency (MHz)	2535.000000
Relative permittivity (real part)	39.082504
Relative permittivity (imaginary part)	13.909350
Conductivity (S/m)	1.958900
Variation (%)	-1.020000



Maximum location: X=-3.00, Y=-5.00
SAR Peak: 5.25 W/kg

SAR 10g (W/Kg)	1.356255
SAR 1g (W/Kg)	2.914749



MEASUREMENT 21


Date of measurement: 7/3/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>LTE band 8</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>



B. SAR Measurement Results

Frequency (MHz)	897.500000
Relative permittivity (real part)	41.584385
Relative permittivity (imaginary part)	19.892946
Conductivity (S/m)	0.991332
Variation (%)	-1.090000



Maximum location: X=-52.00, Y=-25.00
SAR Peak: 0.24 W/kg

SAR 10g (W/Kg)	0.189277
SAR 1g (W/Kg)	0.218854



MEASUREMENT 22


Date of measurement: 7/3/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 8</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	897.500000
Relative permittivity (real part)	41.584385
Relative permittivity (imaginary part)	19.892946
Conductivity (S/m)	0.991332
Variation (%)	-0.430000



Maximum location: X=5.00, Y=3.00

SAR Peak: 2.00 W/kg

SAR 10g (W/Kg)	0.715653
SAR 1g (W/Kg)	1.274033



MEASUREMENT 23


Date of measurement: 7/3/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>LTE band 20</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	847.000000
Relative permittivity (real part)	42.203186
Relative permittivity (imaginary part)	19.678045
Conductivity (S/m)	0.925961
Variation (%)	-1.240000



Maximum location: X=-52.00, Y=-32.00
SAR Peak: 0.22 W/kg

SAR 10g (W/Kg)	0.171038
SAR 1g (W/Kg)	0.193915

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	0.2140	0.1969	0.1804	0.1691	0.1595	0.1515	0.1411



MEASUREMENT 24


Date of measurement: 7/3/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>$dx=15\text{mm}$ $dy=15\text{mm}$, $h= 5.00 \text{ mm}$</u>
<u>ZoomScan</u>	<u>$5\times 5\times 7, dx=8\text{mm}$ $dy=8\text{mm}$ $dz=5\text{mm}$</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 20</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>

B. SAR Measurement Results

Frequency (MHz)	847.000000
Relative permittivity (real part)	42.203186
Relative permittivity (imaginary part)	19.678045
Conductivity (S/m)	0.925961
Variation (%)	-0.530000





Maximum location: X=5.00, Y=-11.00

SAR Peak: 1.73 W/kg

SAR 10g (W/Kg)	0.599760
SAR 1g (W/Kg)	1.079708

Z (mm)	0.00	4.00	9.00	14.00	19.00	24.00	29.00
SAR (W/Kg)	1.6402	1.1109	0.6985	0.4684	0.3338	0.2464	0.1814



MEASUREMENT 25


Date of measurement: 25/2/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>LTE band 28</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	728.000000
Relative permittivity (real part)	41.602898
Relative permittivity (imaginary part)	21.882107
Conductivity (S/m)	0.885010
Variation (%)	-3.090000



Maximum location: X=-50.00, Y=-36.00

SAR Peak: 0.42 W/kg

SAR 10g (W/Kg)	0.205797
SAR 1g (W/Kg)	0.230470



MEASUREMENT 26


Date of measurement: 25/2/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>$dx=15\text{mm}$ $dy=15\text{mm}$, $h= 5.00 \text{ mm}$</u>
<u>ZoomScan</u>	<u>$5\times 5\times 7$, $dx=8\text{mm}$ $dy=8\text{mm}$ $dz=5\text{mm}$</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 28</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	728.000000
Relative permittivity (real part)	41.602898
Relative permittivity (imaginary part)	21.882107
Conductivity (S/m)	0.885010
Variation (%)	-1.100000



Maximum location: X=8.00, Y=-10.00

SAR Peak: 1.94 W/kg

SAR 10g (W/Kg)	0.638475
SAR 1g (W/Kg)	1.158260



MEASUREMENT 27


Date of measurement: 1/3/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>LTE band 40</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.6)</u>



B. SAR Measurement Results

Frequency (MHz)	2350.000000
Relative permittivity (real part)	39.553371
Relative permittivity (imaginary part)	13.251040
Conductivity (S/m)	1.729997
Variation (%)	-2.490000



Maximum location: X=-80.00, Y=-48.00
SAR Peak: 0.09 W/kg

SAR 10g (W/Kg)	0.035414
SAR 1g (W/Kg)	0.056782



MEASUREMENT 28


Date of measurement: 1/3/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>LTE band 40</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>LTE (Crest factor: 1.6)</u>

B. SAR Measurement Results



Frequency (MHz)	2350.000000
Relative permittivity (real part)	39.553371
Relative permittivity (imaginary part)	13.251040
Conductivity (S/m)	1.729997
Variation (%)	0.670000



Maximum location: X=9.00, Y=-13.00

SAR Peak: 4.55 W/kg

SAR 10g (W/Kg)	1.097781
SAR 1g (W/Kg)	2.472871



MEASUREMENT 29


Date of measurement: 28/2/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>NR N1</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>(Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	1950.000000
Relative permittivity (real part)	41.236614
Relative permittivity (imaginary part)	12.492943
Conductivity (S/m)	1.353402
Variation (%)	-3.620000



Maximum location: X=-50.00, Y=-53.00

SAR Peak: 0.09 W/kg

SAR 10g (W/Kg)	0.042141
SAR 1g (W/Kg)	0.061007



MEASUREMENT 30


Date of measurement: 28/2/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>NR N1</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>(Crest factor: 1.0)</u>



B. SAR Measurement Results

Frequency (MHz)	1950.000000
Relative permittivity (real part)	41.236614
Relative permittivity (imaginary part)	12.492943
Conductivity (S/m)	1.353402
Variation (%)	-0.980000



Maximum location: X=19.00, Y=1.00
SAR Peak: 2.20 W/kg

SAR 10g (W/Kg)	0.564743
SAR 1g (W/Kg)	1.222837



MEASUREMENT 31


Date of measurement: 26/2/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>NR N3</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>(Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	1747.500000
Relative permittivity (real part)	39.437603
Relative permittivity (imaginary part)	13.921253
Conductivity (S/m)	1.351522
Variation (%)	-2.580000



Maximum location: X=-52.00, Y=-57.00

SAR Peak: 0.16 W/kg

SAR 10g (W/Kg)	0.074328
SAR 1g (W/Kg)	0.111369



MEASUREMENT 32


Date of measurement: 26/2/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>NR N3</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>(Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	1747.500000
Relative permittivity (real part)	39.437603
Relative permittivity (imaginary part)	13.921253
Conductivity (S/m)	1.351522
Variation (%)	-1.470000



Maximum location: X=19.00, Y=3.00

SAR Peak: 2.17 W/kg

SAR 10g (W/Kg)	0.641132
SAR 1g (W/Kg)	1.252448



MEASUREMENT 33


Date of measurement: 7/3/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>NR N8</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>(Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	897.500000
Relative permittivity (real part)	41.572186
Relative permittivity (imaginary part)	19.925797
Conductivity (S/m)	0.993522
Variation (%)	-4.870000



Maximum location: X=-51.00, Y=-25.00

SAR Peak: 0.19 W/kg

SAR 10g (W/Kg)	0.138770
SAR 1g (W/Kg)	0.161071



MEASUREMENT 34


Date of measurement: 7/3/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>$dx=15\text{mm}$ $dy=15\text{mm}$, $h= 5.00 \text{ mm}$</u>
<u>ZoomScan</u>	<u>$5\times 5\times 7, dx=8\text{mm}$ $dy=8\text{mm}$ $dz=5\text{mm}$</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>NR N8</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>(Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	897.500000
Relative permittivity (real part)	41.572186
Relative permittivity (imaginary part)	19.925797
Conductivity (S/m)	0.993522
Variation (%)	-0.820000



Maximum location: X=5.00, Y=5.00

SAR Peak: 1.47 W/kg

SAR 10g (W/Kg)	0.507708
SAR 1g (W/Kg)	0.921944



MEASUREMENT 35


Date of measurement: 7/3/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>NR N20</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>(Crest factor: 1.0)</u>



B. SAR Measurement Results

Frequency (MHz)	847.000000
Relative permittivity (real part)	42.203186
Relative permittivity (imaginary part)	19.678045
Conductivity (S/m)	0.925961
Variation (%)	-0.560000



Maximum location: X=-52.00, Y=-32.00
SAR Peak: 0.16 W/kg

SAR 10g (W/Kg)	0.121076
SAR 1g (W/Kg)	0.138936



MEASUREMENT 36


Date of measurement: 7/3/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>NR N20</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>(Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	847.000000
Relative permittivity (real part)	42.203186
Relative permittivity (imaginary part)	19.678045
Conductivity (S/m)	0.925961
Variation (%)	-0.040000



Maximum location: X=6.00, Y=-11.00

SAR Peak: 1.14 W/kg

SAR 10g (W/Kg)	0.423778
SAR 1g (W/Kg)	0.727164



MEASUREMENT 37


Date of measurement: 25/2/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>NR N28</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>(Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	725.500000
Relative permittivity (real part)	41.622898
Relative permittivity (imaginary part)	22.063505
Conductivity (S/m)	0.889282
Variation (%)	-2.950000



Maximum location: X=-51.00, Y=-36.00

SAR Peak: 0.28 W/kg

SAR 10g (W/Kg)	0.133658
SAR 1g (W/Kg)	0.174831



MEASUREMENT 38


Date of measurement: 25/2/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=15mm dy=15mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>5x5x7,dx=8mm dy=8mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>NR N28</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>(Crest factor: 1.0)</u>

B. SAR Measurement Results



Frequency (MHz)	725.500000
Relative permittivity (real part)	41.622898
Relative permittivity (imaginary part)	22.063505
Conductivity (S/m)	0.889282
Variation (%)	-0.720000



Maximum location: X=15.00, Y=-25.00

SAR Peak: 1.29 W/kg

SAR 10g (W/Kg)	0.463123
SAR 1g (W/Kg)	0.802201



MEASUREMENT 39


Date of measurement: 3/3/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>NR N38</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>(Crest factor: 1.6)</u>



B. SAR Measurement Results

Frequency (MHz)	2595.000000
Relative permittivity (real part)	38.714603
Relative permittivity (imaginary part)	14.123150
Conductivity (S/m)	2.036087
Variation (%)	1.340000



Maximum location: X=-46.00, Y=-52.00
SAR Peak: 0.19 W/kg

SAR 10g (W/Kg)	0.068041
SAR 1g (W/Kg)	0.118739



MEASUREMENT 40


Date of measurement: 3/3/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>NR N38</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>(Crest factor: 1.6)</u>

B. SAR Measurement Results



Frequency (MHz)	2595.000000
Relative permittivity (real part)	38.714603
Relative permittivity (imaginary part)	14.123150
Conductivity (S/m)	2.036087
Variation (%)	0.510000



Maximum location: X=-7.00, Y=-11.00

SAR Peak: 4.21 W/kg

SAR 10g (W/Kg)	0.940378
SAR 1g (W/Kg)	2.213509



MEASUREMENT 41


Date of measurement: 10/3/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>NR N77</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>(Crest factor: 1.6)</u>

B. SAR Measurement Results



Frequency (MHz)	3750.000000
Relative permittivity (real part)	37.545631
Relative permittivity (imaginary part)	14.837460
Conductivity (S/m)	3.091137
Variation (%)	1.770000



Maximum location: X=1.00, Y=-1.00

SAR Peak: 1.72 W/kg

SAR 10g (W/Kg)	0.258408
SAR 1g (W/Kg)	0.750225



MEASUREMENT 42


Date of measurement: 10/3/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>NR N77</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>(Crest factor: 1.6)</u>



B. SAR Measurement Results

Frequency (MHz)	3750.000000
Relative permittivity (real part)	37.545631
Relative permittivity (imaginary part)	14.837460
Conductivity (S/m)	3.091137
Variation (%)	-0.110000



Maximum location: X=-3.00, Y=9.00
SAR Peak: 7.68 W/kg

SAR 10g (W/Kg)	1.124116
SAR 1g (W/Kg)	3.343640



MEASUREMENT 43


Date of measurement: 10/3/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Left head</u>
<u>Device Position</u>	<u>Cheek</u>
<u>Band</u>	<u>NR N78</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>(Crest factor: 1.6)</u>

B. SAR Measurement Results



Frequency (MHz)	3750.000000
Relative permittivity (real part)	37.545632
Relative permittivity (imaginary part)	14.837460
Conductivity (S/m)	3.091138
Variation (%)	2.390000



Maximum location: X=2.00, Y=-2.00

SAR Peak: 0.72 W/kg

SAR 10g (W/Kg)	0.131878
SAR 1g (W/Kg)	0.334604



MEASUREMENT 44


Date of measurement: 10/3/2022

A. Experimental conditions.

<u>Area Scan</u>	<u>dx=12mm dy=12mm, h= 5.00 mm</u>
<u>ZoomScan</u>	<u>7x7x7,dx=5mm dy=5mm dz=5mm</u>
<u>Phantom</u>	<u>Validation plane</u>
<u>Device Position</u>	<u>Body</u>
<u>Band</u>	<u>NR N78</u>
<u>Channels</u>	<u>Middle</u>
<u>Signal</u>	<u>(Crest factor: 1.6)</u>

B. SAR Measurement Results



Frequency (MHz)	3750.000000
Relative permittivity (real part)	37.545632
Relative permittivity (imaginary part)	14.837460
Conductivity (S/m)	3.091138
Variation (%)	-1.110000



Maximum location: X=-2.00, Y=-13.00

SAR Peak: 5.23 W/kg

SAR 10g (W/Kg)	0.828675
SAR 1g (W/Kg)	2.312678



13. Appendix D. Calibration Certificate

Table of contents

E Field Probe - SN 08/16 EPGO287
750 MHz Dipole - SN 03/15 DIP 0G750-355
900 MHz Dipole - SN 03/15 DIP 0G900-348
1800 MHz Dipole - SN 03/15 DIP 1G800-349
2000 MHz Dipole - SN 03/15 DIP 2G000-351
2300 MHz Dipole - SN 03/16 DIP 2G300-358
2450 MHz Dipole - SN 03/15 DIP 2G450-352
2600 MHz Dipole - SN 03/15 DIP 2G600-356
3700 MHz Dipole - SN 09/12 DIP 3G700-361
5000-6000 MHz Dipole - SN 13/14 WGA 33



COMOSAR E-Field Probe Calibration Report

Ref : ACR.60.1.21.MVGB.A

SHENZHEN NTEK TESTING TECHNOLOGY CO., LTD.

BUILDING E, FENDA SCIENCE PARK, SANWEI
COMMUNITY, XIXIANG STREET,
BAO'AN DISTRICT, SHENZHEN GUANGDONG, CHINA
MVG COMOSAR DOSIMETRIC E-FIELD PROBE
SERIAL NO.: SN 08/16 EPGO287

Calibrated at MVG

Z.I. de la pointe du diable

Technopôle Brest Iroise – 295 avenue Alexis de Rochon
29280 PLOUZANE - FRANCE

Calibration date: 02/01/2022



Accreditations #2-6789 and #2-6814
Scope available on www.cofrac.fr


Summary:

This document presents the method and results from an accredited COMOSAR E-Field Probe calibration performed at MVG, using the CALIPROBE test bench, for use with a MVG COMOSAR system only. The test results covered by accreditation are traceable to the International System of Units (SI).



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref. ACR.60.1.21.MVGB.A

	Name	Function	Date	Signature
Prepared by :	Jérôme Luc	Technical Manager	2/1/2022	
Checked by :	Jérôme Luc	Technical Manager	2/1/2022	
Approved by :	Yann Toutain	Laboratory Director	2/1/2022	

Mode d'emploi
2022.02.0
110:07:13
+01'00'
PHILIPS

	Customer Name
Distribution :	SHENZHEN NTEK TESTING TECHNOLOGY CO., LTD.

Issue	Name	Date	Modifications
A	Jérôme Luc	2/1/2022	Initial release



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.60.1.21.MVGB.A

TABLE OF CONTENTS

1	Device Under Test	4
2	Product Description	4
2.1	General Information	4
3	Measurement Method	4
3.1	Linearity	4
3.2	Sensitivity	5
3.3	Lower Detection Limit	5
3.4	Isotropy	5
3.1	Boundary Effect	5
4	Measurement Uncertainty	6
5	Calibration Measurement Results	6
5.1	Sensitivity in air	6
5.2	Linearity	7
5.3	Sensitivity in liquid	8
5.4	Isotropy	9
6	List of Equipment	10



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref. ACR.60.1.21.MVGB.A

1 DEVICE UNDER TEST

Device Under Test	
Device Type	COMOSAR DOSIMETRIC E FIELD PROBE
Manufacturer	MVG
Model	SSE2
Serial Number	SN 08/16 EPGO287
Product Condition (new / used)	Used
Frequency Range of Probe	0.15 GHz-6GHz
Resistance of Three Dipoles at Connector	Dipole 1: R1=0.211 MΩ Dipole 2: R2=0.199 MΩ Dipole 3: R3=0.199 MΩ

2 PRODUCT DESCRIPTION**2.1 GENERAL INFORMATION**

MVG's COMOSAR E field Probes are built in accordance to the IEEE 1528, FCC KDB865664 D01, CENELEC EN62209 and CEI/IEC 62209 standards.



Figure 1 – MVG COMOSAR Dosimetric E field Dipole

Probe Length	330 mm
Length of Individual Dipoles	2 mm
Maximum external diameter	8 mm
Probe Tip External Diameter	2.5 mm
Distance between dipoles / probe extremity	1 mm

3 MEASUREMENT METHOD

The IEEE 1528, FCC KDB865664 D01, CENELEC EN62209 and CEI/IEC 62209 standards provide recommended practices for the probe calibrations, including the performance characteristics of interest and methods by which to assess their affect. All calibrations / measurements performed meet the fore mentioned standards.

3.1 LINEARITY

The evaluation of the linearity was done in free space using the waveguide, performing a power sweep to cover the SAR range 0.01W/kg to 100W/kg.



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref. ACR.60.1.21.MVGB.A

3.2 SENSITIVITY

The sensitivity factors of the three dipoles were determined using a two step calibration method (air and tissue simulating liquid) using waveguides as outlined in the standards.

3.3 LOWER DETECTION LIMIT

The lower detection limit was assessed using the same measurement set up as used for the linearity measurement. The required lower detection limit is 10 mW/kg.

3.4 ISOTROPY

The axial isotropy was evaluated by exposing the probe to a reference wave from a standard dipole with the dipole mounted under the flat phantom in the test configuration suggested for system validations and checks. The probe was rotated along its main axis from 0 to 360 degrees in 15-degree steps. The hemispherical isotropy is determined by inserting the probe in a thin plastic box filled with tissue-equivalent liquid, with the plastic box illuminated with the fields from a half wave dipole. The dipole is rotated about its axis (0°–180°) in 15° increments. At each step the probe is rotated about its axis (0°–360°).

3.1 BOUNDARY EFFECT

The boundary effect is defined as the deviation between the SAR measured data and the expected exponential decay in the liquid when the probe is oriented normal to the interface. To evaluate this effect, the liquid filled flat phantom is exposed to fields from either a reference dipole or waveguide. With the probe normal to the phantom surface, the peak spatial average SAR is measured and compared to the analytical value at the surface.

The boundary effect uncertainty can be estimated according to the following uncertainty approximation formula based on linear and exponential extrapolations between the surface and d_{be} + d_{step} along lines that are approximately normal to the surface:

$$\text{SAR}_{\text{uncertainty}} [\%] = \frac{\Delta \text{SAR}_{be}}{2d_{step}} \frac{(d_{be} + d_{step})^2}{\delta/2} \left(e^{-\frac{4\pi}{3}\delta/2} \right) \quad \text{for } (d_{be} + d_{step}) < 10 \text{ mm}$$

where

ΔSAR_{be}	is the uncertainty in percent of the probe boundary effect
d_{be}	is the distance between the surface and the closest <i>zoom-scan</i> measurement point, in millimetre
Δ_{step}	is the separation distance between the first and second measurement points that are closest to the phantom surface, in millimetre, assuming the boundary effect at the second location is negligible
δ	is the minimum penetration depth in millimetres of the head tissue-equivalent liquids defined in this standard, i.e., $\delta \approx 14$ mm at 3 GHz;
	in percent of SAR is the deviation between the measured SAR value, at the distance d_{be} from the boundary, and the analytical SAR value.



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref. ACR.60.1.21.MVGB.A

The measured worst case boundary effect SARuncertainty[%] for scanning distances larger than 4mm is 1.0% Limit ,2%).

4 MEASUREMENT UNCERTAINTY

The guidelines outlined in the IEEE 1528, OET 65 Bulletin C, CENELEC EN50361 and CEI/IEC 62209 standards were followed to generate the measurement uncertainty associated with an E-field probe calibration using the waveguide technique. All uncertainties listed below represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2, traceable to the Internationally Accepted Guides to Measurement Uncertainty.

Uncertainty analysis of the probe calibration in waveguide					
ERROR SOURCES	Uncertainty value (%)	Probability Distribution	Divisor	ci	Standard Uncertainty (%)
Expanded uncertainty 95 % confidence level k = 2					14 %

5 CALIBRATION MEASUREMENT RESULTS

Calibration Parameters	
Liquid Temperature	20 +/- 1 °C
Lab Temperature	20 +/- 1 °C
Lab Humidity	30-70 %

5.1 SENSITIVITY IN AIR

Normx dipole 1 ($\mu\text{V}/(\text{V}/\text{m})^2$)	Normy dipole 2 ($\mu\text{V}/(\text{V}/\text{m})^2$)	Normz dipole 3 ($\mu\text{V}/(\text{V}/\text{m})^2$)
0.72	0.66	0.77

DCP dipole 1 (mV)	DCP dipole 2 (mV)	DCP dipole 3 (mV)
107	110	110

Calibration curves $ei=f(V)$ (i=1,2,3) allow to obtain E-field value using the formula:


$$E = \sqrt{E_1^2 + E_2^2 + E_3^2}$$




COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref. ACR.60.1.21.MVGB.A

Calibration curves

5.2 LINEARITY

Linearity

Linearity: +/- 1.90% (+/-0.08dB)



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.60.1.21.MVGB.A

5.3 SENSITIVITY IN LIQUID


Liquid	Frequency (MHz +/- 100MHz)	ConvF
HL750	750	1.49
HL850	835	1.50
HL900	900	1.61
HL1800	1800	1.73
HL1900	1900	1.91
HL2000	2000	1.97
HL2300	2300	1.92
HL2450	2450	1.98
HL2600	2600	1.87
HL3300	3300	1.79
HL3500	3500	1.85
HL3700	3700	1.79
HL3900	3900	2.07
HL4200	4200	2.21
HL4600	4600	2.25
HL4900	4900	2.05
HL5200	5200	1.80
HL5400	5400	2.05
HL5600	5600	2.16
HL5800	5800	2.07

LOWER DETECTION LIMIT: 8mW/kg



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref. ACR.60.1.21.MVGB.A

5.4 ISOTROPYHL1800 MHz



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.60.1.21.MVGB.A

6 LIST OF EQUIPMENT

Equipment Summary Sheet				
Equipment Description	Manufacturer / Model	Identification No.	Current Calibration Date	Next Calibration Date
Flat Phantom	MVG	SN-20/09-SAM71	Validated. No cal required.	Validated. No cal required.
COMOSAR Test Bench	Version 3	NA	Validated. No cal required.	Validated. No cal required.
Network Analyzer	Rohde & Schwarz ZVM	100203	05/2019	05/2022
Network Analyzer – Calibration kit	Rohde & Schwarz ZV-Z235	101223	05/2019	05/2022
Multimeter	Keithley 2000	1160271	02/2020	02/2023
Signal Generator	Rohde & Schwarz SMB	106589	04/2019	04/2022
Amplifier	Aethercomm	SN 046	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.
Power Meter	NI-USB 5680	170100013	05/2019	05/2022
Directional Coupler	Narda 4216-20	01386	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.
Waveguide	Mega Industries	069Y7-158-13-712	Validated. No cal required.	Validated. No cal required.
Waveguide Transition	Mega Industries	069Y7-158-13-701	Validated. No cal required.	Validated. No cal required.
Waveguide Termination	Mega Industries	069Y7-158-13-701	Validated. No cal required.	Validated. No cal required.
Temperature / Humidity Sensor	Testo 184 H1	44220687	05/2020	05/2023



SAR Reference Dipole Calibration Report

Ref : ACR.60.2.21.MVGB.A

SHENZHEN NTEK TESTING TECHNOLOGY CO., LTD.

BUILDING E, FENDA SCIENCE PARK, SANWEI
COMMUNITY, XIXIANG STREET,
BAO'AN DISTRICT, SHENZHEN GUANGDONG, CHINA

MVG COMOSAR REFERENCE DIPOLE

FREQUENCY: 750 MHZ

SERIAL NO.: SN 03/15 DIP0G750-355

Calibrated at MVG

Z.I. de la pointe du diable

Technopôle Brest Iroise – 295 avenue Alexis de Rochon
29280 PLOUZANE - FRANCE

Calibration date: 03/01/2021



Accreditations #2-6789 and #2-6814
Scope available on www.cofrac.fr

Summary:

This document presents the method and results from an accredited SAR reference dipole calibration performed at MVG, using the COMOSAR test bench. The test results covered by accreditation are traceable to the International System of Units (SI).



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.60.2.21.MVGB.A

	Name	Function	Date	Signature
Prepared by :	Jérôme Luc	Technical Manager	3/1/2021	
Checked by :	Jérôme Luc	Technical Manager	3/1/2021	
Approved by :	Yann Toutain	Laboratory Director	3/1/2021	 Yann Toutain

2021.03.0

113:08:18
+01'00'

	Customer Name
Distribution :	SHENZHEN NTEK TESTING TECHNOLOGY CO., LTD.

Issue	Name	Date	Modifications
A	Jérôme Luc	3/1/2021	Initial release



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.60.2.21.MVGB.A

TABLE OF CONTENTS

1	Introduction.....	4
2	Device Under Test	4
3	Product Description	4
3.1	General Information	4
4	Measurement Method	5
4.1	Return Loss Requirements	5
4.2	Mechanical Requirements	5
5	Measurement Uncertainty.....	5
5.1	Return Loss	5
5.2	Dimension Measurement	5
5.3	Validation Measurement	5
6	Calibration Measurement Results.....	6
6.1	Return Loss and Impedance	6
6.2	Mechanical Dimensions	6
7	Validation measurement	7
7.1	Measurement Condition	7
7.2	Head Liquid Measurement	7
7.3	Measurement Result	8
8	List of Equipment	10



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.60.2.21.MVGB.A

1 INTRODUCTION

This document contains a summary of the requirements set forth by the IEEE 1528, FCC KDBs and CEI/IEC 62209 standards for reference dipoles used for SAR measurement system validations and the measurements that were performed to verify that the product complies with the fore mentioned standards.

2 DEVICE UNDER TEST

Device Under Test	
Device Type	COMOSAR 750 MHz REFERENCE DIPOLE
Manufacturer	MVG
Model	SID750
Serial Number	SN 03/15 DIP0G750-355
Product Condition (new / used)	Used

3 PRODUCT DESCRIPTION

3.1 GENERAL INFORMATION

MVG's COMOSAR Validation Dipoles are built in accordance to the IEEE 1528, FCC KDBs and CEI/IEC 62209 standards. The product is designed for use with the COMOSAR test bench only.



Figure 1 – MVG COMOSAR Validation Dipole

**SAR REFERENCE DIPOLE CALIBRATION REPORT**

Ref. ACR.60.2.21.MVGB.A

4 MEASUREMENT METHOD

The IEEE 1528, FCC KDBs and CEI/IEC 62209 standards provide requirements for reference dipoles used for system validation measurements. The following measurements were performed to verify that the product complies with the fore mentioned standards.

4.1 RETURN LOSS REQUIREMENTS

The dipole used for SAR system validation measurements and checks must have a return loss of -20 dB or better. The return loss measurement shall be performed against a liquid filled flat phantom, with the phantom constructed as outlined in the fore mentioned standards. A direct method is used with a network analyser and its calibration kit, both with a valid ISO17025 calibration.

4.2 MECHANICAL REQUIREMENTS

The IEEE Std. 1528 and CEI/IEC 62209 standards specify the mechanical components and dimensions of the validation dipoles, with the dimension's frequency and phantom shell thickness dependent. The COMOSAR test bench employs a 2 mm phantom shell thickness therefore the dipoles sold for use with the COMOSAR test bench comply with the requirements set forth for a 2 mm phantom shell thickness. A direct method is used with a ISO17025 calibrated caliper.

5 MEASUREMENT UNCERTAINTY

All uncertainties listed below represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2, traceable to the Internationally Accepted Guides to Measurement Uncertainty.

5.1 RETURN LOSS

The following uncertainties apply to the return loss measurement:

Frequency band	Expanded Uncertainty on Return Loss
400-6000MHz	0.08 LIN

5.2 DIMENSION MEASUREMENT

The following uncertainties apply to the dimension measurements:

Length (mm)	Expanded Uncertainty on Length
0 - 300	0.20 mm
300 - 450	0.44 mm

5.3 VALIDATION MEASUREMENT

The guidelines outlined in the IEEE 1528, FCC KDBs, CENELEC EN50361 and CEI/IEC 62209 standards were followed to generate the measurement uncertainty for validation measurements.

Scan Volume	Expanded Uncertainty




SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.60.2.21.MVGB.A

1 g	19 % (SAR)
10 g	19 % (SAR)

6 CALIBRATION MEASUREMENT RESULTS

6.1 RETURN LOSS AND IMPEDANCE



Frequency (MHz)	Return Loss (dB)	Requirement (dB)	Impedance
750	-23.80	-20	56.4 Ω - 0.1 jΩ

6.2 MECHANICAL DIMENSIONS

Frequency MHz	L mm		h mm		d mm	
	required	measured	required	measured	required	measured
300	420.0 ±1 %.		250.0 ±1 %.		6.35 ±1 %.	
450	290.0 ±1 %.		166.7 ±1 %.		6.35 ±1 %.	
750	176.0 ±1 %.	-	100.0 ±1 %.	-	6.35 ±1 %.	-
835	161.0 ±1 %.		89.8 ±1 %.		3.6 ±1 %.	
900	149.0 ±1 %.		83.3 ±1 %.		3.6 ±1 %.	
1450	89.1 ±1 %.		51.7 ±1 %.		3.6 ±1 %.	
1500	80.5 ±1 %.		50.0 ±1 %.		3.6 ±1 %.	
1640	79.0 ±1 %.		45.7 ±1 %.		3.6 ±1 %.	
1750	75.2 ±1 %.		42.9 ±1 %.		3.6 ±1 %.	
1800	72.0 ±1 %.		41.7 ±1 %.		3.6 ±1 %.	
1900	68.0 ±1 %.		39.5 ±1 %.		3.6 ±1 %.	
1950	66.3 ±1 %.		38.5 ±1 %.		3.6 ±1 %.	
2000	64.5 ±1 %.		37.5 ±1 %.		3.6 ±1 %.	
2100	61.0 ±1 %.		35.7 ±1 %.		3.6 ±1 %.	
2300	55.5 ±1 %.		32.6 ±1 %.		3.6 ±1 %.	
2450	51.5 ±1 %.		30.4 ±1 %.		3.6 ±1 %.	

Page: 6/10

Template_ACR.DDD.N.YY.MVGB.ISSUE_SAR Reference Dipole vG

This document shall not be reproduced, except in full or in part, without the written approval of MVG. The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.60.2.21.MVGB.A

2600	48.5 ±1 %.		28.8 ±1 %.		3.6 ±1 %.	
3000	41.5 ±1 %.		25.0 ±1 %.		3.6 ±1 %.	
3500	37.0 ±1 %.		26.4 ±1 %.		3.6 ±1 %.	
3700	34.7 ±1 %.		26.4 ±1 %.		3.6 ±1 %.	

7 VALIDATION MEASUREMENT

The IEEE Std. 1528, FCC KDBs and CEI/IEC 62209 standards state that the system validation measurements must be performed using a reference dipole meeting the fore mentioned return loss and mechanical dimension requirements. The validation measurement must be performed against a liquid filled flat phantom, with the phantom constructed as outlined in the fore mentioned standards. Per the standards, the dipole shall be positioned below the bottom of the phantom, with the dipole length centered and parallel to the longest dimension of the flat phantom, with the top surface of the dipole at the described distance from the bottom surface of the phantom.

7.1 MEASUREMENT CONDITION

Software	OPENSAR V5
Phantom	SN 13/09 SAM68
Probe	SN 41/18 EPGO333
Liquid	Head Liquid Values: ϵ_r' : 41.8 sigma : 0.82
Distance between dipole center and liquid	15.0 mm
Area scan resolution	dx=8mm/dy=8mm
Zoon Scan Resolution	dx=8mm/dy=8mm/dz=5mm
Frequency	750750 MHz
Input power	20 dBm
Liquid Temperature	20 +/- 1 °C
Lab Temperature	20 +/- 1 °C
Lab Humidity	30-70 %

7.2 HEAD LIQUID MEASUREMENT

Frequency MHz	Relative permittivity (ϵ_r')		Conductivity (σ) S/m	
	required	measured	required	measured
300	45.3 ±10 %		0.87 ±10 %	
450	43.5 ±10 %		0.87 ±10 %	
750	41.9 ±10 %	41.8	0.89 ±10 %	0.82
835	41.5 ±10 %		0.90 ±10 %	
900	41.5 ±10 %		0.97 ±10 %	
1450	40.5 ±10 %		1.20 ±10 %	
1500	40.4 ±10 %		1.23 ±10 %	
1640	40.2 ±10 %		1.31 ±10 %	
1750	40.1 ±10 %		1.37 ±10 %	
1800	40.0 ±10 %		1.40 ±10 %	
1900	40.0 ±10 %		1.40 ±10 %	
1950	40.0 ±10 %		1.40 ±10 %	
2000	40.0 ±10 %		1.40 ±10 %	

**SAR REFERENCE DIPOLE CALIBRATION REPORT**

Ref: ACR.60.2.21.MVGB.A

2100	$39.8 \pm 10\%$		$1.49 \pm 10\%$	
2300	$39.5 \pm 10\%$		$1.67 \pm 10\%$	
2450	$39.2 \pm 10\%$		$1.80 \pm 10\%$	
2600	$39.0 \pm 10\%$		$1.96 \pm 10\%$	
3000	$38.5 \pm 10\%$		$2.40 \pm 10\%$	
3500	$37.9 \pm 10\%$		$2.91 \pm 10\%$	

7.3 MEASUREMENT RESULT


The IEEE Std. 1528 and CEI/IEC 62209 standards state that the system validation measurements should produce the SAR values shown below (for phantom thickness of 2 mm), within the uncertainty for the system validation. All SAR values are normalized to 1 W forward power. In bracket, the measured SAR is given with the used input power.

Frequency MHz	1 g SAR (W/kg/W)		10 g SAR (W/kg/W)	
	required	measured	required	measured
300	2.85		1.94	
450	4.58		3.06	
750	8.49	8.53 (0.85)	5.55	5.56 (0.56)
835	9.56		6.22	
900	10.9		6.99	
1450	29		16	
1500	30.5		16.8	
1640	34.2		18.4	
1750	36.4		19.3	
1800	38.4		20.1	
1900	39.7		20.5	
1950	40.5		20.9	
2000	41.1		21.1	
2100	43.6		21.9	
2300	48.7		23.3	
2450	52.4		24	
2600	55.3		24.6	
3000	63.8		25.7	
3500	67.1		25	



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.60.2.21.MVGB.A





SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.60.2.21.MVGB.A

8 LIST OF EQUIPMENT

Equipment Summary Sheet				
Equipment Description	Manufacturer / Model	Identification No.	Current Calibration Date	Next Calibration Date
SAM Phantom	MVG	SN-13/09-SAM68	Validated. No cal required.	Validated. No cal required.
COMOSAR Test Bench	Version 3	NA	Validated. No cal required.	Validated. No cal required.
Network Analyzer	Rohde & Schwarz ZVM	100203	05/2019	05/2022
Network Analyzer – Calibration kit	Rohde & Schwarz ZV-Z235	101223	05/2019	05/2022
Calipers	Mitutoyo	SN 0009732	10/2019	10/2022
Reference Probe	MVG	EPGO333 SN 41/18	05/2020	05/2021
Multimeter	Keithley 2000	1160271	02/2020	02/2023
Signal Generator	Rohde & Schwarz SMB	106589	04/2019	04/2022
Amplifier	Aethercomm	SN 046	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.
Power Meter	NI-USB 5680	170100013	05/2019	05/2022
Directional Coupler	Narda 4216-20	01386	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.
Temperature / Humidity Sensor	Testo 184 H1	44220687	05/2020	05/2023



SAR Reference Dipole Calibration Report

Ref : ACR.60.4.21.MVGB.A

SHENZHEN NTEK TESTING TECHNOLOGY CO., LTD.

BUILDING E, FENDA SCIENCE PARK, SANWEI
COMMUNITY, XIXIANG STREET,
BAO'AN DISTRICT, SHENZHEN GUANGDONG, CHINA
MVG COMOSAR REFERENCE DIPOLE
FREQUENCY: 900 MHZ
SERIAL NO.: SN 03/15 DIP0G900-348

Calibrated at MVG

Z.I. de la pointe du diable

Technopôle Brest Iroise – 295 avenue Alexis de Rochon
29280 PLOUZANE - FRANCE

Calibration date: 03/01/2021



Accreditations #2-6789 and #2-6814
Scope available on www.cofrac.fr


Summary:

This document presents the method and results from an accredited SAR reference dipole calibration performed at MVG, using the COMOSAR test bench. The test results covered by accreditation are traceable to the International System of Units (SI).



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.60.4.21.MVGB.A

	Name	Function	Date	Signature
Prepared by :	Jérôme Luc	Technical Manager	3/1/2021	
Checked by :	Jérôme Luc	Technical Manager	3/1/2021	
Approved by :	Yann Toutain	Laboratory Director	3/1/2021	

Mode d'empilement 2021.03.0

1
 13:09:56
 +01'00'
 PHILIPS

	Customer Name
Distribution :	SHENZHEN NTEK TESTING TECHNOLOGY CO., LTD.

Issue	Name	Date	Modifications
A	Jérôme Luc	3/1/2021	Initial release



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.60.4.21.MVGB.A

TABLE OF CONTENTS

1	Introduction.....	4
2	Device Under Test	4
3	Product Description	4
3.1	General Information	4
4	Measurement Method	5
4.1	Return Loss Requirements	5
4.2	Mechanical Requirements	5
5	Measurement Uncertainty.....	5
5.1	Return Loss	5
5.2	Dimension Measurement	5
5.3	Validation Measurement	5
6	Calibration Measurement Results.....	6
6.1	Return Loss and Impedance	6
6.2	Mechanical Dimensions	6
7	Validation measurement	7
7.1	Measurement Condition	7
7.2	Head Liquid Measurement	7
7.3	Measurement Result	8
8	List of Equipment	10



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref. ACR.60.4.21.MVGB.A

1 INTRODUCTION

This document contains a summary of the requirements set forth by the IEEE 1528, FCC KDBs and CEI/IEC 62209 standards for reference dipoles used for SAR measurement system validations and the measurements that were performed to verify that the product complies with the fore mentioned standards.

2 DEVICE UNDER TEST

Device Under Test	
Device Type	COMOSAR 900 MHz REFERENCE DIPOLE
Manufacturer	MVG
Model	SID900
Serial Number	SN 03/15 DIP0G900-348
Product Condition (new / used)	Used

3 PRODUCT DESCRIPTION

3.1 GENERAL INFORMATION

MVG's COMOSAR Validation Dipoles are built in accordance to the IEEE 1528, FCC KDBs and CEI/IEC 62209 standards. The product is designed for use with the COMOSAR test bench only.



Figure 1 – MVG COMOSAR Validation Dipole

**SAR REFERENCE DIPOLE CALIBRATION REPORT**

Ref. ACR.60.4.21.MVGB.A

4 MEASUREMENT METHOD

The IEEE 1528, FCC KDBs and CEI/IEC 62209 standards provide requirements for reference dipoles used for system validation measurements. The following measurements were performed to verify that the product complies with the fore mentioned standards.

4.1 RETURN LOSS REQUIREMENTS

The dipole used for SAR system validation measurements and checks must have a return loss of -20 dB or better. The return loss measurement shall be performed against a liquid filled flat phantom, with the phantom constructed as outlined in the fore mentioned standards. A direct method is used with a network analyser and its calibration kit, both with a valid ISO17025 calibration.

4.2 MECHANICAL REQUIREMENTS

The IEEE Std. 1528 and CEI/IEC 62209 standards specify the mechanical components and dimensions of the validation dipoles, with the dimension's frequency and phantom shell thickness dependent. The COMOSAR test bench employs a 2 mm phantom shell thickness therefore the dipoles sold for use with the COMOSAR test bench comply with the requirements set forth for a 2 mm phantom shell thickness. A direct method is used with a ISO17025 calibrated caliper.

5 MEASUREMENT UNCERTAINTY

All uncertainties listed below represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2, traceable to the Internationally Accepted Guides to Measurement Uncertainty.

5.1 RETURN LOSS

The following uncertainties apply to the return loss measurement:

Frequency band	Expanded Uncertainty on Return Loss
400-6000MHz	0.08 LIN

5.2 DIMENSION MEASUREMENT

The following uncertainties apply to the dimension measurements:

Length (mm)	Expanded Uncertainty on Length
0 - 300	0.20 mm
300 - 450	0.44 mm

5.3 VALIDATION MEASUREMENT

The guidelines outlined in the IEEE 1528, FCC KDBs, CENELEC EN50361 and CEI/IEC 62209 standards were followed to generate the measurement uncertainty for validation measurements.

Scan Volume	Expanded Uncertainty




SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref. ACR.60.4.21.MVGB.A

1 g	19 % (SAR)
10 g	19 % (SAR)

6 CALIBRATION MEASUREMENT RESULTS

6.1 RETURN LOSS AND IMPEDANCE



Frequency (MHz)	Return Loss (dB)	Requirement (dB)	Impedance
900	-34.70	-20	51.0 Ω - 1.5 jΩ

6.2 MECHANICAL DIMENSIONS

Frequency MHz	L mm		h mm		d mm	
	required	measured	required	measured	required	measured
300	420.0 ±1 %.		250.0 ±1 %.		6.35 ±1 %.	
450	290.0 ±1 %.		166.7 ±1 %.		6.35 ±1 %.	
750	176.0 ±1 %.		100.0 ±1 %.		6.35 ±1 %.	
835	161.0 ±1 %.		89.8 ±1 %.		3.6 ±1 %.	
900	149.0 ±1 %.	-	83.3 ±1 %.	-	3.6 ±1 %.	-
1450	89.1 ±1 %.		51.7 ±1 %.		3.6 ±1 %.	
1500	80.5 ±1 %.		50.0 ±1 %.		3.6 ±1 %.	
1640	79.0 ±1 %.		45.7 ±1 %.		3.6 ±1 %.	
1750	75.2 ±1 %.		42.9 ±1 %.		3.6 ±1 %.	
1800	72.0 ±1 %.		41.7 ±1 %.		3.6 ±1 %.	
1900	68.0 ±1 %.		39.5 ±1 %.		3.6 ±1 %.	
1950	66.3 ±1 %.		38.5 ±1 %.		3.6 ±1 %.	
2000	64.5 ±1 %.		37.5 ±1 %.		3.6 ±1 %.	
2100	61.0 ±1 %.		35.7 ±1 %.		3.6 ±1 %.	
2300	55.5 ±1 %.		32.6 ±1 %.		3.6 ±1 %.	
2450	51.5 ±1 %.		30.4 ±1 %.		3.6 ±1 %.	

Page: 6/10

Template_ACR.DDD.N.YY.MVGB.ISSUE_SAR Reference Dipole vG

This document shall not be reproduced, except in full or in part, without the written approval of MVG. The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.60.4.21.MVGB.A

2600	48.5 ±1 %.		28.8 ±1 %.		3.6 ±1 %.	
3000	41.5 ±1 %.		25.0 ±1 %.		3.6 ±1 %.	
3500	37.0 ±1 %.		26.4 ±1 %.		3.6 ±1 %.	
3700	34.7 ±1 %.		26.4 ±1 %.		3.6 ±1 %.	

7 VALIDATION MEASUREMENT

The IEEE Std. 1528, FCC KDBs and CEI/IEC 62209 standards state that the system validation measurements must be performed using a reference dipole meeting the fore mentioned return loss and mechanical dimension requirements. The validation measurement must be performed against a liquid filled flat phantom, with the phantom constructed as outlined in the fore mentioned standards. Per the standards, the dipole shall be positioned below the bottom of the phantom, with the dipole length centered and parallel to the longest dimension of the flat phantom, with the top surface of the dipole at the described distance from the bottom surface of the phantom.

7.1 MEASUREMENT CONDITION

Software	OPENSAR V5
Phantom	SN 13/09 SAM68
Probe	SN 41/18 EPGO333
Liquid	Head Liquid Values: ϵ_r' : 39.8 sigma : 0.97
Distance between dipole center and liquid	15.0 mm
Area scan resolution	dx=8mm/dy=8mm
Zoon Scan Resolution	dx=8mm/dy=8mm/dz=5mm
Frequency	900900 MHz
Input power	20 dBm
Liquid Temperature	20 +/- 1 °C
Lab Temperature	20 +/- 1 °C
Lab Humidity	30-70 %

7.2 HEAD LIQUID MEASUREMENT

Frequency MHz	Relative permittivity (ϵ_r')		Conductivity (σ) S/m	
	required	measured	required	measured
300	45.3 ±10 %		0.87 ±10 %	
450	43.5 ±10 %		0.87 ±10 %	
750	41.9 ±10 %		0.89 ±10 %	
835	41.5 ±10 %		0.90 ±10 %	
900	41.5 ±10 %	39.8	0.97 ±10 %	0.97
1450	40.5 ±10 %		1.20 ±10 %	
1500	40.4 ±10 %		1.23 ±10 %	
1640	40.2 ±10 %		1.31 ±10 %	
1750	40.1 ±10 %		1.37 ±10 %	
1800	40.0 ±10 %		1.40 ±10 %	
1900	40.0 ±10 %		1.40 ±10 %	
1950	40.0 ±10 %		1.40 ±10 %	
2000	40.0 ±10 %		1.40 ±10 %	



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.60.4.21.MVGB.A

2100	$39.8 \pm 10\%$		$1.49 \pm 10\%$	
2300	$39.5 \pm 10\%$		$1.67 \pm 10\%$	
2450	$39.2 \pm 10\%$		$1.80 \pm 10\%$	
2600	$39.0 \pm 10\%$		$1.96 \pm 10\%$	
3000	$38.5 \pm 10\%$		$2.40 \pm 10\%$	
3500	$37.9 \pm 10\%$		$2.91 \pm 10\%$	

7.3 MEASUREMENT RESULT


The IEEE Std. 1528 and CEI/IEC 62209 standards state that the system validation measurements should produce the SAR values shown below (for phantom thickness of 2 mm), within the uncertainty for the system validation. All SAR values are normalized to 1 W forward power. In bracket, the measured SAR is given with the used input power.

Frequency MHz	1 g SAR (W/kg/W)		10 g SAR (W/kg/W)	
	required	measured	required	measured
300	2.85		1.94	
450	4.58		3.06	
750	8.49		5.55	
835	9.56		6.22	
900	10.9	11.08 (1.11)	6.99	6.81 (0.68)
1450	29		16	
1500	30.5		16.8	
1640	34.2		18.4	
1750	36.4		19.3	
1800	38.4		20.1	
1900	39.7		20.5	
1950	40.5		20.9	
2000	41.1		21.1	
2100	43.6		21.9	
2300	48.7		23.3	
2450	52.4		24	
2600	55.3		24.6	
3000	63.8		25.7	
3500	67.1		25	



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref. ACR.60.4.21.MVGB.A





SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.60.4.21.MVGB.A

8 LIST OF EQUIPMENT

Equipment Summary Sheet				
Equipment Description	Manufacturer / Model	Identification No.	Current Calibration Date	Next Calibration Date
SAM Phantom	MVG	SN-13/09-SAM68	Validated. No cal required.	Validated. No cal required.
COMOSAR Test Bench	Version 3	NA	Validated. No cal required.	Validated. No cal required.
Network Analyzer	Rohde & Schwarz ZVM	100203	05/2019	05/2022
Network Analyzer – Calibration kit	Rohde & Schwarz ZV-Z235	101223	05/2019	05/2022
Calipers	Mitutoyo	SN 0009732	10/2019	10/2022
Reference Probe	MVG	EPGO333 SN 41/18	05/2020	05/2021
Multimeter	Keithley 2000	1160271	02/2020	02/2023
Signal Generator	Rohde & Schwarz SMB	106589	04/2019	04/2022
Amplifier	Aethercomm	SN 046	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.
Power Meter	NI-USB 5680	170100013	05/2019	05/2022
Directional Coupler	Narda 4216-20	01386	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.
Temperature / Humidity Sensor	Testo 184 H1	44220687	05/2020	05/2023



SAR Reference Dipole Calibration Report

Ref : ACR.60.5.21.MVGB.A

SHENZHEN NTEK TESTING TECHNOLOGY CO., LTD.

BUILDING E, FENDA SCIENCE PARK, SANWEI
COMMUNITY, XIXIANG STREET,
BAO'AN DISTRICT, SHENZHEN GUANGDONG, CHINA

MVG COMOSAR REFERENCE DIPOLE

FREQUENCY: 1800 MHZ

SERIAL NO.: SN 03/15 DIP1G800-349

Calibrated at MVG

Z.I. de la pointe du diable

Technopôle Brest Iroise – 295 avenue Alexis de Rochon
29280 PLOUZANE - FRANCE

Calibration date: 03/01/2021



Accreditations #2-6789 and #2-6814
Scope available on www.cofrac.fr

Summary:

This document presents the method and results from an accredited SAR reference dipole calibration performed at MVG, using the COMOSAR test bench. The test results covered by accreditation are traceable to the International System of Units (SI).



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref. ACR.60.5.21.MVGB.A

	Name	Function	Date	Signature
Prepared by :	Jérôme Luc	Technical Manager	3/1/2021	
Checked by :	Jérôme Luc	Technical Manager	3/1/2021	
Approved by :	Yann Toutain	Laboratory Director	3/1/2021	 Mode d'emploi

2021.03.0

1 13:10:48

+01'00'

PHILIPS

	Customer Name
Distribution :	SHENZHEN NTEK TESTING TECHNOLOGY CO., LTD.

Issue	Name	Date	Modifications
A	Jérôme Luc	3/1/2021	Initial release



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.60.5.21.MVGB.A

TABLE OF CONTENTS

1	Introduction.....	4
2	Device Under Test	4
3	Product Description	4
3.1	General Information	4
4	Measurement Method	5
4.1	Return Loss Requirements	5
4.2	Mechanical Requirements	5
5	Measurement Uncertainty.....	5
5.1	Return Loss	5
5.2	Dimension Measurement	5
5.3	Validation Measurement	5
6	Calibration Measurement Results.....	6
6.1	Return Loss and Impedance	6
6.2	Mechanical Dimensions	6
7	Validation measurement	7
7.1	Measurement Condition	7
7.2	Head Liquid Measurement	7
7.3	Measurement Result	8
8	List of Equipment	10



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.60.5.21.MVGB.A

1 INTRODUCTION

This document contains a summary of the requirements set forth by the IEEE 1528, FCC KDBs and CEI/IEC 62209 standards for reference dipoles used for SAR measurement system validations and the measurements that were performed to verify that the product complies with the fore mentioned standards.

2 DEVICE UNDER TEST

Device Under Test	
Device Type	COMOSAR 1800 MHz REFERENCE DIPOLE
Manufacturer	MVG
Model	SID1800
Serial Number	SN 03/15 DIP1G800-349
Product Condition (new / used)	Used

3 PRODUCT DESCRIPTION

3.1 GENERAL INFORMATION

MVG's COMOSAR Validation Dipoles are built in accordance to the IEEE 1528, FCC KDBs and CEI/IEC 62209 standards. The product is designed for use with the COMOSAR test bench only.



Figure 1 – MVG COMOSAR Validation Dipole



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref. ACR.60.5.21.MVGB.A

4 MEASUREMENT METHOD

The IEEE 1528, FCC KDBs and CEI/IEC 62209 standards provide requirements for reference dipoles used for system validation measurements. The following measurements were performed to verify that the product complies with the fore mentioned standards.

4.1 RETURN LOSS REQUIREMENTS

The dipole used for SAR system validation measurements and checks must have a return loss of -20 dB or better. The return loss measurement shall be performed against a liquid filled flat phantom, with the phantom constructed as outlined in the fore mentioned standards. A direct method is used with a network analyser and its calibration kit, both with a valid ISO17025 calibration.

4.2 MECHANICAL REQUIREMENTS

The IEEE Std. 1528 and CEI/IEC 62209 standards specify the mechanical components and dimensions of the validation dipoles, with the dimension's frequency and phantom shell thickness dependent. The COMOSAR test bench employs a 2 mm phantom shell thickness therefore the dipoles sold for use with the COMOSAR test bench comply with the requirements set forth for a 2 mm phantom shell thickness. A direct method is used with a ISO17025 calibrated caliper.

5 MEASUREMENT UNCERTAINTY

All uncertainties listed below represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2, traceable to the Internationally Accepted Guides to Measurement Uncertainty.

5.1 RETURN LOSS

The following uncertainties apply to the return loss measurement:

Frequency band	Expanded Uncertainty on Return Loss
400-6000MHz	0.08 LIN

5.2 DIMENSION MEASUREMENT

The following uncertainties apply to the dimension measurements:

Length (mm)	Expanded Uncertainty on Length
0 - 300	0.20 mm
300 - 450	0.44 mm

5.3 VALIDATION MEASUREMENT

The guidelines outlined in the IEEE 1528, FCC KDBs, CENELEC EN50361 and CEI/IEC 62209 standards were followed to generate the measurement uncertainty for validation measurements.

Scan Volume	Expanded Uncertainty




SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.60.5.21.MVGB.A

1 g	19 % (SAR)
10 g	19 % (SAR)

6 CALIBRATION MEASUREMENT RESULTS

6.1 RETURN LOSS AND IMPEDANCE



Frequency (MHz)	Return Loss (dB)	Requirement (dB)	Impedance
1800	-28.85	-20	$47.9 \Omega + 2.9 j\Omega$

6.2 MECHANICAL DIMENSIONS

Frequency MHz	L mm		h mm		d mm	
	required	measured	required	measured	required	measured
300	$420.0 \pm 1\%$.		$250.0 \pm 1\%$.		$6.35 \pm 1\%$.	
450	$290.0 \pm 1\%$.		$166.7 \pm 1\%$.		$6.35 \pm 1\%$.	
750	$176.0 \pm 1\%$.		$100.0 \pm 1\%$.		$6.35 \pm 1\%$.	
835	$161.0 \pm 1\%$.		$89.8 \pm 1\%$.		$3.6 \pm 1\%$.	
900	$149.0 \pm 1\%$.		$83.3 \pm 1\%$.		$3.6 \pm 1\%$.	
1450	$89.1 \pm 1\%$.		$51.7 \pm 1\%$.		$3.6 \pm 1\%$.	
1500	$80.5 \pm 1\%$.		$50.0 \pm 1\%$.		$3.6 \pm 1\%$.	
1640	$79.0 \pm 1\%$.		$45.7 \pm 1\%$.		$3.6 \pm 1\%$.	
1750	$75.2 \pm 1\%$.		$42.9 \pm 1\%$.		$3.6 \pm 1\%$.	
1800	$72.0 \pm 1\%$.	-	$41.7 \pm 1\%$.	-	$3.6 \pm 1\%$.	-
1900	$68.0 \pm 1\%$.		$39.5 \pm 1\%$.		$3.6 \pm 1\%$.	
1950	$66.3 \pm 1\%$.		$38.5 \pm 1\%$.		$3.6 \pm 1\%$.	
2000	$64.5 \pm 1\%$.		$37.5 \pm 1\%$.		$3.6 \pm 1\%$.	
2100	$61.0 \pm 1\%$.		$35.7 \pm 1\%$.		$3.6 \pm 1\%$.	
2300	$55.5 \pm 1\%$.		$32.6 \pm 1\%$.		$3.6 \pm 1\%$.	
2450	$51.5 \pm 1\%$.		$30.4 \pm 1\%$.		$3.6 \pm 1\%$.	

Page: 6/10

Template_ACR.DDD.N.YY.MVGB.ISSUE_SAR Reference Dipole vG

This document shall not be reproduced, except in full or in part, without the written approval of MVG. The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.60.5.21.MVGB.A

2600	48.5 ±1 %.		28.8 ±1 %.		3.6 ±1 %.	
3000	41.5 ±1 %.		25.0 ±1 %.		3.6 ±1 %.	
3500	37.0 ±1 %.		26.4 ±1 %.		3.6 ±1 %.	
3700	34.7 ±1 %.		26.4 ±1 %.		3.6 ±1 %.	

7 VALIDATION MEASUREMENT

The IEEE Std. 1528, FCC KDBs and CEI/IEC 62209 standards state that the system validation measurements must be performed using a reference dipole meeting the fore mentioned return loss and mechanical dimension requirements. The validation measurement must be performed against a liquid filled flat phantom, with the phantom constructed as outlined in the fore mentioned standards. Per the standards, the dipole shall be positioned below the bottom of the phantom, with the dipole length centered and parallel to the longest dimension of the flat phantom, with the top surface of the dipole at the described distance from the bottom surface of the phantom.

7.1 MEASUREMENT CONDITION

Software	OPENSAR V5
Phantom	SN 13/09 SAM68
Probe	SN 41/18 EPGO333
Liquid	Head Liquid Values: ϵ_r' : 43.7 sigma : 1.34
Distance between dipole center and liquid	10.0 mm
Area scan resolution	$dx=8mm/dy=8mm$
Zoon Scan Resolution	$dx=8mm/dy=8mm/dz=5mm$
Frequency	18001800 MHz
Input power	20 dBm
Liquid Temperature	20 +/- 1 °C
Lab Temperature	20 +/- 1 °C
Lab Humidity	30-70 %

7.2 HEAD LIQUID MEASUREMENT

Frequency MHz	Relative permittivity (ϵ_r')		Conductivity (σ) S/m	
	required	measured	required	measured
300	45.3 ±10 %		0.87 ±10 %	
450	43.5 ±10 %		0.87 ±10 %	
750	41.9 ±10 %		0.89 ±10 %	
835	41.5 ±10 %		0.90 ±10 %	
900	41.5 ±10 %		0.97 ±10 %	
1450	40.5 ±10 %		1.20 ±10 %	
1500	40.4 ±10 %		1.23 ±10 %	
1640	40.2 ±10 %		1.31 ±10 %	
1750	40.1 ±10 %		1.37 ±10 %	
1800	40.0 ±10 %	43.7	1.40 ±10 %	1.34
1900	40.0 ±10 %		1.40 ±10 %	
1950	40.0 ±10 %		1.40 ±10 %	
2000	40.0 ±10 %		1.40 ±10 %	

Page: 7/10

Template_ACR.DDD.N.YY.MVGB.ISSUE_SAR Reference Dipole vG

This document shall not be reproduced, except in full or in part, without the written approval of MVG. The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref. ACR.60.5.21.MVGB.A

2100	$39.8 \pm 10\%$		$1.49 \pm 10\%$	
2300	$39.5 \pm 10\%$		$1.67 \pm 10\%$	
2450	$39.2 \pm 10\%$		$1.80 \pm 10\%$	
2600	$39.0 \pm 10\%$		$1.96 \pm 10\%$	
3000	$38.5 \pm 10\%$		$2.40 \pm 10\%$	
3500	$37.9 \pm 10\%$		$2.91 \pm 10\%$	

7.3 MEASUREMENT RESULT


The IEEE Std. 1528 and CEI/IEC 62209 standards state that the system validation measurements should produce the SAR values shown below (for phantom thickness of 2 mm), within the uncertainty for the system validation. All SAR values are normalized to 1 W forward power. In bracket, the measured SAR is given with the used input power.

Frequency MHz	1 g SAR (W/kg/W)		10 g SAR (W/kg/W)	
	required	measured	required	measured
300	2.85		1.94	
450	4.58		3.06	
750	8.49		5.55	
835	9.56		6.22	
900	10.9		6.99	
1450	29		16	
1500	30.5		16.8	
1640	34.2		18.4	
1750	36.4		19.3	
1800	38.4	37.96 (3.80)	20.1	19.81 (1.98)
1900	39.7		20.5	
1950	40.5		20.9	
2000	41.1		21.1	
2100	43.6		21.9	
2300	48.7		23.3	
2450	52.4		24	
2600	55.3		24.6	
3000	63.8		25.7	
3500	67.1		25	



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.60.5.21.MVGB.A





SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref. ACR.60.5.21.MVGB.A

8 LIST OF EQUIPMENT

Equipment Summary Sheet				
Equipment Description	Manufacturer / Model	Identification No.	Current Calibration Date	Next Calibration Date
SAM Phantom	MVG	SN-13/09-SAM68	Validated. No cal required.	Validated. No cal required.
COMOSAR Test Bench	Version 3	NA	Validated. No cal required.	Validated. No cal required.
Network Analyzer	Rohde & Schwarz ZVM	100203	05/2019	05/2022
Network Analyzer – Calibration kit	Rohde & Schwarz ZV-Z235	101223	05/2019	05/2022
Calipers	Mitutoyo	SN 0009732	10/2019	10/2022
Reference Probe	MVG	EPGO333 SN 41/18	05/2020	05/2021
Multimeter	Keithley 2000	1160271	02/2020	02/2023
Signal Generator	Rohde & Schwarz SMB	106589	04/2019	04/2022
Amplifier	Aethercomm	SN 046	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.
Power Meter	NI-USB 5680	170100013	05/2019	05/2022
Directional Coupler	Narda 4216-20	01386	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.
Temperature / Humidity Sensor	Testo 184 H1	44220687	05/2020	05/2023



SAR Reference Dipole Calibration Report

Ref : ACR.60.7.21.MVGB.A

SHENZHEN NTEK TESTING TECHNOLOGY CO., LTD.

BUILDING E, FENDA SCIENCE PARK, SANWEI
COMMUNITY, XIXIANG STREET,
BAO'AN DISTRICT, SHENZHEN GUANGDONG, CHINA

MVG COMOSAR REFERENCE DIPOLE

FREQUENCY: 2000 MHZ

SERIAL NO.: SN 03/15 DIP2G000-351

Calibrated at MVG

Z.I. de la pointe du diable

Technopôle Brest Iroise – 295 avenue Alexis de Rochon
29280 PLOUZANE - FRANCE

Calibration date: 03/01/2021



Accreditations #2-6789 and #2-6814
Scope available on www.cofrac.fr


Summary:

This document presents the method and results from an accredited SAR reference dipole calibration performed at MVG, using the COMOSAR test bench. The test results covered by accreditation are traceable to the International System of Units (SI).



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.60.7.21.MVGB.A

	Name	Function	Date	Signature
Prepared by :	Jérôme Luc	Technical Manager	3/1/2021	
Checked by :	Jérôme Luc	Technical Manager	3/1/2021	
Approved by :	Yann Toutain	Laboratory Director	3/1/2021	 Yann Toutain

2021.03.0
113:12:43
+01'00'
PHIPE

	Customer Name
Distribution :	SHENZHEN NTEK TESTING TECHNOLOGY CO., LTD.

Issue	Name	Date	Modifications
A	Jérôme Luc	3/1/2021	Initial release



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.60.7.21.MVGB.A

TABLE OF CONTENTS

1	Introduction.....	4
2	Device Under Test	4
3	Product Description	4
3.1	General Information	4
4	Measurement Method	5
4.1	Return Loss Requirements	5
4.2	Mechanical Requirements	5
5	Measurement Uncertainty.....	5
5.1	Return Loss	5
5.2	Dimension Measurement	5
5.3	Validation Measurement	5
6	Calibration Measurement Results.....	6
6.1	Return Loss and Impedance	6
6.2	Mechanical Dimensions	6
7	Validation measurement	7
7.1	Measurement Condition	7
7.2	Head Liquid Measurement	7
7.3	Measurement Result	8
8	List of Equipment	10



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref. ACR.60.7.21.MVGB.A

1 INTRODUCTION

This document contains a summary of the requirements set forth by the IEEE 1528, FCC KDBs and CEI/IEC 62209 standards for reference dipoles used for SAR measurement system validations and the measurements that were performed to verify that the product complies with the fore mentioned standards.

2 DEVICE UNDER TEST

Device Under Test	
Device Type	COMOSAR 2000 MHz REFERENCE DIPOLE
Manufacturer	MVG
Model	SID2000
Serial Number	SN 03/15 DIP2G000-351
Product Condition (new / used)	Used

3 PRODUCT DESCRIPTION

3.1 GENERAL INFORMATION

MVG's COMOSAR Validation Dipoles are built in accordance to the IEEE 1528, FCC KDBs and CEI/IEC 62209 standards. The product is designed for use with the COMOSAR test bench only.



Figure 1 – MVG COMOSAR Validation Dipole

**SAR REFERENCE DIPOLE CALIBRATION REPORT**

Ref: ACR.60.7.21.MVGB.A

4 MEASUREMENT METHOD

The IEEE 1528, FCC KDBs and CEI/IEC 62209 standards provide requirements for reference dipoles used for system validation measurements. The following measurements were performed to verify that the product complies with the fore mentioned standards.

4.1 RETURN LOSS REQUIREMENTS

The dipole used for SAR system validation measurements and checks must have a return loss of -20 dB or better. The return loss measurement shall be performed against a liquid filled flat phantom, with the phantom constructed as outlined in the fore mentioned standards. A direct method is used with a network analyser and its calibration kit, both with a valid ISO17025 calibration.

4.2 MECHANICAL REQUIREMENTS

The IEEE Std. 1528 and CEI/IEC 62209 standards specify the mechanical components and dimensions of the validation dipoles, with the dimension's frequency and phantom shell thickness dependent. The COMOSAR test bench employs a 2 mm phantom shell thickness therefore the dipoles sold for use with the COMOSAR test bench comply with the requirements set forth for a 2 mm phantom shell thickness. A direct method is used with a ISO17025 calibrated caliper.

5 MEASUREMENT UNCERTAINTY

All uncertainties listed below represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2, traceable to the Internationally Accepted Guides to Measurement Uncertainty.

5.1 RETURN LOSS

The following uncertainties apply to the return loss measurement:

Frequency band	Expanded Uncertainty on Return Loss
400-6000MHz	0.08 LIN

5.2 DIMENSION MEASUREMENT

The following uncertainties apply to the dimension measurements:

Length (mm)	Expanded Uncertainty on Length
0 - 300	0.20 mm
300 - 450	0.44 mm

5.3 VALIDATION MEASUREMENT

The guidelines outlined in the IEEE 1528, FCC KDBs, CENELEC EN50361 and CEI/IEC 62209 standards were followed to generate the measurement uncertainty for validation measurements.

Scan Volume	Expanded Uncertainty




SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.60.7.21.MVGB.A

1 g	19 % (SAR)
10 g	19 % (SAR)

6 CALIBRATION MEASUREMENT RESULTS

6.1 RETURN LOSS AND IMPEDANCE



Frequency (MHz)	Return Loss (dB)	Requirement (dB)	Impedance
2000	-20.68	-20	$60.3 \Omega + 0.1 j\Omega$

6.2 MECHANICAL DIMENSIONS

Frequency MHz	L mm		h mm		d mm	
	required	measured	required	measured	required	measured
300	$420.0 \pm 1\%$.		$250.0 \pm 1\%$.		$6.35 \pm 1\%$.	
450	$290.0 \pm 1\%$.		$166.7 \pm 1\%$.		$6.35 \pm 1\%$.	
750	$176.0 \pm 1\%$.		$100.0 \pm 1\%$.		$6.35 \pm 1\%$.	
835	$161.0 \pm 1\%$.		$89.8 \pm 1\%$.		$3.6 \pm 1\%$.	
900	$149.0 \pm 1\%$.		$83.3 \pm 1\%$.		$3.6 \pm 1\%$.	
1450	$89.1 \pm 1\%$.		$51.7 \pm 1\%$.		$3.6 \pm 1\%$.	
1500	$80.5 \pm 1\%$.		$50.0 \pm 1\%$.		$3.6 \pm 1\%$.	
1640	$79.0 \pm 1\%$.		$45.7 \pm 1\%$.		$3.6 \pm 1\%$.	
1750	$75.2 \pm 1\%$.		$42.9 \pm 1\%$.		$3.6 \pm 1\%$.	
1800	$72.0 \pm 1\%$.		$41.7 \pm 1\%$.		$3.6 \pm 1\%$.	
1900	$68.0 \pm 1\%$.		$39.5 \pm 1\%$.		$3.6 \pm 1\%$.	
1950	$66.3 \pm 1\%$.		$38.5 \pm 1\%$.		$3.6 \pm 1\%$.	
2000	$64.5 \pm 1\%$.	-	$37.5 \pm 1\%$.	-	$3.6 \pm 1\%$.	-
2100	$61.0 \pm 1\%$.		$35.7 \pm 1\%$.		$3.6 \pm 1\%$.	
2300	$55.5 \pm 1\%$.		$32.6 \pm 1\%$.		$3.6 \pm 1\%$.	
2450	$51.5 \pm 1\%$.		$30.4 \pm 1\%$.		$3.6 \pm 1\%$.	

Page: 6/10

Template_ACR.DDD.N.YY.MVGB.ISSUE_SAR Reference Dipole vG

This document shall not be reproduced, except in full or in part, without the written approval of MVG. The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.60.7.21.MVGB.A

2600	48.5 ±1 %.		28.8 ±1 %.		3.6 ±1 %.	
3000	41.5 ±1 %.		25.0 ±1 %.		3.6 ±1 %.	
3500	37.0 ±1 %.		26.4 ±1 %.		3.6 ±1 %.	
3700	34.7 ±1 %.		26.4 ±1 %.		3.6 ±1 %.	

7 VALIDATION MEASUREMENT

The IEEE Std. 1528, FCC KDBs and CEI/IEC 62209 standards state that the system validation measurements must be performed using a reference dipole meeting the fore mentioned return loss and mechanical dimension requirements. The validation measurement must be performed against a liquid filled flat phantom, with the phantom constructed as outlined in the fore mentioned standards. Per the standards, the dipole shall be positioned below the bottom of the phantom, with the dipole length centered and parallel to the longest dimension of the flat phantom, with the top surface of the dipole at the described distance from the bottom surface of the phantom.

7.1 MEASUREMENT CONDITION

Software	OPENSAR V5
Phantom	SN 13/09 SAM68
Probe	SN 41/18 EPGO333
Liquid	Head Liquid Values: ϵ_r' : 43.1 sigma : 1.48
Distance between dipole center and liquid	10.0 mm
Area scan resolution	dx=8mm/dy=8mm
Zoon Scan Resolution	dx=5mm/dy=5mm/dz=5mm
Frequency	20002000 MHz
Input power	20 dBm
Liquid Temperature	20 +/- 1 °C
Lab Temperature	20 +/- 1 °C
Lab Humidity	30-70 %

7.2 HEAD LIQUID MEASUREMENT

Frequency MHz	Relative permittivity (ϵ_r')		Conductivity (σ) S/m	
	required	measured	required	measured
300	45.3 ±10 %		0.87 ±10 %	
450	43.5 ±10 %		0.87 ±10 %	
750	41.9 ±10 %		0.89 ±10 %	
835	41.5 ±10 %		0.90 ±10 %	
900	41.5 ±10 %		0.97 ±10 %	
1450	40.5 ±10 %		1.20 ±10 %	
1500	40.4 ±10 %		1.23 ±10 %	
1640	40.2 ±10 %		1.31 ±10 %	
1750	40.1 ±10 %		1.37 ±10 %	
1800	40.0 ±10 %		1.40 ±10 %	
1900	40.0 ±10 %		1.40 ±10 %	
1950	40.0 ±10 %		1.40 ±10 %	
2000	40.0 ±10 %	43.1	1.40 ±10 %	1.48

Page: 7/10

Template_ACR.DDD.N.YY.MVGB.ISSUE_SAR Reference Dipole vG

This document shall not be reproduced, except in full or in part, without the written approval of MVG. The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref. ACR.60.7.21.MVGB.A

2100	$39.8 \pm 10\%$		$1.49 \pm 10\%$	
2300	$39.5 \pm 10\%$		$1.67 \pm 10\%$	
2450	$39.2 \pm 10\%$		$1.80 \pm 10\%$	
2600	$39.0 \pm 10\%$		$1.96 \pm 10\%$	
3000	$38.5 \pm 10\%$		$2.40 \pm 10\%$	
3500	$37.9 \pm 10\%$		$2.91 \pm 10\%$	

7.3 MEASUREMENT RESULT


The IEEE Std. 1528 and CEI/IEC 62209 standards state that the system validation measurements should produce the SAR values shown below (for phantom thickness of 2 mm), within the uncertainty for the system validation. All SAR values are normalized to 1 W forward power. In bracket, the measured SAR is given with the used input power.

Frequency MHz	1 g SAR (W/kg/W)		10 g SAR (W/kg/W)	
	required	measured	required	measured
300	2.85		1.94	
450	4.58		3.06	
750	8.49		5.55	
835	9.56		6.22	
900	10.9		6.99	
1450	29		16	
1500	30.5		16.8	
1640	34.2		18.4	
1750	36.4		19.3	
1800	38.4		20.1	
1900	39.7		20.5	
1950	40.5		20.9	
2000	41.1	41.26 (4.13)	21.1	20.52 (2.05)
2100	43.6		21.9	
2300	48.7		23.3	
2450	52.4		24	
2600	55.3		24.6	
3000	63.8		25.7	
3500	67.1		25	



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref. ACR.60.7.21.MVGB.A





SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref. ACR.60.7.21.MVGB.A

8 LIST OF EQUIPMENT

Equipment Summary Sheet				
Equipment Description	Manufacturer / Model	Identification No.	Current Calibration Date	Next Calibration Date
SAM Phantom	MVG	SN-13/09-SAM68	Validated. No cal required.	Validated. No cal required.
COMOSAR Test Bench	Version 3	NA	Validated. No cal required.	Validated. No cal required.
Network Analyzer	Rohde & Schwarz ZVM	100203	05/2019	05/2022
Network Analyzer – Calibration kit	Rohde & Schwarz ZV-Z235	101223	05/2019	05/2022
Calipers	Mitutoyo	SN 0009732	10/2019	10/2022
Reference Probe	MVG	EPGO333 SN 41/18	05/2020	05/2021
Multimeter	Keithley 2000	1160271	02/2020	02/2023
Signal Generator	Rohde & Schwarz SMB	106589	04/2019	04/2022
Amplifier	Aethercomm	SN 046	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.
Power Meter	NI-USB 5680	170100013	05/2019	05/2022
Directional Coupler	Narda 4216-20	01386	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.
Temperature / Humidity Sensor	Testo 184 H1	44220687	05/2020	05/2023



SAR Reference Dipole Calibration Report

Ref : ACR.60.11.21.MVGB.A

SHENZHEN NTEK TESTING TECHNOLOGY CO., LTD.

BUILDING E, FENDA SCIENCE PARK, SANWEI
COMMUNITY, XIXIANG STREET,
BAO'AN DISTRICT, SHENZHEN GUANGDONG, CHINA
MVG COMOSAR REFERENCE DIPOLE
FREQUENCY: 2300 MHZ
SERIAL NO.: SN 03/16 DIP2G300-358

Calibrated at MVG

Z.I. de la pointe du diable

Technopôle Brest Iroise – 295 avenue Alexis de Rochon
29280 PLOUZANE - FRANCE

Calibration date: 03/01/2021



Accreditations #2-6789 and #2-6814
Scope available on www.cofrac.fr

Summary:

This document presents the method and results from an accredited SAR reference dipole calibration performed at MVG, using the COMOSAR test bench. The test results covered by accreditation are traceable to the International System of Units (SI).



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.60.11.21.MVGB.A

	Name	Function	Date	Signature
Prepared by :	Jérôme LUC	Technical Manager	3/1/2021	
Checked by :	Jérôme LUC	Technical Manager	3/1/2021	
Approved by :	Yann Toutain	Laboratory Director	3/1/2021	

Mode d'emploi

2021.03.0
113:16:13
+01'00'

PHILIPS

	Customer Name
Distribution :	SHENZHEN NTEK TESTING TECHNOLOGY CO., LTD.

Issue	Name	Date	Modifications
A	Jérôme LE GALL	3/1/2021	Initial release



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref. ACR.60.11.21.MVGB.A

TABLE OF CONTENTS

1	Introduction	4
2	Device Under Test	4
3	Product Description	4
3.1	General Information	4
4	Measurement Method	5
4.1	Return Loss Requirements	5
4.2	Mechanical Requirements	5
5	Measurement Uncertainty	5
5.1	Return Loss	5
5.2	Dimension Measurement	5
5.3	Validation Measurement	5
6	Calibration Measurement Results	6
6.1	Return Loss and Impedance	6
6.2	Mechanical Dimensions	6
7	Validation measurement	7
7.1	Measurement Condition	7
7.2	Head Liquid Measurement	7
7.3	Measurement Result	8
8	List of Equipment	10



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.60.11.21.MVGB.A

1 INTRODUCTION

This document contains a summary of the requirements set forth by the IEEE 1528, FCC KDBs and CEI/IEC 62209 standards for reference dipoles used for SAR measurement system validations and the measurements that were performed to verify that the product complies with the fore mentioned standards.

2 DEVICE UNDER TEST

Device Under Test	
Device Type	COMOSAR 2300 MHz REFERENCE DIPOLE
Manufacturer	MVG
Model	SID2300
Serial Number	SN 03/15 DIP2G300-358
Product Condition (new / used)	Used

3 PRODUCT DESCRIPTION

3.1 GENERAL INFORMATION

MVG's COMOSAR Validation Dipoles are built in accordance to the IEEE 1528, FCC KDBs and CEI/IEC 62209 standards. The product is designed for use with the COMOSAR test bench only.



Figure 1 – MVG COMOSAR Validation Dipole

**SAR REFERENCE DIPOLE CALIBRATION REPORT**

Ref. ACR.60.11.21.MVGB.A

4 MEASUREMENT METHOD

The IEEE 1528, FCC KDBs and CEI/IEC 62209 standards provide requirements for reference dipoles used for system validation measurements. The following measurements were performed to verify that the product complies with the fore mentioned standards.

4.1 RETURN LOSS REQUIREMENTS

The dipole used for SAR system validation measurements and checks must have a return loss of -20 dB or better. The return loss measurement shall be performed against a liquid filled flat phantom, with the phantom constructed as outlined in the fore mentioned standards. A direct method is used with a network analyser and its calibration kit, both with a valid ISO17025 calibration.

4.2 MECHANICAL REQUIREMENTS

The IEEE Std. 1528 and CEI/IEC 62209 standards specify the mechanical components and dimensions of the validation dipoles, with the dimension's frequency and phantom shell thickness dependent. The COMOSAR test bench employs a 2 mm phantom shell thickness therefore the dipoles sold for use with the COMOSAR test bench comply with the requirements set forth for a 2 mm phantom shell thickness. A direct method is used with a ISO17025 calibrated caliper.

5 MEASUREMENT UNCERTAINTY

All uncertainties listed below represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$, traceable to the Internationally Accepted Guides to Measurement Uncertainty.

5.1 RETURN LOSS

The following uncertainties apply to the return loss measurement:

Frequency band	Expanded Uncertainty on Return Loss
400-6000MHz	0.08 LIN

5.2 DIMENSION MEASUREMENT

The following uncertainties apply to the dimension measurements:

Length (mm)	Expanded Uncertainty on Length
0 - 300	0.20 mm
300 - 450	0.44 mm

5.3 VALIDATION MEASUREMENT

The guidelines outlined in the IEEE 1528, FCC KDBs, CENELEC EN50361 and CEI/IEC 62209 standards were followed to generate the measurement uncertainty for validation measurements.

Scan Volume	Expanded Uncertainty




SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.60.11.21.MVGB.A

1 g	19 % (SAR)
10 g	19 % (SAR)

6 CALIBRATION MEASUREMENT RESULTS

6.1 RETURN LOSS AND IMPEDANCE



Frequency (MHz)	Return Loss (dB)	Requirement (dB)	Impedance
2300	-31.09	-20	$56.3 \Omega - 2.9 j\Omega$

6.2 MECHANICAL DIMENSIONS

Frequency MHz	L mm		h mm		d mm	
	required	measured	required	measured	required	measured
300	$420.0 \pm 1 \%$.		$250.0 \pm 1 \%$.		$6.35 \pm 1 \%$.	
450	$290.0 \pm 1 \%$.		$166.7 \pm 1 \%$.		$6.35 \pm 1 \%$.	
750	$176.0 \pm 1 \%$.		$100.0 \pm 1 \%$.		$6.35 \pm 1 \%$.	
835	$161.0 \pm 1 \%$.		$89.8 \pm 1 \%$.		$3.6 \pm 1 \%$.	
900	$149.0 \pm 1 \%$.		$83.3 \pm 1 \%$.		$3.6 \pm 1 \%$.	
1450	$89.1 \pm 1 \%$.		$51.7 \pm 1 \%$.		$3.6 \pm 1 \%$.	
1500	$80.5 \pm 1 \%$.		$50.0 \pm 1 \%$.		$3.6 \pm 1 \%$.	
1640	$79.0 \pm 1 \%$.		$45.7 \pm 1 \%$.		$3.6 \pm 1 \%$.	
1750	$75.2 \pm 1 \%$.		$42.9 \pm 1 \%$.		$3.6 \pm 1 \%$.	
1800	$72.0 \pm 1 \%$.		$41.7 \pm 1 \%$.		$3.6 \pm 1 \%$.	
1900	$68.0 \pm 1 \%$.		$39.5 \pm 1 \%$.		$3.6 \pm 1 \%$.	
1950	$66.3 \pm 1 \%$.		$38.5 \pm 1 \%$.		$3.6 \pm 1 \%$.	
2000	$64.5 \pm 1 \%$.		$37.5 \pm 1 \%$.		$3.6 \pm 1 \%$.	
2100	$61.0 \pm 1 \%$.		$35.7 \pm 1 \%$.		$3.6 \pm 1 \%$.	
2300	$55.5 \pm 1 \%$.	-	$32.6 \pm 1 \%$.	-	$3.6 \pm 1 \%$.	-
2450	$51.5 \pm 1 \%$.		$30.4 \pm 1 \%$.		$3.6 \pm 1 \%$.	

Page: 6/10

Template_ACR.DDD.N.YY.MVGB.ISSUE_SAR Reference Dipole vG

This document shall not be reproduced, except in full or in part, without the written approval of MVG. The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.60.11.21.MVGB.A

2600	$48.5 \pm 1\%$.		$28.8 \pm 1\%$.		$3.6 \pm 1\%$.	
3000	$41.5 \pm 1\%$.		$25.0 \pm 1\%$.		$3.6 \pm 1\%$.	
3500	$37.0 \pm 1\%$.		$26.4 \pm 1\%$.		$3.6 \pm 1\%$.	
3700	$34.7 \pm 1\%$.		$26.4 \pm 1\%$.		$3.6 \pm 1\%$.	

7 VALIDATION MEASUREMENT

The IEEE Std. 1528, FCC KDBs and CEI/IEC 62209 standards state that the system validation measurements must be performed using a reference dipole meeting the fore mentioned return loss and mechanical dimension requirements. The validation measurement must be performed against a liquid filled flat phantom, with the phantom constructed as outlined in the fore mentioned standards. Per the standards, the dipole shall be positioned below the bottom of the phantom, with the dipole length centered and parallel to the longest dimension of the flat phantom, with the top surface of the dipole at the described distance from the bottom surface of the phantom.

7.1 MEASUREMENT CONDITION

Software	OPENSAR V5
Phantom	SN 13/09 SAM68
Probe	SN 41/18 EPGO333
Liquid	Head Liquid Values: $\epsilon_r' : 42.0$ sigma : 1.80
Distance between dipole center and liquid	10.0 mm
Area scan resolution	$dx=8mm/dy=8mm$
Zoon Scan Resolution	$dx=5mm/dy=5mm/dz=5mm$
Frequency	23002300 MHz
Input power	20 dBm
Liquid Temperature	20 +/- 1 °C
Lab Temperature	20 +/- 1 °C
Lab Humidity	30-70 %

7.2 HEAD LIQUID MEASUREMENT

Frequency MHz	Relative permittivity (ϵ_r')		Conductivity (σ) S/m	
	required	measured	required	measured
300	$45.3 \pm 10\%$		$0.87 \pm 10\%$	
450	$43.5 \pm 10\%$		$0.87 \pm 10\%$	
750	$41.9 \pm 10\%$		$0.89 \pm 10\%$	
835	$41.5 \pm 10\%$		$0.90 \pm 10\%$	
900	$41.5 \pm 10\%$		$0.97 \pm 10\%$	
1450	$40.5 \pm 10\%$		$1.20 \pm 10\%$	
1500	$40.4 \pm 10\%$		$1.23 \pm 10\%$	
1640	$40.2 \pm 10\%$		$1.31 \pm 10\%$	
1750	$40.1 \pm 10\%$		$1.37 \pm 10\%$	
1800	$40.0 \pm 10\%$		$1.40 \pm 10\%$	
1900	$40.0 \pm 10\%$		$1.40 \pm 10\%$	
1950	$40.0 \pm 10\%$		$1.40 \pm 10\%$	
2000	$40.0 \pm 10\%$		$1.40 \pm 10\%$	



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.60.11.21.MVGB.A

2100	39.8 ±10 %		1.49 ±10 %	
2300	39.5 ±10 %	42.2	1.67 ±10 %	1.75
2450	39.2 ±10 %		1.80 ±10 %	
2600	39.0 ±10 %		1.96 ±10 %	
3000	38.5 ±10 %		2.40 ±10 %	
3500	37.9 ±10 %		2.91 ±10 %	

7.3 MEASUREMENT RESULT


The IEEE Std. 1528 and CEI/IEC 62209 standards state that the system validation measurements should produce the SAR values shown below (for phantom thickness of 2 mm), within the uncertainty for the system validation. All SAR values are normalized to 1 W forward power. In bracket, the measured SAR is given with the used input power.

Frequency MHz	1 g SAR (W/kg/W)		10 g SAR (W/kg/W)	
	required	measured	required	measured
300	2.85		1.94	
450	4.58		3.06	
750	8.49		5.55	
835	9.56		6.22	
900	10.9		6.99	
1450	29		16	
1500	30.5		16.8	
1640	34.2		18.4	
1750	36.4		19.3	
1800	38.4		20.1	
1900	39.7		20.5	
1950	40.5		20.9	
2000	41.1		21.1	
2100	43.6		21.9	
2300	48.7	50.65 (5.07)	23.3	23.55 (2.36)
2450	52.4		24	
2600	55.3		24.6	
3000	63.8		25.7	
3500	67.1		25	



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.60.11.21.MVGB.A





SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.60.11.21.MVGB.A

8 LIST OF EQUIPMENT

Equipment Summary Sheet				
Equipment Description	Manufacturer / Model	Identification No.	Current Calibration Date	Next Calibration Date
SAM Phantom	MVG	SN-13/09-SAM68	Validated. No cal required.	Validated. No cal required.
COMOSAR Test Bench	Version 3	NA	Validated. No cal required.	Validated. No cal required.
Network Analyzer	Rohde & Schwarz ZVM	100203	05/2019	05/2022
Network Analyzer – Calibration kit	Rohde & Schwarz ZV-Z235	101223	05/2019	05/2022
Calipers	Mitutoyo	SN 0009732	10/2019	10/2022
Reference Probe	MVG	EPGO333 SN 41/18	05/2020	05/2021
Multimeter	Keithley 2000	1160271	02/2020	02/2023
Signal Generator	Rohde & Schwarz SMB	106589	04/2019	04/2022
Amplifier	Aethercomm	SN 046	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.
Power Meter	NI-USB 5680	170100013	05/2019	05/2022
Directional Coupler	Narda 4216-20	01386	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.
Temperature / Humidity Sensor	Testo 184 H1	44220687	05/2020	05/2023



SAR Reference Dipole Calibration Report

Ref : ACR.60.8.21.MVGB.A

SHENZHEN NTEK TESTING TECHNOLOGY CO., LTD.

BUILDING E, FENDA SCIENCE PARK, SANWEI COMMUNITY, XIXIANG STREET,
BAO'AN DISTRICT, SHENZHEN GUANGDONG, CHINA

MVG COMOSAR REFERENCE DIPOLE

FREQUENCY: 2450 MHZ

SERIAL NO.: SN 03/15 DIP2G450-352

Calibrated at MVG

Z.I. de la pointe du diable

Technopôle Brest Iroise – 295 avenue Alexis de Rochon
29280 PLOUZANE - FRANCE

Calibration date: 03/01/2021



Accreditations #2-6789 and #2-6814
Scope available on www.cofrac.fr

Summary:

This document presents the method and results from an accredited SAR reference dipole calibration performed at MVG, using the COMOSAR test bench. The test results covered by accreditation are traceable to the International System of Units (SI).



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.60.8.21.MVGB.A

	Name	Function	Date	Signature
Prepared by :	Jérôme LUC	Technical Manager	3/1/2021	
Checked by :	Jérôme LUC	Technical Manager	3/1/2021	
Approved by :	Yann Toutain	Laboratory Director	3/1/2021	

2021.03.01

13:13:40

+01'00'

	Customer Name
Distribution :	SHENZHEN NTEK TESTING TECHNOLOGY CO., LTD.

Issue	Name	Date	Modifications
A	Jérôme LE GALL	3/1/2021	Initial release



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref. ACR.60.8.21.MVGB.A

TABLE OF CONTENTS

1	Introduction.....	4
2	Device Under Test	4
3	Product Description	4
3.1	General Information	4
4	Measurement Method	5
4.1	Return Loss Requirements	5
4.2	Mechanical Requirements	5
5	Measurement Uncertainty.....	5
5.1	Return Loss	5
5.2	Dimension Measurement	5
5.3	Validation Measurement	5
6	Calibration Measurement Results	6
6.1	Return Loss and Impedance	6
6.2	Mechanical Dimensions	6
7	Validation measurement	7
7.1	Measurement Condition	7
7.2	Head Liquid Measurement	7
7.3	Measurement Result	8
8	List of Equipment	10



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.60.8.21.MVGB.A

1 INTRODUCTION

This document contains a summary of the requirements set forth by the IEEE 1528, FCC KDBs and CEI/IEC 62209 standards for reference dipoles used for SAR measurement system validations and the measurements that were performed to verify that the product complies with the fore mentioned standards.

2 DEVICE UNDER TEST

Device Under Test	
Device Type	COMOSAR 2450 MHz REFERENCE DIPOLE
Manufacturer	MVG
Model	SID2450
Serial Number	SN 03/15 DIP2G450-352
Product Condition (new / used)	Used

3 PRODUCT DESCRIPTION

3.1 GENERAL INFORMATION

MVG's COMOSAR Validation Dipoles are built in accordance to the IEEE 1528, FCC KDBs and CEI/IEC 62209 standards. The product is designed for use with the COMOSAR test bench only.



Figure 1 – MVG COMOSAR Validation Dipole



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.60.8.21.MVGB.A

4 MEASUREMENT METHOD

The IEEE 1528, FCC KDBs and CEI/IEC 62209 standards provide requirements for reference dipoles used for system validation measurements. The following measurements were performed to verify that the product complies with the fore mentioned standards.

4.1 RETURN LOSS REQUIREMENTS

The dipole used for SAR system validation measurements and checks must have a return loss of -20 dB or better. The return loss measurement shall be performed against a liquid filled flat phantom, with the phantom constructed as outlined in the fore mentioned standards. A direct method is used with a network analyser and its calibration kit, both with a valid ISO17025 calibration.

4.2 MECHANICAL REQUIREMENTS

The IEEE Std. 1528 and CEI/IEC 62209 standards specify the mechanical components and dimensions of the validation dipoles, with the dimension's frequency and phantom shell thickness dependent. The COMOSAR test bench employs a 2 mm phantom shell thickness therefore the dipoles sold for use with the COMOSAR test bench comply with the requirements set forth for a 2 mm phantom shell thickness. A direct method is used with a ISO17025 calibrated caliper.

5 MEASUREMENT UNCERTAINTY

All uncertainties listed below represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2, traceable to the Internationally Accepted Guides to Measurement Uncertainty.

5.1 RETURN LOSS

The following uncertainties apply to the return loss measurement:

Frequency band	Expanded Uncertainty on Return Loss
400-6000MHz	0.08 LIN

5.2 DIMENSION MEASUREMENT

The following uncertainties apply to the dimension measurements:

Length (mm)	Expanded Uncertainty on Length
0 - 300	0.20 mm
300 - 450	0.44 mm

5.3 VALIDATION MEASUREMENT

The guidelines outlined in the IEEE 1528, FCC KDBs, CENELEC EN50361 and CEI/IEC 62209 standards were followed to generate the measurement uncertainty for validation measurements.

Scan Volume	Expanded Uncertainty




SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.60.8.21.MVGB.A

1 g	19 % (SAR)
10 g	19 % (SAR)

6 CALIBRATION MEASUREMENT RESULTS

6.1 RETURN LOSS AND IMPEDANCE



Frequency (MHz)	Return Loss (dB)	Requirement (dB)	Impedance
2450	-23.18	-20	56.3 Ω - 2.9 jΩ

6.2 MECHANICAL DIMENSIONS

Frequency MHz	L mm		h mm		d mm	
	required	measured	required	measured	required	measured
300	420.0 ±1 %.		250.0 ±1 %.		6.35 ±1 %.	
450	290.0 ±1 %.		166.7 ±1 %.		6.35 ±1 %.	
750	176.0 ±1 %.		100.0 ±1 %.		6.35 ±1 %.	
835	161.0 ±1 %.		89.8 ±1 %.		3.6 ±1 %.	
900	149.0 ±1 %.		83.3 ±1 %.		3.6 ±1 %.	
1450	89.1 ±1 %.		51.7 ±1 %.		3.6 ±1 %.	
1500	80.5 ±1 %.		50.0 ±1 %.		3.6 ±1 %.	
1640	79.0 ±1 %.		45.7 ±1 %.		3.6 ±1 %.	
1750	75.2 ±1 %.		42.9 ±1 %.		3.6 ±1 %.	
1800	72.0 ±1 %.		41.7 ±1 %.		3.6 ±1 %.	
1900	68.0 ±1 %.		39.5 ±1 %.		3.6 ±1 %.	
1950	66.3 ±1 %.		38.5 ±1 %.		3.6 ±1 %.	
2000	64.5 ±1 %.		37.5 ±1 %.		3.6 ±1 %.	
2100	61.0 ±1 %.		35.7 ±1 %.		3.6 ±1 %.	
2300	55.5 ±1 %.		32.6 ±1 %.		3.6 ±1 %.	
2450	51.5 ±1 %.	-	30.4 ±1 %.	-	3.6 ±1 %.	-

Page: 6/10

Template_ACR.DDD.N.YY.MVGB.ISSUE_SAR Reference Dipole vG

This document shall not be reproduced, except in full or in part, without the written approval of MVG. The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.60.8.21.MVGB.A

2600	48.5 ±1 %.		28.8 ±1 %.		3.6 ±1 %.	
3000	41.5 ±1 %.		25.0 ±1 %.		3.6 ±1 %.	
3500	37.0 ±1 %.		26.4 ±1 %.		3.6 ±1 %.	
3700	34.7 ±1 %.		26.4 ±1 %.		3.6 ±1 %.	

7 VALIDATION MEASUREMENT

The IEEE Std. 1528, FCC KDBs and CEI/IEC 62209 standards state that the system validation measurements must be performed using a reference dipole meeting the fore mentioned return loss and mechanical dimension requirements. The validation measurement must be performed against a liquid filled flat phantom, with the phantom constructed as outlined in the fore mentioned standards. Per the standards, the dipole shall be positioned below the bottom of the phantom, with the dipole length centered and parallel to the longest dimension of the flat phantom, with the top surface of the dipole at the described distance from the bottom surface of the phantom.

7.1 MEASUREMENT CONDITION

Software	OPENSAR V5
Phantom	SN 13/09 SAM68
Probe	SN 41/18 EPGO333
Liquid	Head Liquid Values: ϵ_r' : 41.9 sigma : 1.88
Distance between dipole center and liquid	10.0 mm
Area scan resolution	dx=8mm/dy=8mm
Zoon Scan Resolution	dx=5mm/dy=5mm/dz=5mm
Frequency	24502450 MHz
Input power	20 dBm
Liquid Temperature	20 +/- 1 °C
Lab Temperature	20 +/- 1 °C
Lab Humidity	30-70 %

7.2 HEAD LIQUID MEASUREMENT

Frequency MHz	Relative permittivity (ϵ_r')		Conductivity (σ) S/m	
	required	measured	required	measured
300	45.3 ±10 %		0.87 ±10 %	
450	43.5 ±10 %		0.87 ±10 %	
750	41.9 ±10 %		0.89 ±10 %	
835	41.5 ±10 %		0.90 ±10 %	
900	41.5 ±10 %		0.97 ±10 %	
1450	40.5 ±10 %		1.20 ±10 %	
1500	40.4 ±10 %		1.23 ±10 %	
1640	40.2 ±10 %		1.31 ±10 %	
1750	40.1 ±10 %		1.37 ±10 %	
1800	40.0 ±10 %		1.40 ±10 %	
1900	40.0 ±10 %		1.40 ±10 %	
1950	40.0 ±10 %		1.40 ±10 %	
2000	40.0 ±10 %		1.40 ±10 %	

Page: 7/10

Template_ACR.DDD.N.YY.MVGB.ISSUE_SAR Reference Dipole vG

This document shall not be reproduced, except in full or in part, without the written approval of MVG. The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.60.8.21.MVGB.A

2100	39.8 ±10 %		1.49 ±10 %	
2300	39.5 ±10 %		1.67 ±10 %	
2450	39.2 ±10 %	41.9	1.80 ±10 %	1.88
2600	39.0 ±10 %		1.96 ±10 %	
3000	38.5 ±10 %		2.40 ±10 %	
3500	37.9 ±10 %		2.91 ±10 %	

7.3 MEASUREMENT RESULT


The IEEE Std. 1528 and CEI/IEC 62209 standards state that the system validation measurements should produce the SAR values shown below (for phantom thickness of 2 mm), within the uncertainty for the system validation. All SAR values are normalized to 1 W forward power. In bracket, the measured SAR is given with the used input power.

Frequency MHz	1 g SAR (W/kg/W)		10 g SAR (W/kg/W)	
	required	measured	required	measured
300	2.85		1.94	
450	4.58		3.06	
750	8.49		5.55	
835	9.56		6.22	
900	10.9		6.99	
1450	29		16	
1500	30.5		16.8	
1640	34.2		18.4	
1750	36.4		19.3	
1800	38.4		20.1	
1900	39.7		20.5	
1950	40.5		20.9	
2000	41.1		21.1	
2100	43.6		21.9	
2300	48.7		23.3	
2450	52.4	53.69 (5.37)	24	23.94 (2.39)
2600	55.3		24.6	
3000	63.8		25.7	
3500	67.1		25	



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref. ACR.60.8.21.MVGB.A





SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.60.8.21.MVGB.A

8 LIST OF EQUIPMENT

Equipment Summary Sheet

Equipment Description	Manufacturer / Model	Identification No.	Current Calibration Date	Next Calibration Date
SAM Phantom	MVG	SN-13/09-SAM68	Validated. No cal required.	Validated. No cal required.
COMOSAR Test Bench	Version 3	NA	Validated. No cal required.	Validated. No cal required.
Network Analyzer	Rohde & Schwarz ZVM	100203	05/2019	05/2022
Network Analyzer – Calibration kit	Rohde & Schwarz ZV-Z235	101223	05/2019	05/2022
Calipers	Mitutoyo	SN 0009732	10/2019	10/2022
Reference Probe	MVG	EPGO333 SN 41/18	05/2020	05/2021
Multimeter	Keithley 2000	1160271	02/2020	02/2023
Signal Generator	Rohde & Schwarz SMB	106589	04/2019	04/2022
Amplifier	Aethercomm	SN 046	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.
Power Meter	NI-USB 5680	170100013	05/2019	05/2022
Directional Coupler	Narda 4216-20	01386	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.
Temperature / Humidity Sensor	Testo 184 H1	44220687	05/2020	05/2023



SAR Reference Dipole Calibration Report

Ref : ACR.60.9.21.MVGB.A

SHENZHEN NTEK TESTING TECHNOLOGY CO., LTD.

BUILDING E, FENDA SCIENCE PARK, SANWEI COMMUNITY, XIXIANG STREET,
BAO'AN DISTRICT, SHENZHEN GUANGDONG, CHINA

MVG COMOSAR REFERENCE DIPOLE

FREQUENCY: 2600 MHZ

SERIAL NO.: SN 03/15 DIP2G600-356

Calibrated at MVG

Z.I. de la pointe du diable

Technopôle Brest Iroise – 295 avenue Alexis de Rochon
29280 PLOUZANE - FRANCE

Calibration date: 03/01/2021



Accreditations #2-6789 and #2-6814
Scope available on www.cofrac.fr


Summary:

This document presents the method and results from an accredited SAR reference dipole calibration performed at MVG, using the COMOSAR test bench. The test results covered by accreditation are traceable to the International System of Units (SI).



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref. ACR.60.9.21.MVGB.A

	Name	Function	Date	Signature
Prepared by :	Jérôme Luc	Technical Manager	3/1/2021	
Checked by :	Jérôme Luc	Technical Manager	3/1/2021	
Approved by :	Yann Toutain	Laboratory Director	3/1/2021	

2021.03.01
13:14:51
+01'00'

	Customer Name
Distribution :	SHENZHEN NTEK TESTING TECHNOLOGY CO., LTD.

Issue	Name	Date	Modifications
A	Jérôme Luc	3/1/2021	Initial release



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref. ACR.60.9.21.MVGB.A

TABLE OF CONTENTS

1	Introduction.....	4
2	Device Under Test	4
3	Product Description	4
3.1	General Information	4
4	Measurement Method	5
4.1	Return Loss Requirements	5
4.2	Mechanical Requirements	5
5	Measurement Uncertainty.....	5
5.1	Return Loss	5
5.2	Dimension Measurement	5
5.3	Validation Measurement	5
6	Calibration Measurement Results	6
6.1	Return Loss and Impedance	6
6.2	Mechanical Dimensions	6
7	Validation measurement	7
7.1	Measurement Condition	7
7.2	Head Liquid Measurement	7
7.3	Measurement Result	8
8	List of Equipment	10



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref. ACR.60.9.21.MVGB.A

1 INTRODUCTION

This document contains a summary of the requirements set forth by the IEEE 1528, FCC KDBs and CEI/IEC 62209 standards for reference dipoles used for SAR measurement system validations and the measurements that were performed to verify that the product complies with the fore mentioned standards.

2 DEVICE UNDER TEST

Device Under Test	
Device Type	COMOSAR 2600 MHz REFERENCE DIPOLE
Manufacturer	MVG
Model	SID2600
Serial Number	SN 03/15 DIP2G600-356
Product Condition (new / used)	Used

3 PRODUCT DESCRIPTION

3.1 GENERAL INFORMATION

MVG's COMOSAR Validation Dipoles are built in accordance to the IEEE 1528, FCC KDBs and CEI/IEC 62209 standards. The product is designed for use with the COMOSAR test bench only.



Figure 1 – MVG COMOSAR Validation Dipole



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref. ACR.60.9.21.MVGB.A

4 MEASUREMENT METHOD

The IEEE 1528, FCC KDBs and CEI/IEC 62209 standards provide requirements for reference dipoles used for system validation measurements. The following measurements were performed to verify that the product complies with the fore mentioned standards.

4.1 RETURN LOSS REQUIREMENTS

The dipole used for SAR system validation measurements and checks must have a return loss of -20 dB or better. The return loss measurement shall be performed against a liquid filled flat phantom, with the phantom constructed as outlined in the fore mentioned standards. A direct method is used with a network analyser and its calibration kit, both with a valid ISO17025 calibration.

4.2 MECHANICAL REQUIREMENTS

The IEEE Std. 1528 and CEI/IEC 62209 standards specify the mechanical components and dimensions of the validation dipoles, with the dimension's frequency and phantom shell thickness dependent. The COMOSAR test bench employs a 2 mm phantom shell thickness therefore the dipoles sold for use with the COMOSAR test bench comply with the requirements set forth for a 2 mm phantom shell thickness. A direct method is used with a ISO17025 calibrated caliper.

5 MEASUREMENT UNCERTAINTY

All uncertainties listed below represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2, traceable to the Internationally Accepted Guides to Measurement Uncertainty.

5.1 RETURN LOSS

The following uncertainties apply to the return loss measurement:

Frequency band	Expanded Uncertainty on Return Loss
400-6000MHz	0.08 LIN

5.2 DIMENSION MEASUREMENT

The following uncertainties apply to the dimension measurements:

Length (mm)	Expanded Uncertainty on Length
0 - 300	0.20 mm
300 - 450	0.44 mm

5.3 VALIDATION MEASUREMENT

The guidelines outlined in the IEEE 1528, FCC KDBs, CENELEC EN50361 and CEI/IEC 62209 standards were followed to generate the measurement uncertainty for validation measurements.

Scan Volume	Expanded Uncertainty




SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.60.9.21.MVGB.A

1 g	19 % (SAR)
10 g	19 % (SAR)

6 CALIBRATION MEASUREMENT RESULTS

6.1 RETURN LOSS AND IMPEDANCE



Frequency (MHz)	Return Loss (dB)	Requirement (dB)	Impedance
2600	-21.15	-20	52.7 Ω - 8.3 jΩ

6.2 MECHANICAL DIMENSIONS

Frequency MHz	L mm		h mm		d mm	
	required	measured	required	measured	required	measured
300	420.0 ±1 %.		250.0 ±1 %.		6.35 ±1 %.	
450	290.0 ±1 %.		166.7 ±1 %.		6.35 ±1 %.	
750	176.0 ±1 %.		100.0 ±1 %.		6.35 ±1 %.	
835	161.0 ±1 %.		89.8 ±1 %.		3.6 ±1 %.	
900	149.0 ±1 %.		83.3 ±1 %.		3.6 ±1 %.	
1450	89.1 ±1 %.		51.7 ±1 %.		3.6 ±1 %.	
1500	80.5 ±1 %.		50.0 ±1 %.		3.6 ±1 %.	
1640	79.0 ±1 %.		45.7 ±1 %.		3.6 ±1 %.	
1750	75.2 ±1 %.		42.9 ±1 %.		3.6 ±1 %.	
1800	72.0 ±1 %.		41.7 ±1 %.		3.6 ±1 %.	
1900	68.0 ±1 %.		39.5 ±1 %.		3.6 ±1 %.	
1950	66.3 ±1 %.		38.5 ±1 %.		3.6 ±1 %.	
2000	64.5 ±1 %.		37.5 ±1 %.		3.6 ±1 %.	
2100	61.0 ±1 %.		35.7 ±1 %.		3.6 ±1 %.	
2300	55.5 ±1 %.		32.6 ±1 %.		3.6 ±1 %.	
2450	51.5 ±1 %.		30.4 ±1 %.		3.6 ±1 %.	

Page: 6/10

Template_ACR.DDD.N.YY.MVGB.ISSUE_SAR Reference Dipole vG

This document shall not be reproduced, except in full or in part, without the written approval of MVG. The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.60.9.21.MVGB.A

2600	48.5 ±1 %.	-	28.8 ±1 %.	-	3.6 ±1 %.	-
3000	41.5 ±1 %.		25.0 ±1 %.		3.6 ±1 %.	
3500	37.0 ±1 %.		26.4 ±1 %.		3.6 ±1 %.	
3700	34.7 ±1 %.		26.4 ±1 %.		3.6 ±1 %.	

7 VALIDATION MEASUREMENT

The IEEE Std. 1528, FCC KDBs and CEI/IEC 62209 standards state that the system validation measurements must be performed using a reference dipole meeting the fore mentioned return loss and mechanical dimension requirements. The validation measurement must be performed against a liquid filled flat phantom, with the phantom constructed as outlined in the fore mentioned standards. Per the standards, the dipole shall be positioned below the bottom of the phantom, with the dipole length centered and parallel to the longest dimension of the flat phantom, with the top surface of the dipole at the described distance from the bottom surface of the phantom.

7.1 MEASUREMENT CONDITION

Software	OPENSAR V5
Phantom	SN 13/09 SAM68
Probe	SN 41/18 EPGO333
Liquid	Head Liquid Values: ϵ_s' : 41.5 sigma : 2.03
Distance between dipole center and liquid	10.0 mm
Area scan resolution	$dx=8mm/dy=8mm$
Zoon Scan Resolution	$dx=5mm/dy=5mm/dz=5mm$
Frequency	2600MHz
Input power	20 dBm
Liquid Temperature	20 +/- 1 °C
Lab Temperature	20 +/- 1 °C
Lab Humidity	30-70 %

7.2 HEAD LIQUID MEASUREMENT

Frequency MHz	Relative permittivity (ϵ_s')		Conductivity (σ) S/m	
	required	measured	required	measured
300	45.3 ±10 %		0.87 ±10 %	
450	43.5 ±10 %		0.87 ±10 %	
750	41.9 ±10 %		0.89 ±10 %	
835	41.5 ±10 %		0.90 ±10 %	
900	41.5 ±10 %		0.97 ±10 %	
1450	40.5 ±10 %		1.20 ±10 %	
1500	40.4 ±10 %		1.23 ±10 %	
1640	40.2 ±10 %		1.31 ±10 %	
1750	40.1 ±10 %		1.37 ±10 %	
1800	40.0 ±10 %		1.40 ±10 %	
1900	40.0 ±10 %		1.40 ±10 %	
1950	40.0 ±10 %		1.40 ±10 %	
2000	40.0 ±10 %		1.40 ±10 %	

Page: 7/10

Template_ACR.DDD.N.YY.MVGB.ISSUE_SAR Reference Dipole vG

This document shall not be reproduced, except in full or in part, without the written approval of MVG. The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.60.9.21.MVGB.A

2100	$39.8 \pm 10\%$		$1.49 \pm 10\%$	
2300	$39.5 \pm 10\%$		$1.67 \pm 10\%$	
2450	$39.2 \pm 10\%$		$1.80 \pm 10\%$	
2600	$39.0 \pm 10\%$	41.5	$1.96 \pm 10\%$	2.03
3000	$38.5 \pm 10\%$		$2.40 \pm 10\%$	
3500	$37.9 \pm 10\%$		$2.91 \pm 10\%$	

7.3 MEASUREMENT RESULT


The IEEE Std. 1528 and CEI/IEC 62209 standards state that the system validation measurements should produce the SAR values shown below (for phantom thickness of 2 mm), within the uncertainty for the system validation. All SAR values are normalized to 1 W forward power. In bracket, the measured SAR is given with the used input power.

Frequency MHz	1 g SAR (W/kg/W)		10 g SAR (W/kg/W)	
	required	measured	required	measured
300	2.85		1.94	
450	4.58		3.06	
750	8.49		5.55	
835	9.56		6.22	
900	10.9		6.99	
1450	29		16	
1500	30.5		16.8	
1640	34.2		18.4	
1750	36.4		19.3	
1800	38.4		20.1	
1900	39.7		20.5	
1950	40.5		20.9	
2000	41.1		21.1	
2100	43.6		21.9	
2300	48.7		23.3	
2450	52.4		24	
2600	55.3	55.83 (5.58)	24.6	24.19 (2.42)
3000	63.8		25.7	
3500	67.1		25	



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref. ACR.60.9.21.MVGB.A





SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.60.9.21.MVGB.A

8 LIST OF EQUIPMENT

Equipment Summary Sheet				
Equipment Description	Manufacturer / Model	Identification No.	Current Calibration Date	Next Calibration Date
SAM Phantom	MVG	SN-13/09-SAM68	Validated. No cal required.	Validated. No cal required.
COMOSAR Test Bench	Version 3	NA	Validated. No cal required.	Validated. No cal required.
Network Analyzer	Rohde & Schwarz ZVM	100203	05/2019	05/2022
Network Analyzer – Calibration kit	Rohde & Schwarz ZV-Z235	101223	05/2019	05/2022
Calipers	Mitutoyo	SN 0009732	10/2019	10/2022
Reference Probe	MVG	EPMG0333 SN 41/18	05/2020	05/2021
Multimeter	Keithley 2000	1160271	02/2020	02/2023
Signal Generator	Rohde & Schwarz SMB	106589	04/2019	04/2022
Amplifier	Aethercomm	SN 046	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.
Power Meter	NI-USB 5680	170100013	05/2019	05/2022
Directional Coupler	Narda 4216-20	01386	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.
Temperature / Humidity Sensor	Testo 184 H1	44220687	05/2020	05/2023



SAR Reference Dipole Calibration Report

Ref : ACR.139.16.20.SATU.A

SHENZHEN NTEK TESTING TECHNOLOGY CO., LTD.

**BUILDING E, FENDA SCIENCE PARK, SANWEI
COMMUNITY, XIXIANG STREET,
BAO'AN DISTRICT, SHENZHEN GUANGDONG, CHINA**

MVG COMOSAR REFERENCE DIPOLE

FREQUENCY: 3700 MHZ

SERIAL NO.: SN 09/12 DIP 3G700-361

Calibrated at MVG US

2105 Barrett Park Dr. - Kennesaw, GA 30144



10/19/2020

Summary:

This document presents the method and results from an accredited SAR reference dipole calibration performed in MVG USA using the COMOSAR test bench. All calibration results are traceable to national metrology institutions.



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.139.16.20.SATU.A

	Name	Function	Date	Signature
Prepared by :	Jérôme LUC	Product Manager	10/19/2020	
Checked by :	Jérôme LUC	Product Manager	10/19/2020	
Approved by :	Kim RUTKOWSKI	Quality Manager	10/19/2020	

Distribution :	Customer Name
	SHENZHEN NTEK TESTING TECHNOLOGY CO., LTD.

Issue	Date	Modifications
A	10/19/2020	Initial release

Page: 2/11

This document shall not be reproduced, except in full or in part, without the written approval of MVG.
The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.139.16.20.SATU.A

TABLE OF CONTENTS

1	Introduction.....	4
2	Device Under Test	4
3	Product Description	4
3.1	General Information	4
4	Measurement Method	5
4.1	Return Loss Requirements	5
4.2	Mechanical Requirements	5
5	Measurement Uncertainty.....	5
5.1	Return Loss	5
5.2	Dimension Measurement	5
5.3	Validation Measurement	5
6	Calibration Measurement Results.....	6
6.1	Return Loss and Impedance In Head Liquid	6
6.2	Return Loss and Impedance In Body Liquid	6
6.3	Mechanical Dimensions	6
7	Validation measurement	7
7.1	Head Liquid Measurement	7
7.2	SAR Measurement Result With Head Liquid.....	8
7.3	Body Liquid Measurement	9
7.4	SAR Measurement Result With Body Liquid	10
8	List of Equipment	11

Page: 3/11

This document shall not be reproduced, except in full or in part, without the written approval of MVG.
The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.139.16.20.SATU.A

1 INTRODUCTION

This document contains a summary of the requirements set forth by the IEEE 1528, FCC KDBs and CEI/IEC 62209 standards for reference dipoles used for SAR measurement system validations and the measurements that were performed to verify that the product complies with the fore mentioned standards.

2 DEVICE UNDER TEST

Device Under Test	
Device Type	COMOSAR 3700 MHz REFERENCE DIPOLE
Manufacturer	MVG
Model	SID3700
Serial Number	SN 09/12 DIP 3G700-361
Product Condition (new / used)	New

A yearly calibration interval is recommended.

3 PRODUCT DESCRIPTION**3.1 GENERAL INFORMATION**

MVG's COMOSAR Validation Dipoles are built in accordance to the IEEE 1528, FCC KDBs and CEI/IEC 62209 standards. The product is designed for use with the COMOSAR test bench only.



Figure 1 – MVG COMOSAR Validation Dipole



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.139.16.20.SATU.A

4 MEASUREMENT METHOD

The IEEE 1528, FCC KDBs and CEI/IEC 62209 standards provide requirements for reference dipoles used for system validation measurements. The following measurements were performed to verify that the product complies with the fore mentioned standards.

4.1 RETURN LOSS REQUIREMENTS

The dipole used for SAR system validation measurements and checks must have a return loss of -20 dB or better. The return loss measurement shall be performed against a liquid filled flat phantom, with the phantom constructed as outlined in the fore mentioned standards.

4.2 MECHANICAL REQUIREMENTS

The IEEE Std. 1528 and CEI/IEC 62209 standards specify the mechanical components and dimensions of the validation dipoles, with the dimensions frequency and phantom shell thickness dependent. The COMOSAR test bench employs a 2 mm phantom shell thickness therefore the dipoles sold for use with the COMOSAR test bench comply with the requirements set forth for a 2 mm phantom shell thickness.

5 MEASUREMENT UNCERTAINTY

All uncertainties listed below represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2, traceable to the Internationally Accepted Guides to Measurement Uncertainty.

5.1 RETURN LOSS

The following uncertainties apply to the return loss measurement:

Frequency band	Expanded Uncertainty on Return Loss
400-6000MHz	0.1 dB

5.2 DIMENSION MEASUREMENT

The following uncertainties apply to the dimension measurements:

Length (mm)	Expanded Uncertainty on Length
3 - 300	0.05 mm

5.3 VALIDATION MEASUREMENT

The guidelines outlined in the IEEE 1528, FCC KDBs, CENELEC EN50361 and CEI/IEC 62209 standards were followed to generate the measurement uncertainty for validation measurements.

Scan Volume	Expanded Uncertainty
1 g	20.3 %

Page: 5/11


*This document shall not be reproduced, except in full or in part, without the written approval of MVG.
The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.*




SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.139.16.20.SATU.A

10 g	20.1 %
------	--------

6 CALIBRATION MEASUREMENT RESULTS**6.1 RETURN LOSS AND IMPEDANCE IN HEAD LIQUID**

Frequency (MHz)	Return Loss (dB)	Requirement (dB)	Impedance
3700	-20.85	-20	54.9 Ω - 8.3 jΩ

6.2 RETURN LOSS AND IMPEDANCE IN BODY LIQUID

Frequency (MHz)	Return Loss (dB)	Requirement (dB)	Impedance
3700	-23.23	-20	50.6 Ω - 7.0 jΩ

6.3 MECHANICAL DIMENSIONS

Frequency MHz	L mm		h mm		d mm	
	required	measured	required	measured	required	measured
300	420.0 ±1 %.		250.0 ±1 %.		6.35 ±1 %.	

Page: 6/11

This document shall not be reproduced, except in full or in part, without the written approval of MVG.
The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.139.16.20.SATU.A

450	290.0 ±1 %.		166.7 ±1 %.		6.35 ±1 %.	
750	176.0 ±1 %.		100.0 ±1 %.		6.35 ±1 %.	
835	161.0 ±1 %.		89.8 ±1 %.		3.6 ±1 %.	
900	149.0 ±1 %.		83.3 ±1 %.		3.6 ±1 %.	
1450	89.1 ±1 %.		51.7 ±1 %.		3.6 ±1 %.	
1500	80.5 ±1 %.		50.0 ±1 %.		3.6 ±1 %.	
1640	79.0 ±1 %.		45.7 ±1 %.		3.6 ±1 %.	
1750	75.2 ±1 %.		42.9 ±1 %.		3.6 ±1 %.	
1800	72.0 ±1 %.		41.7 ±1 %.		3.6 ±1 %.	
1900	68.0 ±1 %.		39.5 ±1 %.		3.6 ±1 %.	
1950	66.3 ±1 %.		38.5 ±1 %.		3.6 ±1 %.	
2000	64.5 ±1 %.		37.5 ±1 %.		3.6 ±1 %.	
2100	61.0 ±1 %.		35.7 ±1 %.		3.6 ±1 %.	
2300	55.5 ±1 %.		32.6 ±1 %.		3.6 ±1 %.	
2450	51.5 ±1 %.		30.4 ±1 %.		3.6 ±1 %.	
2600	48.5 ±1 %.		28.8 ±1 %.		3.6 ±1 %.	
3400	41.5 ±1 %.		25.0 ±1 %.		3.6 ±1 %.	
3600	37.0 ±1 %.		26.4 ±1 %.		3.6 ±1 %.	
3700	34.7 ±1 %.	PASS	26.4 ±1 %.	PASS	3.6 ±1 %.	PASS

7 VALIDATION MEASUREMENT

The IEEE Std. 1528, FCC KDBs and CEI/IEC 62209 standards state that the system validation measurements must be performed using a reference dipole meeting the fore mentioned return loss and mechanical dimension requirements. The validation measurement must be performed against a liquid filled flat phantom, with the phantom constructed as outlined in the fore mentioned standards. Per the standards, the dipole shall be positioned below the bottom of the phantom, with the dipole length centered and parallel to the longest dimension of the flat phantom, with the top surface of the dipole at the described distance from the bottom surface of the phantom.

7.1 HEAD LIQUID MEASUREMENT

Frequency MHz	Relative permittivity (ϵ_r')		Conductivity (σ) S/m	
	required	measured	required	measured
300	45.3 ±5 %		0.87 ±5 %	
450	43.5 ±5 %		0.87 ±5 %	
750	41.9 ±5 %		0.89 ±5 %	
835	41.5 ±5 %		0.90 ±5 %	
900	41.5 ±5 %		0.97 ±5 %	
1450	40.5 ±5 %		1.20 ±5 %	
1500	40.4 ±5 %		1.23 ±5 %	
1640	40.2 ±5 %		1.31 ±5 %	
1750	40.1 ±5 %		1.37 ±5 %	

Page: 7/11

This document shall not be reproduced, except in full or in part, without the written approval of MVG.
The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.139.16.20.SATU.A

1800	40.0 ±5 %		1.40 ±5 %	
1900	40.0 ±5 %		1.40 ±5 %	
1950	40.0 ±5 %		1.40 ±5 %	
2000	40.0 ±5 %		1.40 ±5 %	
2100	39.8 ±5 %		1.49 ±5 %	
2300	39.5 ±5 %		1.67 ±5 %	
2450	39.2 ±5 %		1.80 ±5 %	
3400	38.0 ±5 %		2.81 ±5 %	
3600	37.8 ±5 %		3.02 ±5 %	
3700	37.7 ±5 %	PASS	3.12 ±5 %	PASS

7.2 SAR MEASUREMENT RESULT WITH HEAD LIQUID

The IEEE Std. 1528 and CEI/IEC 62209 standards state that the system validation measurements should produce the SAR values shown below (for phantom thickness of 2 mm), within the uncertainty for the system validation. All SAR values are normalized to 1 W forward power. In bracket, the measured SAR is given with the used input power.

Software	OPENSAR V4
Phantom	SN 20/09 SAM71
Probe	SN 18/11 EPG122
Liquid	Head Liquid Values: $\epsilon\mu$: 37.8 sigma : 3.25
Distance between dipole center and liquid	10.0 mm
Area scan resolution	dx=8mm/dy=8mm
Zoon Scan Resolution	dx=5mm/dy=5mm/dz=5mm
Frequency	3700 MHz
Input power	20 dBm
Liquid Temperature	21 °C
Lab Temperature	21 °C
Lab Humidity	45 %

Frequency MHz	1 g SAR (W/kg/W)		10 g SAR (W/kg/W)	
	required	measured	required	measured
300	2.85		1.94	
450	4.58		3.06	
750	8.49		5.55	
835	9.56		6.22	
900	10.9		6.99	
1450	29		16	
1500	30.5		16.8	
1640	34.2		18.4	
1750	36.4		19.3	
1800	38.4		20.1	

Page: 8/11


This document shall not be reproduced, except in full or in part, without the written approval of MVG.
The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.139.16.20.SATU.A

1900	39.7		20.5	
1950	40.5		20.9	
2000	41.1		21.1	
2100	43.6		21.9	
2300	48.7		23.3	
2450	52.4		24	
2600	55.3		24.6	
3400	66.4		25.1	
3600	67.3		24.6	
3700	67.4	66.30 (6.63)	24.2	24.16 (2.42)



7.3 BODY LIQUID MEASUREMENT

Frequency MHz	Relative permittivity (ϵ_r')		Conductivity (σ) S/m	
	required	measured	required	measured
150	61.9 ±5 %		0.80 ±5 %	
300	58.2 ±5 %		0.92 ±5 %	
450	56.7 ±5 %		0.94 ±5 %	
750	55.5 ±5 %		0.96 ±5 %	
835	55.2 ±5 %		0.97 ±5 %	
900	55.0 ±5 %		1.05 ±5 %	
915	55.0 ±5 %		1.06 ±5 %	
1450	54.0 ±5 %		1.30 ±5 %	
1610	53.8 ±5 %		1.40 ±5 %	
1800	53.3 ±5 %		1.52 ±5 %	
1900	53.3 ±5 %		1.52 ±5 %	
2000	53.3 ±5 %		1.52 ±5 %	
2100	53.2 ±5 %		1.62 ±5 %	

Page: 9/11

This document shall not be reproduced, except in full or in part, without the written approval of MVG.
The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



SAR REFERENCE DIPOLE CALIBRATION REPORT


Ref: ACR.139.16.20.SATU.A

2300	52.9 ±5 %		1.81 ±5 %	
2450	52.7 ±5 %		1.95 ±5 %	
2600	52.5 ±5 %		2.16 ±5 %	
3400	51.5 ±5 %		3.20 ±5 %	
3600	51.2 ±5 %		3.43 ±5 %	
3700	51.1 ±5 %	PASS	3.55 ±5 %	PASS
5200	49.0 ±10 %		5.30 ±10 %	
5300	48.9 ±10 %		5.42 ±10 %	
5400	48.7 ±10 %		5.53 ±10 %	
5500	48.6 ±10 %		5.65 ±10 %	
5600	48.5 ±10 %		5.77 ±10 %	
5800	48.2 ±10 %		6.00 ±10 %	

7.4 SAR MEASUREMENT RESULT WITH BODY LIQUID

Software	OPENSAR V4
Phantom	SN 20/09 SAM71
Probe	SN 18/11 EPG122
Liquid	Body Liquid Values: ϵ_s : 51.3 sigma : 3.56
Distance between dipole center and liquid	10.0 mm
Area scan resolution	$dx=8mm/dy=8mm$
Zoon Scan Resolution	$dx=5mm/dy=5mm/dz=5mm$
Frequency	3700 MHz
Input power	20 dBm
Liquid Temperature	21 °C
Lab Temperature	21 °C
Lab Humidity	45 %

Frequency MHz	1 g SAR (W/kg/W)	10 g SAR (W/kg/W)
	measured	measured
3700	62.36 (6.24)	23.56 (2.35)



Page: 10/11

This document shall not be reproduced, except in full or in part, without the written approval of MVG.
The information contained herein is to be used only for the purpose for which it is submitted and is not to be released in whole or part without written approval of MVG.



SAR REFERENCE DIPOLE CALIBRATION REPORT

Ref: ACR.139.16.20.SATU.A

8 LIST OF EQUIPMENT

Equipment Summary Sheet				
Equipment Description	Manufacturer / Model	Identification No.	Current Calibration Date	Next Calibration Date
SAM Phantom	MVG	SN-20/09-SAM71	Validated. No cal required.	Validated. No cal required.
COMOSAR Test Bench	Version 3	NA	Validated. No cal required.	Validated. No cal required.
Network Analyzer	Rhode & Schwarz ZVA	SN100132	02/2020	02/2023
Calipers	Carrera	CALIPER-01	01/2020	01/2023
Reference Probe	MVG	EPG122 SN 18/11	09/2020	09/2021
Multimeter	Keithley 2000	1188656	01/2020	01/2023
Signal Generator	Agilent E4438C	MY49070581	01/2020	01/2023
Amplifier	Aethercomm	SN 046	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.
Power Meter	HP E4418A	US38261498	01/2020	01/2023
Power Sensor	HP ECP-E26A	US37181460	01/2020	01/2023
Directional Coupler	Narda 4216-20	01386	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.
Temperature and Humidity Sensor	Control Company	11-661-9	11/2017	11/2020



SAR Reference Waveguide Calibration Report

Ref : ACR.60.10.21.MVGB.A

SHENZHEN NTEK TESTING TECHNOLOGY CO., LTD.

BUILDING E, FENDA SCIENCE PARK, SANWEI
COMMUNITY, XIXIANG STREET,
BAO'AN DISTRICT, SHENZHEN GUANGDONG, CHINA
SATIMO COMOSAR REFERENCE WAVEGUIDE

FREQUENCY: 5000-6000 MHZ
SERIAL NO.: SN 13/14 WGA33

Calibrated at MVG

Z.I. de la pointe du diable

Technopôle Brest Iroise – 295 avenue Alexis de Rochon
29280 PLOUZANE - FRANCE

Calibration date: 03/01/2021



Accreditations #2-6789 and #2-6814
Scope available on www.cofrac.fr

Summary:

This document presents the method and results from an accredited SAR reference waveguide calibration performed at MVG, using the COMOSAR test bench. The test results covered by accreditation are traceable to the International System of Units (SI).



SAR REFERENCE WAVEGUIDE CALIBRATION REPORT

Ref: ACR.60.10.21.MVGB.A

	Name	Function	Date	Signature
Prepared by :	Jérôme Luc	Technical Manager	3/1/2021	
Checked by :	Jérôme Luc	Technical Manager	3/1/2021	
Approved by :	Yann Toutain	Laboratory Director	3/1/2021	

Mode d'emploi
2021.03.0
1 13:15:44
+01'00'
PHILIPS

	Customer Name
Distribution :	SHENZHEN NTEK TESTING TECHNOLOGY CO., LTD.

Issue	Name	Date	Modifications
A	Jérôme Luc	3/1/2021	Initial release



SAR REFERENCE WAVEGUIDE CALIBRATION REPORT

Ref. ACR.60.10.21.MVGB.A

TABLE OF CONTENTS

1	Introduction	4
2	Device Under Test	4
3	Product Description	4
3.1	General Information	4
4	Measurement Method	4
4.1	Return Loss Requirements	4
4.2	Mechanical Requirements	4
5	Measurement Uncertainty	5
5.1	Return Loss	5
5.2	Dimension Measurement	5
5.3	Validation Measurement	5
6	Calibration Measurement Results	5
6.1	Return Loss	5
6.2	Mechanical Dimensions	6
7	Validation measurement	6
7.1	Head Liquid Measurement	8
7.2	Measurement Result	8
8	List of Equipment	11

**SAR REFERENCE WAVEGUIDE CALIBRATION REPORT**

Ref. ACR.60.10.21.MVGB.A

1 INTRODUCTION

This document contains a summary of the requirements set forth by the IEEE 1528 and CEI/IEC 62209 standards for reference waveguides used for SAR measurement system validations and the measurements that were performed to verify that the product complies with the fore mentioned standards.

2 DEVICE UNDER TEST

Device Under Test	
Device Type	COMOSAR 5000-6000 MHz REFERENCE WAVEGUIDE
Manufacturer	MVG
Model	SWG5500
Serial Number	SN 13/14 WGA33
Product Condition (new / used)	Used

3 PRODUCT DESCRIPTION**3.1 GENERAL INFORMATION**

MVG's COMOSAR Validation Waveguides are built in accordance to the IEEE 1528 and CEI/IEC 62209 standards.

4 MEASUREMENT METHOD

The IEEE 1528 and CEI/IEC 62209 standards provide requirements for reference waveguides used for system validation measurements. The following measurements were performed to verify that the product complies with the fore mentioned standards.

4.1 RETURN LOSS REQUIREMENTS

The waveguide used for SAR system validation measurements and checks must have a return loss of -8 dB or better. The return loss measurement shall be performed with matching layer placed in the open end of the waveguide, with the waveguide and matching layer in direct contact with the phantom shell as outlined in the fore mentioned standards. A direct method is used with a network analyser and its calibration kit, both with a valid ISO17025 calibration.

4.2 MECHANICAL REQUIREMENTS

The IEEE 1528 and CEI/IEC 62209 standards specify the mechanical dimensions of the validation waveguide, the specified dimensions are as shown in Section 6.2. Figure 1 shows how the dimensions relate to the physical construction of the waveguide. A direct method is used with a ISO17025 calibrated caliper.



SAR REFERENCE WAVEGUIDE CALIBRATION REPORT

Ref: ACR.60.10.21.MVGB.A

5 MEASUREMENT UNCERTAINTY

All uncertainties listed below represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$, traceable to the Internationally Accepted Guides to Measurement Uncertainty.

5.1 RETURN LOSS

The following uncertainties apply to the return loss measurement:

Frequency band	Expanded Uncertainty on Return Loss
400-6000MHz	0.08 LIN

5.2 DIMENSION MEASUREMENT


The following uncertainties apply to the dimension measurements:

Length (mm)	Expanded Uncertainty on Length
0 - 300	0.20 mm

5.3 VALIDATION MEASUREMENT

The guidelines outlined in the IEEE 1528 and CEI/IEC 62209 standards were followed to generate the measurement uncertainty for validation measurements.

Scan Volume	Expanded Uncertainty
1 g	19 % (SAR)
10 g	19 % (SAR)

6 CALIBRATION MEASUREMENT RESULTS**6.1 RETURN LOSS**



SAR REFERENCE WAVEGUIDE CALIBRATION REPORT

Ref. ACR.60.10.21.MVGB.A

Frequency (MHz)	Return Loss (dB)	Requirement (dB)	Impedance
5200	-9.15	-8	$21.17 \Omega + 13.26 j\Omega$
5400	-13.75	-8	$68.57 \Omega + 6.68 j\Omega$
5600	-16.65	-8	$35.76 \Omega - 2.15 j\Omega$
5800	-14.30	-8	$54.74 \Omega + 18.27 j\Omega$

6.2 MECHANICAL DIMENSIONS

Frequency (MHz)	L (mm)		W (mm)		L _f (mm)		W _f (mm)	
	Required	Measured	Required	Measured	Required	Measured	Required	Measured
5800	40.39 ± 0.13	-	20.19 ± 0.13	-	81.03 ± 0.13	-	61.98 ± 0.13	-




Figure 1: Validation Waveguide Dimensions

7 VALIDATION MEASUREMENT

The IEEE Std. 1528 and CEI/IEC 62209 standards state that the system validation measurements must be performed using a reference waveguide meeting the fore mentioned return loss and mechanical dimension requirements. The validation measurement must be performed with the matching layer placed in the open end of the waveguide, with the waveguide and matching layer in direct contact with the phantom shell.



SAR REFERENCE WAVEGUIDE CALIBRATION REPORT

Ref: ACR.60.10.21.MVGB.A

Measurement Condition

Software	OPEN SAR V5
Phantom	SN 13/09 SAM68
Probe	SN 41/18 EPGO333
Liquid	Head Liquid Values 5200 MHz: eps' :34.06 sigma : 4.70 Head Liquid Values 5400 MHz: eps' :33.39 sigma : 4.91 Head Liquid Values 5600 MHz: eps' :32.77 sigma : 5.13 Head Liquid Values 5800 MHz: eps' :32.40 sigma : 5.34
Distance between dipole waveguide and liquid	0 mm
Area scan resolution	dx=8mm/dy=8mm
Zoon Scan Resolution	dx=4mm/dy=4m/dz=2mm
Frequency	5200 MHz 5400 MHz 5600 MHz 5800 MHz
Input power	20 dBm
Liquid Temperature	20 +/- 1 °C
Lab Temperature	20 +/- 1 °C
Lab Humidity	30-70 %



SAR REFERENCE WAVEGUIDE CALIBRATION REPORT

Ref. ACR.60.10.21.MVGB.A

7.1 HEAD LIQUID MEASUREMENT

Frequency MHz	Relative permittivity (ϵ_r')		Conductivity (σ) S/m	
	required	measured	required	measured
5000	36.2 ±10 %		4.45 ±10 %	
5100	36.1 ±10 %		4.56 ±10 %	
5200	36.0 ±10 %	34.06	4.66 ±10 %	4.70
5300	35.9 ±10 %		4.76 ±10 %	
5400	35.8 ±10 %	33.39	4.86 ±10 %	4.91
5500	35.6 ±10 %		4.97 ±10 %	
5600	35.5 ±10 %	32.77	5.07 ±10 %	5.13
5700	35.4 ±10 %		5.17 ±10 %	
5800	35.3 ±10 %	32.40	5.27 ±10 %	5.34
5900	35.2 ±10 %		5.38 ±10 %	
6000	35.1 ±10 %		5.48 ±10 %	

7.2 MEASUREMENT RESULT




At those frequencies, the target SAR value can not be generic. Hereunder is the target SAR value defined by Satimo, within the uncertainty for the system validation. All SAR values are normalized to 1 W net power. In bracket, the measured SAR is given with the used input power.

Frequency (MHz)	1 g SAR (W/kg)		10 g SAR (W/kg)	
	required	measured	required	measured
5200	159.00	162.34 (16.23)	56.90	55.42 (5.54)
5400	166.40	168.48 (16.85)	58.43	57.03 (5.70)
5600	173.80	174.92 (17.49)	59.97	58.63 (5.86)
5800	181.20	178.89 (17.89)	61.50	59.32 (5.93)



SAR REFERENCE WAVEGUIDE CALIBRATION REPORT

Ref: ACR_60.10.21.MVGB.A


SAR MEASUREMENT PLOTS @ 5200 MHzSAR MEASUREMENT PLOTS @ 5400 MHzSAR MEASUREMENT PLOTS @ 5600 MHz



SAR REFERENCE WAVEGUIDE CALIBRATION REPORT

Ref: ACR_60.10.21.MVGB.A

SAR MEASUREMENT PLOTS @ 5800 MHz





SAR REFERENCE WAVEGUIDE CALIBRATION REPORT

Ref: ACR.60.10.21.MVGB.A

8 LIST OF EQUIPMENT

Equipment Summary Sheet

Equipment Description	Manufacturer / Model	Identification No.	Current Calibration Date	Next Calibration Date
Flat Phantom	MVG	SN-13/09-SAM68	Validated. No cal required.	Validated. No cal required.
COMOSAR Test Bench	Version 3	NA	Validated. No cal required.	Validated. No cal required.
Network Analyzer	Rohde & Schwarz ZVM	100203	05/2019	05/2022
Network Analyzer – Calibration kit	Rohde & Schwarz ZV-Z235	101223	05/2019	05/2022
Calipers	Mitutoyo	SN 0009732	10/2019	10/2022
Reference Probe	MVG	EPGO333 SN 41/18	05/2020	05/2021
Multimeter	Keithley 2000	1160271	02/2020	02/2023
Signal Generator	Rohde & Schwarz SMB	106589	04/2019	04/2022
Amplifier	Aethercomm	SN 046	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.
Power Meter	NI-USB 5680	170100013	05/2019	05/2022
Directional Coupler	Narda 4216-20	01386	Characterized prior to test. No cal required.	Characterized prior to test. No cal required.
Temperature / Humidity Sensor	Testo 184 H1	44220687	05/2020	05/2023